

Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

[manuals.plus](#) /

› [Lamp](#) /

› [Sugatsune Lamp HH-KL160 Pulls Instruction Manual](#)

Lamp HH-KL160

Sugatsune Lamp HH-KL160 Pulls Instruction Manual

Model: HH-KL160 | Material: 304 Stainless Steel | Finish: Satin

1. INTRODUCTION

This manual provides instructions for the proper installation, operation, and maintenance of the Sugatsune Lamp HH-KL160 Pulls. Please read this manual thoroughly before installation and retain it for future reference. This product is designed for use as a recessed pull handle for doors or drawers.



Image 1: The Sugatsune Lamp HH-KL160 Pull, a rectangular recessed handle made of satin-finished 304 stainless steel. The brand "LAMP" and material "SUS304" are subtly engraved on the surface.

2. SAFETY INFORMATION

Observe the following safety precautions to prevent injury or damage to the product:

- Ensure all components are present and undamaged before installation.
- Use appropriate tools for installation.
- Do not apply excessive force during installation or operation.
- Keep out of reach of children.

3. PACKAGE CONTENTS

Verify that all items are included in the package:

- 1x Sugatsune Lamp HH-KL160 Pull
- Mounting Screws (quantity as required for installation)

4. SPECIFICATIONS

Feature	Detail
Model Number	HH-KL160
Material	304 Stainless Steel
Finish	Satin
Product Dimensions	7 x 3.3 x 1.3 inches
Weight	9.6 ounces
Compliance	SEMI S8-0600, NSF certified, RoHS Compliant
Handle Type	Pull Handle

5. SETUP AND INSTALLATION

This section outlines the general steps for installing the HH-KL160 Pull. Specific installation requirements may vary based on the application (e.g., door, drawer, cabinet).

5.1 Tools Required

- Measuring Tape or Ruler
- Pencil or Marker
- Drill
- Appropriate Drill Bits (for pilot holes and recess)
- Screwdriver (compatible with mounting screws)
- Chisel or Router (for recess, if applicable)

5.2 Installation Steps

1. **Determine Placement:** Carefully select the desired location for the pull handle on your door or drawer. Mark the center points for the mounting screws and the outline for the recessed area.
2. **Prepare Recess (if required):** If the pull is to be flush-mounted, create a recess in the material according to the dimensions of the pull's body. Ensure the depth is sufficient for the pull to sit flush or slightly proud as desired.

- 3. Drill Pilot Holes:** Drill pilot holes for the mounting screws at the marked locations. Ensure the drill bit size is appropriate for the screws to prevent splitting the material.
- 4. Position the Pull:** Place the HH-KL160 Pull into the prepared recess (if applicable) and align the screw holes with the pilot holes.
- 5. Secure the Pull:** Insert the mounting screws and tighten them securely. Do not overtighten, as this can damage the pull or the mounting surface.
- 6. Test Operation:** Gently pull the handle to ensure it is firmly attached and operates smoothly.

6. OPERATING INSTRUCTIONS

The Sugatsune Lamp HH-KL160 Pull is a static handle designed for manual operation. To use, simply grasp the recessed area and apply gentle force to open or close the door or drawer it is attached to.

- Avoid using excessive force, which could damage the handle or the mounting surface.
- Do not use the handle for purposes other than its intended function (e.g., as a climbing aid).

7. CARE AND MAINTENANCE

To ensure the longevity and appearance of your HH-KL160 Pull, follow these maintenance guidelines:

- **Cleaning:** Wipe the surface regularly with a soft, damp cloth. For stubborn marks, use a mild soap solution and then dry thoroughly. Avoid abrasive cleaners, harsh chemicals, or scouring pads, as these can damage the satin finish.
- **Inspection:** Periodically check the mounting screws for tightness. If they become loose, gently retighten them.
- **Corrosion Prevention:** While 304 stainless steel is highly resistant to corrosion, prolonged exposure to harsh environments (e.g., saltwater, strong acids) should be avoided.

8. TROUBLESHOOTING

Problem	Possible Cause	Solution
Pull feels loose	Mounting screws are loose.	Gently tighten the mounting screws. Do not overtighten.
Scratches or dull finish	Abrasive cleaning, impact, or wear.	For minor scuffs, a stainless steel polish designed for satin finishes may help. Deep scratches may require professional attention or replacement. Prevent future damage by avoiding abrasive materials.
Difficulty installing	Incorrect measurements or tools.	Re-check measurements and ensure correct tools and drill bit sizes are used. Consult a professional if unsure.

9. WARRANTY AND SUPPORT

For information regarding warranty coverage or technical support for your Sugatsune Lamp HH-KL160 Pull, please refer to the official Sugatsune America website or contact their customer service directly. Keep your purchase receipt as proof of purchase.


Manufacturer: Sugatsune America

Website: www.sugatsune.com

© 2023 Sugatsune America. All rights reserved. Information in this manual is subject to change without notice.

Related Documents - HH-KL160

	<p>Installation Guide for TL-1R-L3M Touch Control Lamp</p> <p>This installation guide provides details for the TL-1R-L3M lamp, highlighting its touch control, 3-way dimmable features, USB C+A charging ports, and power input specifications.</p>
	<p>Decorative Lamp User Guide: Instructions, Charging, and Care</p> <p>Concise user guide for a decorative table lamp, detailing operation, three color temperature settings, brightness adjustment, Type-C fast charging, and cleaning precautions. Includes information on returns and accessories.</p>
	<p>The Lamp Installation Instructions: Step-by-Step Guide</p> <p>Comprehensive guide for installing your new lamp, covering the installation procedure, essential maintenance tips, and important safety precautions. Features clear instructions for wiring and mounting.</p>
	<p>Lamp Installation Guide and Assembly Instructions</p> <p>Comprehensive guide for installing a new lamp, featuring essential safety cautions, a description of lamp components, and step-by-step assembly instructions.</p>
	<p>Product Installation Diagram - NO:9943-800, SKU:DS-SZ59-2300259001</p> <p>Installation guide and precautions for product NO:9943-800, SKU:DS-SZ59-2300259001. Includes steps for mounting, wiring, and attaching decorative parts.</p>



T8856BU-LM-C Lamp Assembly Instructions

Step-by-step assembly instructions for the T8856BU-LM-C lamp, detailing installation without a junction box, wiring guidance, and parts identification.