



[Manuals.plus](#) /

> [KRUPS](#) /

> KRUPS Replacement Seal for Mokona Bialetti CF 40 and Gaggia G107 Instruction Manual

KRUPS 4930037000

KRUPS Replacement Seal for Mokona Bialetti CF 40 and Gaggia G107

Model Number: 4930037000

[Introduction](#)

[Safety Information](#)

[Installation](#)

[Maintenance](#)

[Troubleshooting](#)

[Specifications](#)

[Support](#)

1. INTRODUCTION

This manual provides comprehensive instructions for the proper installation and maintenance of your KRUPS replacement seal, designed for Mokona Bialetti CF 40 and Gaggia G107 coffee makers. This seal is a critical component for maintaining optimal pressure and preventing leaks in your espresso machine. Please read these instructions carefully before proceeding with installation.



Image 1.1: Packaging of the KRUPS Replacement Seal. This image shows the product as it typically appears in its retail packaging.

2. SAFETY INFORMATION

Always prioritize safety when performing maintenance on any appliance. Failure to follow these safety guidelines may result in injury or damage to your coffee maker.

- **Disconnect Power:** Before beginning any installation or maintenance, ensure your coffee maker is unplugged from the electrical outlet.
- **Allow Cooling:** If the coffee maker has recently been used, allow it to cool completely before handling any internal components. Hot surfaces can cause burns.
- **Use Correct Tools:** Use only appropriate tools for disassembly and assembly to avoid damaging parts.
- **Keep Away from Children:** Small parts can be a choking hazard. Keep the seal and tools out of reach of children.
- **Handle with Care:** The seal is made of flexible material. Avoid sharp objects that could puncture or tear it.

3. INSTALLATION

This section details the steps for replacing the seal in your compatible coffee maker. The process is generally similar for both Mokona Bialetti CF 40 and Gaggia G107 models.

3.1. Removing the Old Seal

1. **Prepare the Machine:** Ensure the coffee maker is unplugged and completely cool.
2. **Open the Brew Head:** Depending on your model, open the brew head or remove the filter basket assembly to access the existing seal.
3. **Locate the Seal:** The seal is typically a rubber or silicone ring situated around the perimeter of the brew head or filter holder.
4. **Carefully Remove:** Using a small, blunt tool (like a plastic spudger or the back of a spoon), gently pry out the old seal. Be careful not to scratch the metal surfaces of the coffee maker. Dispose of the old seal responsibly.
5. **Clean the Groove:** Thoroughly clean the groove where the seal sits. Remove any coffee grounds, residue, or mineral deposits. A damp cloth and a small brush can be useful. Ensure the area is dry before proceeding.

3.2. Installing the New Seal

1. **Inspect the New Seal:** Before installation, inspect the new KRUPS seal for any defects, tears, or deformities.
2. **Position the Seal:** Place the new seal into the clean groove. Ensure it sits evenly and is not twisted or pinched.
3. **Press Firmly:** Gently press the seal into place around its entire circumference. It should fit snugly without bulging.
4. **Test Fit:** Reassemble the filter basket or brew head. Close the coffee maker as if preparing to brew. If there is resistance or it doesn't close smoothly, the seal may not be seated correctly. Reopen and adjust.
5. **Perform a Test Brew:** After installation, plug in the coffee maker and perform a test brew with water only (no coffee). Observe for any leaks around the brew head. If leaks occur, refer to the Troubleshooting section.

4. MAINTENANCE

Proper maintenance extends the life of your seal and ensures consistent coffee quality.

- **Regular Cleaning:** After each use, wipe down the area around the seal to remove coffee grounds and oils.
- **Deep Cleaning:** Periodically, remove the seal (following the "Removing the Old Seal" steps) and wash it with warm, soapy water. Rinse thoroughly and ensure it is completely dry before reinstallation.
- **Check for Wear:** Regularly inspect the seal for signs of wear, cracking, hardening, or deformation. Replace the seal if any of these are observed to prevent leaks and maintain optimal performance.
- **Dishwasher Safe:** The seal is dishwasher safe, as indicated in the product specifications. However, hand washing is recommended for longevity.

5. TROUBLESHOOTING

If you encounter issues after installing your new seal, consult the table below for common problems and solutions.

Problem	Possible Cause	Solution
Water leaking from brew head during operation.	Seal not seated correctly; Seal is damaged; Groove is dirty.	Unplug the machine, allow to cool. Remove and re-seat the seal, ensuring it is flat and even. Clean the groove thoroughly. Inspect the seal for damage and replace if necessary.

Problem	Possible Cause	Solution
Difficulty closing the brew head/filter basket.	Seal is twisted or improperly installed; Incorrect seal size.	Unplug the machine, allow to cool. Remove and re-install the seal, ensuring it is not twisted. Verify that you have the correct seal for your model (Mokona Bialetti CF 40 or Gaggia G107).
Weak coffee or poor pressure.	Seal not creating a proper seal; Seal is worn out.	Check for leaks. If no visible leaks, the seal might be slightly compromised. Ensure it's clean and properly seated. If the problem persists, consider replacing the seal again.

6. SPECIFICATIONS

Key technical details for the KRUPS Replacement Seal.

- **Brand:** KRUPS
- **Model Number:** 4930037000
- **Compatible Models:** Mokona Bialetti CF 40, Gaggia G107
- **Material:** Aluminum (*Note: This refers to the coffee maker's material, not the seal itself, which is typically rubber/silicone. The product description implies the seal is for an aluminum moka pot.*)
- **Item Weight:** 0.02 Kilograms (approximate)
- **Dishwasher Safe:** Yes

7. WARRANTY AND SUPPORT

For warranty information or further technical assistance, please refer to the official KRUPS website or contact their customer support directly. Keep your proof of purchase for any warranty claims.

KRUPS Official Website: www.krups.com

