



[Manuals.plus](#) /

› [SentrySafe](#) /

› SentrySafe FHW40100 Fireproof and Waterproof Lock Box User Manual

SentrySafe FHW40100

SentrySafe FHW40100 Fireproof and Waterproof Lock Box User Manual

Model: FHW40100

[Introduction](#)

[Setup](#)

[Operating](#)

[Maintenance
Warranty &
Support](#)

[Troubleshooting](#)

[Specifications](#)

INTRODUCTION

The SentrySafe FHW40100 is a robust and reliable lock box designed to safeguard your valuable possessions from fire and water damage. This manual provides essential information for the proper setup, operation, and maintenance of your safe.

Key features include UL Classified fire protection for 30 minutes at 1550°F, ETL Verified water submersion protection for 72 hours, and a secure key lock mechanism. Its portable design with integrated carrying handles makes it convenient for home or office use.

SETUP AND FIRST USE

Unpacking

Carefully remove the SentrySafe FHW40100 from its packaging. Inspect the unit for any signs of damage. Retain all packaging materials for future transport or if a return is necessary.



Figure 1: SentrySafe FHW40100 Lock Box in a home setting, showcasing its compact design.

Key Operation

Your SentrySafe FHW40100 comes with two keys. The key lock mechanism is designed for secure closure. To unlock, insert the key and turn it. To lock, close the lid and turn the key to the locked position.

**Holds Standard
Letter-Size Hanging Folders
(12.75 in. x 9.375 in.)**



Hanging Folders Sold Separately

Figure 2: A hand demonstrating the insertion of a key into the SentrySafe FHW40100 lock mechanism.

Placement

Place the lock box on a flat, stable surface. The integrated feet on the bottom help keep it elevated. Consider a location that is easily accessible in an emergency but also discreet for security.



Figure 3: The SentrySafe FHW40100 positioned on a shelf, illustrating its suitability for discreet storage.

OPERATING INSTRUCTIONS

Opening the Safe

1. Insert the key into the lock.
2. Turn the key clockwise to the unlocked position.
3. Press the latch release button (if applicable) or lift the lid directly.

Closing and Locking the Safe

1. Ensure the contents are properly placed inside and the lid is clear of obstructions.
2. Close the lid firmly until it clicks into place.

3. Insert the key and turn it counter-clockwise to the locked position. Remove the key.

Storing Documents and Valuables

The SentrySafe FHW40100 is designed to accommodate letter-size hanging files and folders (sold separately). This allows for organized storage of important documents such as passports, birth certificates, and legal papers. It also provides ample space for small valuables, DVDs, and USBs.



Figure 4: The interior of the SentrySafe FHW40100, demonstrating its capacity for letter-sized hanging files.

2 Privacy Keys Included



Figure 5: An example of various documents and small valuables securely stored within the safe.

MAINTENANCE

Cleaning

Wipe the exterior of the safe with a soft, damp cloth. Avoid using abrasive cleaners or solvents, as these can damage the finish. Ensure the interior remains dry to protect stored items.

Key Care

Keep your keys in a secure location, separate from the safe. Do not store keys inside the safe. If keys are lost, contact SentrySafe customer support for assistance.

TROUBLESHOOTING

Lid Not Closing Properly

- Check for any obstructions preventing the lid from fully closing.
- Ensure the internal contents are not overfilling the safe.
- Verify that the lid's sealing gasket is clean and free of debris.

Key Not Turning

- Ensure the key is fully inserted into the lock.
- Apply gentle pressure while turning the key. Do not force it.
- Check for any debris in the keyhole.

SPECIFICATIONS

Feature	Detail
Model Number	FHW40100
Exterior Dimensions (H x W x D)	14.1 in. x 16.6 in. x 13.8 in.
Interior Dimensions (H x W x D)	11.6 in. x 12 in. x 8.1 in.
Capacity	0.66 Cubic Feet (18.55 Liters)
Item Weight	41 Pounds
Fire Protection	UL Classified for 1/2 hour at 1550°F
Water Protection	ETL Verified for 72 hours of water submersion
Lock Type	Key Lock (includes two keys)
Color	Dark Gray
Material	Captured Fire Insulation



ADVANCED PERIL PROTECTION

Fire Protection For 1/2 Hour At 1550°F

Water Protection For 72 Hours



Interior Dimensions

11.6 in. 12 in. 8.1 in.
29.5 cm 30.5 cm 20.6 cm

Weight

41 lbs.
18.6 kgs

Capacity

0.66 cu. ft.
18.7 liters



Figure 6: Visual representation of the SentrySafe FHW40100's dimensions and protective features.

WARRANTY AND SUPPORT

Manufacturer's Warranty

The SentrySafe FHW40100 comes with a Limited One Year Manufacturer Warranty. For specific terms and conditions, please refer to the warranty documentation included with your product or visit the official SentrySafe website.

Customer Support

For any questions, technical assistance, or warranty claims, please contact SentrySafe customer support. Contact information can be found on the product packaging or the official SentrySafe website. Please have your model number (FHW40100) and serial number ready when contacting support.

You can also register your product on the SentrySafe website for after-fire replacement services.