

Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

manuals.plus /

› [Rust-Oleum](#) /

› [Rust-Oleum 280699 American Accents Ultra Cover 2X Spray Paint, Gloss Sun Yellow User Manual](#)

Rust-Oleum 280699

Rust-Oleum American Accents Ultra Cover 2X Spray Paint User Manual

Model: 280699 - Gloss Sun Yellow

[Preparation](#) [Application](#) [Introduction](#) [Safety Information](#) [Setup & Specifications](#) [Maintenance](#) [Troubleshooting](#) [Warranty & Support](#)

1. INTRODUCTION

This manual provides instructions for the proper use and care of your Rust-Oleum American Accents Ultra Cover 2X Spray Paint, Model 280699, in Gloss Sun Yellow. This product is designed for interior and exterior use on various surfaces, offering enhanced coverage and durability. Please read all instructions carefully before use to ensure safe and effective application.



Image 1.1: Rust-Oleum American Accents Ultra Cover 2X Spray Paint can, Gloss Sun Yellow.

2. SAFETY INFORMATION

Always prioritize safety when using spray paint. Failure to follow these warnings may result in serious injury or property damage.

- **Ventilation:** Use in a well-ventilated area. Avoid breathing vapors. If used indoors, open windows and doors and use a fan to ensure fresh air movement.
- **Flammability:** This product is extremely flammable. Keep away from heat, sparks, open flames, and other ignition sources. Do not smoke while using.
- **Eye Protection:** Wear safety glasses with side shields during application to protect eyes from paint mist.
- **Skin Protection:** Wear chemical-resistant gloves and protective clothing to prevent skin contact. Wash hands thoroughly after handling.
- **Respiratory Protection:** If ventilation is inadequate, wear an appropriate NIOSH-approved respirator.
- **Keep Out of Reach of Children:** Store in a secure location away from children and pets.

- **Disposal:** Dispose of empty cans and unused paint according to local regulations. Do not puncture or incinerate cans, even when empty.

3. SETUP & PREPARATION

Proper preparation is key to achieving optimal results and durability.

1. Surface Preparation:

- Ensure the surface is clean, dry, and free of loose rust, dirt, oil, grease, wax, and old paint.
- Lightly sand glossy surfaces to create a profile for better adhesion.
- For bare wood, metal, or plastic, a primer may be used for best results, though this product contains paint and primer in one.

2. Environmental Conditions:

- Apply when temperature is between 10°C (50°F) and 32°C (90°F) and humidity is below 85% to ensure proper drying.
- Avoid spraying in windy conditions to prevent overspray.

3. **Protect Surrounding Areas:** Mask off adjacent areas and cover surrounding objects to protect from overspray.

4. **Shake Can:** Shake the can vigorously for one minute after the mixing ball begins to rattle. Continue to shake occasionally during use.

4. APPLICATION

Follow these steps for effective paint application.

1. **Hold Can Correctly:** Hold the can upright 25-30 cm (10-12 inches) from the surface.

2. **Spray Technique:** Press the spray button firmly and apply paint with steady, even strokes. Overlap each stroke slightly.

3. **Multiple Coats:** Apply two or more light coats a few minutes apart rather than one heavy coat to avoid drips and runs.

4. Drying Time:

- Dries to touch in 20 minutes.
- Handle in 1 hour.
- Fully dry in 24 hours.
- Recoat within 1 hour or after 24 hours.



Image 4.1: Demonstration of proper spray technique. Hold the can upright and apply with even strokes.

5. MAINTENANCE

Proper maintenance ensures the longevity of your spray paint can and nozzle.

- **Cleaning the Nozzle:** After each use, invert the can and spray for 5 seconds or until only clear gas comes out. This clears the nozzle and prevents clogging.
- **Storage:** Store the can in a cool, dry place away from direct sunlight and temperatures above 49°C (120°F).

6. TROUBLESHOOTING

Problem	Possible Cause	Solution
Clogged Nozzle	Paint dried in the nozzle.	Remove the nozzle and soak it in mineral spirits or paint thinner. If severely clogged, replace with a new nozzle. Always clear the nozzle after use by inverting the can and spraying.
Uneven Spray/Spitting	Insufficient shaking; can too cold; nozzle partially clogged.	Shake the can vigorously for at least one minute before use and periodically during application. Warm the can to room temperature. Clean or replace the nozzle.
Drips or Runs	Applying too much paint in one coat; holding can too close to surface.	Apply several thin coats instead of one heavy coat. Maintain a distance of 25-30 cm (10-12 inches) from the surface.
Poor Adhesion	Improper surface preparation; surface too glossy.	Ensure surface is clean, dry, and properly sanded if glossy. Use a primer if necessary for challenging surfaces.

7. SPECIFICATIONS

- **Model Number:** 280699
- **Brand:** Rust-Oleum
- **Product Type:** American Accents Ultra Cover 2X Spray Paint
- **Color:** Gloss Sun Yellow
- **Finish:** Gloss

- **Size:** 12 g (Pack of 1) / 12 Fluid Ounces
- **Coverage:** Up to 12 sq ft
- **Drying Time (Touch):** 20 minutes
- **Usage:** Interior/Exterior
- **Manufacturer:** Rust-Oleum
- **Product Dimensions:** 6.65 x 6.65 x 20.02 cm; 453.59 g

8. WARRANTY & SUPPORT

For specific warranty information, product support, or to contact customer service, please refer to the official Rust-Oleum website or the contact information provided on the product label. Keep your purchase receipt for any warranty claims.

Rust-Oleum Official Website: www.rustoleum.com

