

Elements 351-96PC

Elements Calloway Collection 351-96PC Cabinet Pull Installation and Care Manual

Model: 351-96PC | Brand: Elements

1. INTRODUCTION

Thank you for choosing the Elements Calloway Collection 351-96PC Cabinet Pull. This manual provides detailed instructions for the safe and proper installation, use, and maintenance of your new cabinet hardware. Please read all instructions carefully before beginning installation and retain this manual for future reference.



Figure 1: The Elements Calloway Collection 351-96PC cabinet pull, featuring a polished chrome finish and a distinctive stepped square design. This image displays the pull from a front-facing perspective, highlighting its curved profile and tiered detailing.

2. SAFETY INFORMATION

- Always wear appropriate safety gear, such as safety glasses, when drilling or using tools.
- Ensure the work area is well-lit and clear of obstructions.
- Keep small parts, such as screws, out of reach of children and pets.
- Handle tools with care to prevent injury.

3. PACKAGE CONTENTS

Verify that all components are present before beginning installation. If any parts are missing or damaged, please contact customer support.

- 1x Elements Calloway Collection 351-96PC Cabinet Pull (Polished Chrome)
- 2x Mounting Screws (appropriate length for standard cabinet doors/drawers)

4. TOOLS REQUIRED

The following tools are recommended for installation:

- Measuring Tape or Ruler
- Pencil
- Drill
- Drill Bit (appropriate size for mounting screws, typically 3/16" or 5mm)
- Screwdriver (Phillips head or flathead, depending on screw type)
- Cabinet Hardware Jig (optional, for precise hole placement)

5. INSTALLATION (SETUP)

Follow these steps to install your cabinet pull:

1. **Determine Placement:** Decide on the desired location for your pull on the cabinet door or drawer. For doors, pulls are typically placed on the stile opposite the hinges. For drawers, they are usually centered horizontally and vertically.
2. **Mark Hole Centers:** Using a measuring tape or ruler, mark the two points where the screws will pass through the cabinet surface. The center-to-center spacing for this pull is 96mm (approximately 3.75 inches). Ensure your marks are level and accurately spaced. A cabinet hardware jig can assist with this step.
3. **Drill Pilot Holes:** Carefully drill pilot holes at the marked locations. Use a drill bit slightly smaller than the diameter of the mounting screws to prevent splitting the wood. Drill straight through the cabinet door or drawer front.
4. **Attach the Pull:** Align the pull with the drilled holes. Insert the mounting screws from the back side of the cabinet door or drawer front, through the pilot holes, and into the threaded receivers on the pull.
5. **Tighten Screws:** Using a screwdriver, carefully tighten the screws until the pull is secure. Do not overtighten, as this can strip the threads or damage the cabinet surface.



Figure 2: A side view of the Elements Calloway Collection 351-96PC cabinet pull, illustrating its depth and the stepped design from a different angle.

This perspective helps in understanding how the pull will sit on a cabinet surface.

6. MAINTENANCE

To ensure the longevity and appearance of your Elements cabinet pull, follow these maintenance guidelines:

- **Cleaning:** Wipe the pull regularly with a soft, damp cloth. For more thorough cleaning, use a mild soap and water solution. Avoid abrasive cleaners, harsh chemicals, or scouring pads, as these can damage the polished chrome finish.
- **Polishing:** If desired, a non-abrasive metal polish specifically designed for chrome finishes can be used to restore luster. Always test on an inconspicuous area first.
- **Tightening:** Periodically check the mounting screws for tightness. If a pull feels loose, gently tighten the screws with a screwdriver. Do not overtighten.

7. TROUBLESHOOTING

Problem	Possible Cause	Solution
Pull feels loose	Mounting screws are loose.	Gently tighten the mounting screws from the back of the cabinet door/drawer. Do not overtighten.
Pull is crooked	Holes were drilled off-center or not level.	If possible, slightly adjust the pull before fully tightening. If the issue persists, consider filling the old holes and re-drilling with a template for accuracy.
Scratches or dull finish	Abrasive cleaning agents or general wear.	Clean with a soft cloth and mild soap. For minor dullness, use a chrome-specific non-abrasive polish. Avoid harsh chemicals.

8. SPECIFICATIONS

Model Number	351-96PC
Brand	Elements
Collection	Calloway Collection
Finish	Polished Chrome
Material	Metal, Zinc
Center-to-Center Spacing	96 mm (3.75 inches)
Overall Length	4.44 inches (approx. 11.28 cm)
Projection (Depth)	1.06 inches (approx. 2.69 cm)
Width	0.69 inches (approx. 1.75 cm)
Item Weight	3.04 ounces (approx. 86 grams)
Included Components	Cabinet Pull, Mounting Screws

9. WARRANTY AND SUPPORT

Elements products are manufactured to high-quality standards. For specific warranty information or technical support, please refer to the official Elements website or contact their customer service department. Keep your purchase receipt for warranty claims. For further assistance, please visit: [Elements Official Website](#)

© 2023 Elements. All rights reserved.

Ask a question about this manual

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page’s manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. [Privacy details](#).

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question