

## Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

### Manuals.plus /

› [Haws](#) /

› Haws SP95 P-Trap Instruction Manual for Wall Mounted Eye and Face Wash Units

## Haws SP95

# Haws SP95 P-Trap Instruction Manual

For Wall Mounted Eye and Face Wash Units

## 1. PRODUCT OVERVIEW

The Haws SP95 P-Trap is a critical component designed for use with wall-mounted eye and face wash units. It functions to prevent sewer gases from entering the building while allowing wastewater to drain. This model features a durable satin chrome-plated brass construction, ensuring reliability and longevity in emergency response applications.



Image 1: The Haws SP95 P-Trap, showing its chrome-plated brass construction and typical P-trap shape for drainage systems.

## 2. SPECIFICATIONS

Feature	Detail
Model Number	SP95
Material	Satin Chrome-Plated Brass
Inlet Size	1-1/4" O.D.
Outlet Size	1-1/2" Iron Pipe Size
Item Weight	2 pounds
Product Dimensions	1 x 1 x 1 inches (Approximate)
Color	Chrome
Manufacturer	Haws

### 3. INSTALLATION AND SETUP

Installation of the Haws SP95 P-Trap should be performed by a qualified plumber or technician in accordance with local plumbing codes and manufacturer instructions for the associated eye/face wash unit. Proper installation is essential for the safety and functionality of the emergency equipment.

- 1. Preparation:** Ensure all necessary tools and additional plumbing components are available. Turn off the water supply to the area before beginning installation to prevent water damage.
- 2. Connection to Eye/Face Wash Unit:** Connect the 1-1/4" O.D. inlet of the P-trap to the drain outlet of the wall-mounted eye or face wash unit. Use appropriate gaskets and fittings to ensure a watertight seal.
- 3. Connection to Waste Line:** Connect the 1-1/2" Iron Pipe Size outlet of the P-trap to the building's waste drainage system. Verify that all connections are secure and leak-free.
- 4. Testing:** Once all connections are made, slowly turn on the water supply. Activate the eye/face wash unit to flush water through the system. Carefully inspect all connections for any signs of leaks.
- 5. Final Check:** Verify that the P-trap is properly aligned and secured, and that water drains freely without obstruction. Ensure the P-trap holds water to prevent sewer gas entry.

**Important:** Proper installation is crucial for the effective operation of the eye/face wash unit and to prevent plumbing issues. If you are unsure about any step, consult a professional.

### 4. MAINTENANCE

Regular maintenance helps ensure the longevity and proper function of the P-trap, which is vital for emergency eye and face wash units.

- **Routine Inspection:** Periodically inspect the P-trap and its connections for any signs of leaks, corrosion, or damage. Address any issues promptly.
- **Cleaning:** If the eye/face wash unit is used frequently, or if drainage slows, the P-trap may accumulate debris. It can be disassembled and cleaned manually. Ensure to reassemble with new gaskets if necessary to maintain a watertight seal.
- **Gasket Replacement:** Gaskets and seals can degrade over time. Replace them as needed to prevent leaks and maintain proper function.
- **Flushing:** Regularly flush the eye/face wash unit to ensure the P-trap remains filled with water, preventing sewer gases from entering the facility.

## 5. TROUBLESHOOTING

---

Common issues related to P-traps and their potential solutions:

- **Slow Drainage:** This often indicates a partial clog. Try cleaning the P-trap as described in the Maintenance section. Avoid using harsh chemical drain cleaners, as they can damage plumbing components and the P-trap material.
- **Leaks at Connections:** Check if the connections are tight. If tightening does not resolve the leak, the gaskets may be worn or improperly seated and require replacement.
- **Sewer Gas Odor:** If a foul odor is detected, it may indicate that the P-trap is dry (not holding water) or improperly installed. Ensure the eye/face wash unit is flushed regularly to keep the trap filled with water. If the problem persists, consult a plumber.

## 6. SAFETY INFORMATION

---

- Always turn off the main water supply before performing any installation or maintenance on plumbing fixtures to prevent accidental water flow.
- Wear appropriate personal protective equipment (PPE), such as gloves and eye protection, during installation and maintenance to ensure personal safety.
- Ensure all connections are properly sealed to prevent water damage and potential hazards from leaks.
- If you are not experienced with plumbing, it is highly recommended to seek professional assistance for installation and complex repairs to ensure compliance with safety standards and proper function.

## 7. WARRANTY AND SUPPORT

---

For information regarding product warranty, technical support, or replacement parts for your Haws SP95 P-Trap, please contact Haws customer service directly or visit their official website. Retain your purchase receipt for warranty claims and proof of purchase.

**Manufacturer:** Haws