Duravit 2551090092

Duravit DuraStyle Wall Mounted Toilet User Manual

Model: 2551090092 | Brand: Duravit

Introduction

Thank you for choosing the Duravit DuraStyle Wall Mounted Toilet. This manual provides essential information for the safe and efficient installation, operation, and maintenance of your new toilet. Please read this manual thoroughly before installation and keep it for future reference.

Important Safety Information

Always adhere to local plumbing codes and regulations during installation. Professional installation is highly recommended to ensure proper function and safety.

- Ensure all water supply lines are shut off before beginning installation.
- Wear appropriate personal protective equipment (PPE) such as gloves and eye protection.
- The toilet is made of ceramic and can be heavy. Handle with care to prevent injury or damage.
- Do not use abrasive cleaners or tools that could scratch the ceramic surface.

Setup and Installation

The Duravit DuraStyle is a wall-mounted toilet designed for a rear outlet connection. Installation typically involves mounting the toilet to a concealed in-wall carrier system (sold separately) which houses the tank and flushing mechanism.

Pre-Installation Checklist:

- Verify all components are present and undamaged.
- Ensure the in-wall carrier system is correctly installed and secured according to its manufacturer's instructions.
- Confirm water supply and waste lines are properly roughed-in for a wall-mounted toilet.

Installation Steps (General Overview):

1. Attach the toilet to the mounting bolts protruding from the in-wall carrier.
2. Connect the waste outlet of the toilet to the drain pipe of the carrier system.
3. Connect the water supply line from the carrier to the toilet's inlet.
4. Secure the toilet firmly to the wall using the provided hardware.
5. Install the toilet seat (sold separately) according to its instructions.
6. Turn on the water supply and check for leaks.
7. Test the flushing mechanism.

Note: Detailed installation instructions for the in-wall carrier system and specific plumbing connections are provided by the carrier manufacturer and should be followed precisely.



Image: Front-right view of the Duravit DuraStyle Wall Mounted Toilet in White Alpin. This image shows the compact, sleek design of the toilet bowl and the closed lid, highlighting its wall-mounted configuration.

Operating Instructions

The Duravit DuraStyle Wall Mounted Toilet features a dual-flush system, designed for water efficiency. The flush mechanism is typically operated via a flush plate installed on the wall above the toilet, which is connected to the in-wall carrier.

Flushing:

- **Full Flush:** Press the larger button or section of the flush plate for a full flush (e.g., for solid waste).
- **Half Flush:** Press the smaller button or section of the flush plate for a reduced flush (e.g., for liquid waste), conserving water.

Ensure the flush plate is properly installed and calibrated according to its manufacturer's instructions for optimal performance.

Maintenance and Care

Regular cleaning and proper care will ensure the longevity and pristine appearance of your Duravit DuraStyle toilet.

Cleaning the Ceramic Surface:

- Use a soft cloth or sponge with mild, non-abrasive bathroom cleaners.
- Avoid cleaners containing harsh chemicals, abrasive powders, or scouring pads, as these can damage the ceramic glaze.
- Rinse thoroughly with clean water after cleaning and wipe dry to prevent water spots.

Cleaning the Toilet Seat:

- Clean the toilet seat with mild soap and water.
- Do not use harsh chemical cleaners, as they may discolor or damage the seat material (Plastic).

General Tips:

- Periodically check all connections for leaks and tighten if necessary.
- If the flush performance diminishes, consult the in-wall carrier manual for adjustments or troubleshooting related to the internal mechanism.

Troubleshooting

This section addresses common issues you might encounter. For complex problems, it is recommended to contact a qualified plumber.

Problem	Possible Cause	Solution
Toilet not flushing or weak flush	Low water level in tank, clogged rim jets, issue with flush valve in carrier.	Check water supply to carrier. Consult carrier manual for water level adjustment or flush valve inspection. Clean rim jets if accessible.
Continuous running water	Faulty fill valve or flush valve in carrier.	Inspect and adjust or replace fill/flush valve components within the in-wall carrier as per its manual.
Leaks around the toilet base	Loose mounting bolts, improper seal at waste connection.	Ensure mounting bolts are securely tightened. Re-seat the toilet if necessary, ensuring proper sealing at the waste outlet. Professional assistance may be required.

Product Specifications

Feature	Detail
Model Number	2551090092
Brand	Duravit
Color	White Alpin
Product Dimensions	14"D x 14.63"W x 14"H
Material	Ceramic
Item Weight	80.4 Pounds
Installation Type	Wall-Mount
Outlet Type	Rear
Flush Type	Dual Flush Toilets
Special Features	Eco Friendly
Included Components	Item included Only, Hardware (Toilet seat sold separately)

Warranty and Support

Duravit products are manufactured to the highest quality standards and come with a manufacturer's warranty. For specific warranty details, including coverage and duration, please refer to the warranty documentation provided with your purchase or visit the official Duravit website.
For technical support, replacement parts, or further assistance, please contact Duravit customer service or your authorized dealer.

- **Manufacturer:** Duravit
- **Website:** www.duravit.us (Example link, actual link may vary)
- **Customer Service:** Refer to Duravit's official website for contact information.

© 2024 Duravit. All rights reserved. Information subject to change without notice.