

Pyle PDBT35

Pyle PDBT35 1-inch Titanium Super Tweeter Instruction Manual

Model: PDBT35 | Brand: Pyle

Contents	Features	Setup	Introduction	Safety Instructions	Package		
			Operating	Maintenance	Troubleshooting	Specifications	Warranty & Support

1. INTRODUCTION

Thank you for purchasing the Pyle PDBT35 1-inch Titanium Super Tweeter. This unit is designed to enhance the high-frequency response of your audio system, providing clear and crisp treble. This manual provides essential information for the proper installation, operation, and maintenance of your tweeter. Please read it thoroughly before use and retain it for future reference.



Figure 1: Pyle PDBT35 1-inch Titanium Super Tweeter. This image shows the compact, metallic horn-shaped tweeter unit.

2. SAFETY INSTRUCTIONS

- **Power Off:** Always disconnect power to your audio system before installing or servicing the tweeter.
- **Correct Wiring:** Ensure correct polarity when connecting the tweeter to avoid damage to the unit or your amplifier.
- **Impedance Matching:** Verify that the tweeter's impedance (4-8 Ohms) is compatible with your amplifier's output.
- **Overpowering:** Avoid exceeding the maximum power handling (500W MAX) to prevent damage. Use a suitable crossover to protect the tweeter from low frequencies.
- **Mounting:** Securely mount the tweeter to prevent it from becoming a projectile in case of sudden stops or accidents.
- **Professional Installation:** If you are unsure about any installation steps, consult a qualified audio technician.

3. PACKAGE CONTENTS

Please check the package for the following items:

- Pyle PDBT35 1-inch Titanium Super Tweeter Unit
- Crossover Capacitor (3.3uF)
- Mounting Hardware (screws, clips, etc. - *if included, check packaging*)
- Instruction Manual (this document)

4. KEY FEATURES

- Short horn tweeter utilizing a titanium diaphragm for crisp high-frequency reproduction.
- Equipped with a powerful neodymium magnet motor structure for high efficiency.
- High power handling: 125 Watts RMS / 500 Watts MAX.

- Includes a 3.3uF crossover capacitor for proper frequency filtering.
- Compact design with a metallic finish.

5. SETUP AND INSTALLATION

1. **Choose Mounting Location:** Select a suitable location in your vehicle or audio setup that allows for optimal sound dispersion and secure mounting. Ensure there is enough depth behind the mounting surface for the tweeter.
2. **Prepare Mounting Surface:** If flush mounting, carefully cut a hole of the appropriate diameter (refer to specifications for horn opening size) using a hole saw or similar tool. If surface mounting, mark and drill pilot holes for the mounting screws.
3. **Wiring Connections:**
 - Identify the positive (+) and negative (-) terminals on the tweeter.
 - Connect the included 3.3uF crossover capacitor in series with the positive (+) wire leading to the tweeter. The capacitor acts as a high-pass filter, protecting the tweeter from damaging low frequencies.
 - Connect the positive (+) wire (with capacitor) from your amplifier or existing crossover to the tweeter's positive terminal.
 - Connect the negative (-) wire from your amplifier or existing crossover to the tweeter's negative terminal.
 - Ensure all connections are secure and properly insulated to prevent short circuits.
4. **Secure the Tweeter:** Mount the tweeter securely using the provided hardware. Ensure it is firmly in place and does not vibrate.
5. **Test System:** Once installed, reconnect power to your audio system. Start with the volume low and gradually increase it, checking for proper sound output from the tweeter.

Note: The included 3.3uF capacitor provides a basic high-pass filter. For advanced systems, consider using a dedicated electronic crossover for more precise frequency control and protection.

6. OPERATING INSTRUCTIONS

The Pyle PDBT35 tweeter operates as a high-frequency sound reproducer within your audio system. Once properly installed and connected, it will automatically function when your audio system is powered on and playing sound.

- **Volume Control:** Adjust the overall volume of your audio system using your head unit or amplifier controls.
- **Tone Adjustments:** Use the treble control on your audio system to fine-tune the high-frequency output to your preference. Avoid excessive treble boost, which can lead to harsh sound or tweeter damage.
- **Listening Position:** Experiment with the tweeter's angle or position (if adjustable) to optimize the soundstage and imaging for your listening position.
- **Break-in Period:** Like many audio components, tweeters may benefit from a short "break-in" period. Play music at moderate volumes for several hours to allow the diaphragm to settle.

7. MAINTENANCE

The Pyle PDBT35 tweeter requires minimal maintenance to ensure long-lasting performance.

- **Cleaning:** Gently wipe the exterior of the tweeter with a soft, dry cloth to remove dust. Do not use harsh chemicals or abrasive cleaners.
- **Inspection:** Periodically check the mounting screws and wiring connections to ensure they remain secure.
- **Avoid Moisture:** Keep the tweeter away from excessive moisture or direct water exposure.

- **Temperature Extremes:** Avoid exposing the tweeter to extreme temperatures, which can affect its performance and lifespan.

8. TROUBLESHOOTING

Problem	Possible Cause	Solution
No sound from tweeter	Loose or incorrect wiring	Check all wiring connections for proper polarity and security.
	Blown fuse in amplifier	Inspect amplifier fuse and replace if necessary.
	Tweeter damaged	Test tweeter with a known good audio source (at low volume).
	Crossover capacitor faulty	Check capacitor for damage or replace.
Distorted or harsh sound	Overpowering the tweeter	Reduce volume. Ensure proper crossover is used.
	Incorrect crossover setting	Verify the 3.3uF capacitor is correctly installed.
	Excessive treble boost	Reduce treble settings on your audio system.
	Loose mounting	Check mounting for tightness.
Intermittent sound	Loose wiring connection	Inspect and secure all wiring connections.
	Faulty cable	Replace audio cables if suspected to be faulty.

9. SPECIFICATIONS

Model Number	PDBT35
Brand	Pyle
Tweeter Type	Horn Tweeter with Titanium Diaphragm
Horn Opening Size	Approx. 4.2 cm
Power Handling (RMS)	125 Watts
Power Handling (MAX)	500 Watts
Impedance	4-8 Ohms
Sound Pressure Level (SPL)	108 dB (at 4kHz)
Voice Coil Diameter	2.5 cm
External Dimensions (Diameter x Length)	60 mm x 70 mm
Weight (Packed)	0.6 kg
Magnet Type	Neodymium
Included Crossover	3.3uF Capacitor
Material	Aluminum
Color	Metallic

10. WARRANTY AND SUPPORT

Pyle products are designed for reliability and performance. For specific warranty information, please refer to the warranty card included with your product or visit the official Pyle website. Keep your purchase receipt as proof of purchase for any warranty claims.

For technical support, product inquiries, or service, please contact Pyle customer support through their official website or the contact information provided with your product documentation. When contacting support, please have your product model number (PDBT35) and purchase details ready.

© 2023 Pyle. All rights reserved. Information in this manual is subject to change without notice.

ASK A QUESTION ABOUT THIS MANUAL

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page’s manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. [Privacy details](#).

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question