

Top Knobs SS66

Top Knobs SS66 Pull Installation and Care Manual

Model: SS66

INTRODUCTION

This manual provides comprehensive instructions for the proper installation, care, and maintenance of your Top Knobs SS66 Polished Stainless Steel cabinet pull. Please read this guide thoroughly before beginning installation to ensure correct procedure and optimal performance.

SAFETY INFORMATION

Always exercise caution when working with tools. Wear appropriate personal protective equipment, such as safety glasses, to prevent injury. Keep small parts, such as screws, out of reach of children and pets. If you are unsure about any step, consult a professional.

PACKAGE CONTENTS

Verify that all components are present before beginning installation:

- 1 x Top Knobs SS66 Cabinet Pull (Polished Stainless Steel)
- 1 x M4 Screw Pack (typically two screws)

If any parts are missing or damaged, please contact your retailer or Top Knobs customer support.

INSTALLATION (SETUP)

Follow these steps to properly install your cabinet pull:

Tools Required:

- Measuring Tape or Ruler
- Pencil
- Drill

- Drill Bit (appropriate size for M4 screws, typically 3/16" or 5mm)
- Screwdriver (Phillips head)
- Optional: Cabinet Hardware Jig/Template for precise hole placement

Installation Steps:

1. **Measure and Mark:** Determine the desired location for your pull on the cabinet door or drawer. The SS66 pull has a center-to-center (c-c) measurement of 5-1/16 inches (129mm). Mark the two drill points precisely using a pencil. For multiple pulls, ensure consistent placement.
2. **Drill Holes:** Using the appropriate drill bit, carefully drill through the marked points. Ensure the drill is perpendicular to the cabinet surface to create straight holes.
3. **Attach Pull:** Align the pull with the drilled holes. Insert the M4 screws from the inside of the cabinet door or drawer through the drilled holes and into the threaded receivers on the back of the pull.
4. **Tighten Screws:** Using a Phillips head screwdriver, carefully tighten the screws until the pull is secure. Do not overtighten, as this can strip the threads or damage the cabinet surface.



Image: Front view of the Top Knobs SS66 Polished Stainless Steel cabinet pull, showcasing its sleek, rectangular design with rounded ends.



Image: Angled view of the Top Knobs SS66 Polished Stainless Steel cabinet pull, highlighting its projection from the mounting surface and the smooth finish.

OPERATION

The Top Knobs SS66 pull functions as a handle for opening and closing cabinet doors and drawers. Simply grasp the pull firmly and apply gentle force in the desired direction to operate the cabinet mechanism.

MAINTENANCE

To maintain the polished stainless steel finish and ensure the longevity of your pull:

- **Cleaning:** Wipe the pull regularly with a soft, damp cloth. For more thorough cleaning, use a mild soap and water solution. Avoid abrasive cleaners, harsh chemicals, or scouring pads, as these can damage the finish.
- **Polishing:** If desired, a non-abrasive stainless steel cleaner or polish can be used to restore luster. Always follow the product manufacturer's instructions.
- **Inspection:** Periodically check the tightness of the mounting screws. If the pull feels loose, gently retighten the screws with a Phillips head screwdriver.

TROUBLESHOOTING

Common issues and their solutions:

Problem	Possible Cause	Solution
Pull feels loose after installation.	Screws are not fully tightened.	Gently tighten the mounting screws with a Phillips head screwdriver. Do not overtighten.
Pull is crooked.	Holes were drilled off-center or misaligned.	If possible, slightly adjust the pull before fully tightening. If severely misaligned, new holes may need to be drilled, and old holes filled.
Scratches or dull finish.	Abrasive cleaning agents or tools used.	Use only soft cloths and mild, non-abrasive cleaners. For existing scratches, consult a professional or consider replacement if severe.

SPECIFICATIONS

Model Number:	SS66
Material:	Stainless Steel (SS304 base material)
Finish:	Polished Stainless Steel
Mounting Holes (c-c):	5-1/16 inches (129mm)
Overall Length:	5-1/2 inches (140mm)
Width:	1/2 inch (13mm)
Projection:	1-3/16 inches (30mm)
Base Diameter:	0.44 inches
Item Weight:	0.3 lbs (approx. 4.32 ounces)

Included Components:	Pull, M4 Screws
----------------------	-----------------

WARRANTY INFORMATION

The Top Knobs SS66 pull comes with a **Lifetime Warranty**. This warranty covers defects in material and workmanship under normal use. For specific details regarding warranty claims and coverage, please refer to the official Top Knobs warranty policy or contact their customer service.

SUPPORT

For further assistance, technical support, or inquiries regarding your Top Knobs SS66 pull, please contact:

- Your original retailer where the product was purchased.
- Top Knobs Customer Service (refer to their official website for contact details).

When contacting support, please have your product model number (SS66) and purchase information readily available.

© 2023 Top Knobs. All rights reserved.

ASK A QUESTION ABOUT THIS MANUAL

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page’s manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. [Privacy details](#).

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question

