

UPBRIGHT TBI Pro TBIPro TBI Bark Pro V3 Power

UpBright 5V AC/DC Adapter Charger and USB Charging Cable Cord User Manual

For TBI Pro TBIPro TBI Bark Pro V3 and SDS6 Dog Training Collars

1. INTRODUCTION

This manual provides essential instructions for the safe and effective use of your UpBright 5V AC/DC Adapter Charger and accompanying USB Charging Cable. This product is designed to provide reliable power for compatible devices, specifically the TBI Pro TBIPro TBI Bark Pro V3 Premium Smart Pet Dog Bark Control Collar and the SDS6 Shock Training Collar Rechargeable Transmitter Unit.

Please read this manual thoroughly before using the product to ensure proper operation and to prevent damage to the charger or your device.

2. SAFETY INFORMATION

- **Voltage Compatibility:** This adapter is designed for World Wide Input Voltage 100-240VAC 50/60Hz. Ensure your power outlet matches these specifications.
- **Protection Features:** The adapter includes Over Voltage Output Protection (OVP), Over Current Output Protection (OCP), and Short Circuit Output Protection (SCP) to safeguard your devices.
- **Proper Connection:** Always ensure the charging cable is securely connected to both the adapter and the device before plugging the adapter into a power outlet.
- **Indoor Use Only:** This product is intended for indoor use in dry conditions. Do not expose to water, moisture, or extreme temperatures.
- **Avoid Damage:** Do not use the adapter or cable if they appear damaged. Do not attempt to open or repair the unit. Contact support if damage occurs.
- **Unplug When Not in Use:** Disconnect the adapter from the power outlet when not in use for extended periods.

3. PRODUCT OVERVIEW

The UpBright 5V AC/DC Adapter Charger provides a stable 5V DC output for charging compatible electronic devices. It comes with a USB charging cable featuring a 5.5mm x 2.1mm barrel plug end, specifically designed for devices such as the TBI Pro TBIPro TBI Bark Pro V3 and SDS6 dog training collars.



Image 1: UpBright 5V AC/DC Adapter Charger and USB Cable. This image displays the compact wall adapter with a USB port and the included USB charging cable with a barrel connector.

4. SETUP

1. **Unpack Components:** Carefully remove the AC/DC adapter and USB charging cable from their packaging.
2. **Connect USB Cable to Adapter:** Insert the USB-A end of the charging cable into the USB port on the UpBright AC/DC adapter. Ensure it is fully seated.
3. **Connect to Device:** Insert the barrel connector end (5.5mm x 2.1mm plug) of the USB charging cable into the charging port of your compatible device (e.g., TBI Pro TBIPRO TBI Bark Pro V3 or SDS6 collar). Ensure a snug fit.
4. **Plug into Power Outlet:** Insert the AC/DC adapter into a standard wall power outlet (100-240VAC).

5. OPERATING INSTRUCTIONS

Once the adapter and cable are properly connected to your device and a power outlet, the device should begin charging. Refer to your device's specific user manual for indicators of charging status (e.g., LED lights).

- **Charging Time:** Charging times will vary depending on the device's battery capacity and its current charge level.
- **Overcharging:** Modern devices and this adapter are designed to prevent overcharging, but it is generally good practice to disconnect the charger once the device is fully charged.
- **Temperature:** It is normal for the adapter to become slightly warm during operation. If it becomes excessively hot, disconnect it immediately and contact support.

6. MAINTENANCE

- **Cleaning:** Disconnect the adapter from the power outlet and device before cleaning. Use a soft, dry cloth to wipe the surface of the adapter and cable. Do not use liquid cleaners or solvents.
- **Storage:** Store the adapter and cable in a cool, dry place away from direct sunlight and moisture when not in use. Avoid tightly coiling the cable to prevent damage.
- **Inspection:** Periodically inspect the adapter and cable for any signs of wear, cuts, or damage. Replace immediately if damage is found.

7. TROUBLESHOOTING

Problem: Device is not charging.

- **Check Power Outlet:** Ensure the power outlet is functional by testing it with another device.
- **Verify Connections:** Make sure the USB cable is firmly inserted into both the adapter and the device. Ensure the adapter is fully plugged into the wall outlet.
- **Cable/Connector Fit:** Confirm the barrel connector fits snugly into your device's charging port. A loose connection may prevent charging.
- **Inspect for Damage:** Check the adapter and cable for any visible damage (e.g., frayed wires, bent pins). Do not use if damaged.
- **Device Compatibility:** Ensure your device is compatible with a 5V DC input and the 5.5mm x 2.1mm barrel plug.

Problem: Adapter feels excessively hot.

- **Disconnect Immediately:** Unplug the adapter from the power outlet and device.
- **Check for Obstructions:** Ensure the adapter is not covered or in an enclosed space that prevents proper ventilation.
- **Contact Support:** If the adapter continues to overheat after ensuring proper ventilation, discontinue use and contact UpBright customer support.

8. SPECIFICATIONS

Input Voltage	100-240VAC, 50/60Hz
Output Voltage	5 Volts
Current Rating	3.33 Amps
Connector Type	Barrel Connector (5.5mm x 2.1mm)
Compatible Devices	TBI Pro, TBIPRO, TBI Bark Pro V3, SDS6 Dog Training Collars
Protection Features	OVP, OCP, SCP
Product Dimensions	Approximately 3 x 3 x 1 inches
Item Weight	Approximately 1.9 ounces

9. WARRANTY AND SUPPORT

UpBright products are designed for reliability and performance. This product comes with the following warranty and support:

- **Refund Policy:** UpBright offers a 30-day refund policy from the date of purchase.
- **Exchange Policy:** A 24-month exchange policy is provided for defective units.

For technical support, warranty claims, or any questions regarding your UpBright product, please refer to the contact information provided with your purchase or visit the official UpBright website.