Jaclo 607-VB

Jaclo 607-VB Lift and Turn Bathroom Sink Drain without Overflow

Model: 607-VB | Brand: Jaclo

Introduction

This manual provides detailed instructions for the installation, operation, and maintenance of your Jaclo 607-VB Lift and Turn Bathroom Sink Drain without Overflow. Please read this manual thoroughly before installation and retain it for future reference. This product is designed for use in bathroom sinks that do not require an overflow function.

Safety Information

- Always turn off the water supply to the sink before beginning any installation or maintenance.
- Wear appropriate personal protective equipment, such as safety glasses and gloves, during installation.
- If you are unsure about any part of the installation process, consult a qualified plumber.
- Ensure all connections are watertight to prevent leaks.

Package Contents

Verify that all components are present before beginning installation:

- Jaclo 607-VB Lift and Turn Drain Assembly (Vintage Bronze finish)
- Upper Flange and Stopper
- Rubber Gaskets/Washers
- Lock Nut
- Tailpiece



Figure 1: Complete Jaclo 607-VB Lift and Turn Bathroom Sink Drain Assembly. This image displays the entire drain unit, including the top stopper, flange, rubber gaskets, threaded body, and tailpiece, all in a metallic finish.

Setup and Installation

Tools Required:

- Plumber's Putty or Silicone Sealant
- Adjustable Wrench or Basin Wrench
- Pliers
- Rag or Towel

Installation Steps:

1. **Prepare the Sink Opening:** Ensure the sink drain opening is clean and free of old sealant or debris.
2. **Apply Sealant:** Roll a thin bead of plumber's putty or apply silicone sealant around the underside of the drain's upper flange.
3. **Insert Drain Body:** Insert the drain body, with the flange and stopper attached, into the sink's drain opening from above. Press firmly to create a seal.
4. **Install Gaskets and Lock Nut:** From underneath the sink, slide the rubber gasket(s) and then the lock nut onto the threaded portion of the drain body.
5. **Tighten Lock Nut:** Hand-tighten the lock nut, then use an adjustable wrench or basin wrench to tighten it securely. Do not overtighten, as this can damage the sink or drain. Wipe away any excess plumber's putty or sealant that squeezes out.
6. **Attach Tailpiece:** Connect the tailpiece to the bottom of the drain body. Ensure a proper seal with a washer and nut (typically supplied with the P-trap assembly, not the drain).
7. **Connect P-Trap:** Connect the P-trap assembly to the tailpiece and the wall drain.
8. **Test for Leaks:** Turn on the water supply and fill the sink. Check all connections for leaks. Tighten any leaking connections as necessary.

Operating Instructions

The Jaclo 607-VB drain features a simple lift and turn mechanism for opening and closing the drain.

- **To Close the Drain:** Push the stopper down into the drain opening and turn it clockwise until it seats firmly, creating a seal to retain water in the sink.
- **To Open the Drain:** Turn the stopper counter-clockwise to release it, then lift it upwards to allow water to drain freely.

Maintenance

Regular cleaning and maintenance will ensure the longevity and proper function of your drain.

- **Cleaning:** Clean the visible parts of the drain regularly with a soft cloth and mild soap. Avoid abrasive cleaners, harsh chemicals, or scouring pads, as these can damage the Vintage Bronze finish.
- **Stopper Removal:** For thorough cleaning or to clear minor clogs, the stopper can typically be unscrewed or pulled out from the drain body. Refer to the specific design of your stopper for removal instructions.
- **Preventing Clogs:** Avoid pouring grease, coffee grounds, or other solid waste down the drain. Consider using a drain screen to catch hair and debris.

Troubleshooting

Problem	Possible Cause	Solution
Drain Leaks	Loose connections, improperly seated gaskets, insufficient sealant.	Tighten lock nut, ensure gaskets are correctly positioned, reapply plumber's putty or sealant if necessary.
Slow Draining	Clog in the drain or P-trap.	Remove stopper and clear any debris. Clean the P-trap if necessary. Avoid chemical drain cleaners that may damage plumbing.
Stopper Not Sealing	Debris under the stopper, stopper mechanism misaligned or damaged.	Remove stopper and clean thoroughly. Check for any obstructions. Ensure stopper is correctly seated and turned to lock.

Specifications

- **Model:** Jaclo 607-VB
- **Type:** Lift and Turn Bathroom Sink Drain
- **Overflow:** Without Overflow
- **Finish:** Vintage Bronze
- **Material:** Metal construction
- **Item Weight:** 1.2 pounds
- **Product Dimensions:** 3 x 3 x 7 inches
- **Manufacturer:** Standard Plumbing Supply
- **UPC:** 020111118272

Warranty and Support

For warranty information or technical support, please contact Jaclo customer service. Keep your purchase receipt as proof of purchase. Contact details can typically be found on the manufacturer's official website or product packaging.

Ask a question about this manual

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. Privacy details.

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question