

Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

Manuals.plus /

› [Skar Audio](#) /

› Skar Audio VD-12 D4 12-inch Dual 4 Ohm Shallow Mount Car Subwoofer Instruction Manual

Skar Audio VD-12 D4

Skar Audio VD-12 D4 12-inch Dual 4 Ohm Shallow Mount Car Subwoofer Instruction Manual

INTRODUCTION

This manual provides essential information for the proper installation, operation, and maintenance of your Skar Audio VD-12 D4 12-inch Dual 4 Ohm Shallow Mount Car Subwoofer. Please read this manual thoroughly before attempting installation or operation to ensure optimal performance and product longevity. Retain this manual for future reference.

SAFETY GUIDELINES

Always observe the following safety precautions during installation and operation:

- Disconnect the vehicle's battery before beginning any electrical work to prevent electrical shock or damage.
- Ensure all wiring connections are secure and properly insulated to prevent short circuits.
- Use appropriate gauge wiring for power, ground, and speaker connections as recommended by your amplifier manufacturer.
- Mount the subwoofer securely in a suitable enclosure to prevent movement during vehicle operation.
- Avoid exposing the subwoofer to excessive moisture or extreme temperatures. This product is not water resistant.
- Consult a professional car audio installer if you are unsure about any aspect of the installation process.

PRODUCT OVERVIEW

The Skar Audio VD-12 D4 is a 12-inch shallow mount subwoofer designed for car audio applications, offering a balance of power and compact design. It features a robust construction suitable for delivering enhanced bass response in various vehicle setups.

Key Features

- 12-Inch Dual 4 Ohm Shallow Mount Subwoofer
- Peak Power: 800 Watts | RMS Power: 500 Watts
- Shallow Mount Design - Mounting Depth: 4.92 inches
- High Performance Pressed Paper Cone Stitched to Premium Foam Surround
- Sensitivity: 85.9 dB | Fs: 36.6 Hz
- Frequency Response: 25 Hz - 300 Hz

Included Components

- Skar Audio VD-12 D4 12-inch Dual 4 Ohm Subwoofer (Quantity: 1)

SPECIFICATIONS

Specification	Value
Model Name	VD-12 D4
Speaker Type	Subwoofer
Subwoofer Diameter	12 Inches
Peak Power	800 Watts
RMS Power	500 Watts
Impedance	Dual 4 Ohm
Mounting Depth	4.92 Inches
Sensitivity	85.9 dB
Frequency Response	25 Hz - 300 Hz
Material	Paper (cone)
Item Weight	15 Pounds
Product Dimensions (D x W x H)	14"D x 14"W x 8"H
Recommended Uses	Car Audio System
Water Resistance Level	Not Water Resistant

SETUP AND INSTALLATION

Proper installation is crucial for the performance and longevity of your subwoofer. It is recommended that installation be performed by a qualified professional.

Enclosure and Mounting

The VD-12 D4 is a shallow mount subwoofer, requiring a mounting depth of 4.92 inches. Ensure your chosen enclosure provides adequate internal volume and clearance for the subwoofer's dimensions. Secure

the subwoofer firmly to the enclosure using appropriate fasteners to prevent air leaks and vibrations.



Figure 1: Angled view of the Skar Audio VD-12 D4 subwoofer, showcasing its shallow design.



Figure 2: Top view of the Skar Audio VD-12 D4 subwoofer, showing the cone and surround.

Wiring Configurations (Dual 4 Ohm Voice Coils)

The VD-12 D4 features dual 4 Ohm voice coils, offering flexibility in wiring to achieve different impedance loads for your amplifier. Always ensure the final impedance matches your amplifier's stable operating range.

- **Parallel Wiring (2 Ohm Load):** Connect the positive terminal of Voice Coil 1 to the positive terminal of Voice Coil 2. Connect the negative terminal of Voice Coil 1 to the negative terminal of Voice Coil 2. Then, connect the combined positive to the amplifier's positive output and the combined negative to the amplifier's negative output. This configuration results in a 2 Ohm load.
- **Series Wiring (8 Ohm Load):** Connect the positive terminal of Voice Coil 1 to the amplifier's positive output. Connect the negative terminal of Voice Coil 1 to the positive terminal of Voice Coil 2. Connect the negative terminal of Voice Coil 2 to the amplifier's negative output. This configuration results in an 8 Ohm load.



Figure 3: Bottom view of the Skar Audio VD-12 D4 subwoofer, highlighting the dual voice coil terminals for wiring.

OPERATING INSTRUCTIONS

Break-in Period

Allow a break-in period of approximately 20-30 hours of normal listening before operating the subwoofer at high volumes. This allows the suspension components (surround and spider) to loosen and reach their optimal compliance, improving overall performance and longevity.

Optimal Settings

Adjust your amplifier's gain, crossover, and bass boost settings carefully. Start with low settings and gradually increase them while listening for distortion. Avoid excessive bass boost, which can lead to clipping and damage the subwoofer. Set the low-pass filter (LPF) on your amplifier to a frequency appropriate for your system, typically between 60Hz and 100Hz, to ensure the subwoofer only reproduces low frequencies.

MAINTENANCE

The Skar Audio VD-12 D4 subwoofer requires minimal maintenance. Keep the cone and surround free from dust and debris. Avoid touching the cone directly. Periodically check all wiring connections for tightness and ensure no wires are frayed or exposed. Do not use harsh chemicals or solvents for cleaning.

TROUBLESHOOTING

If you experience issues with your subwoofer, refer to the following common problems and solutions:

- **No Sound:** Check all wiring connections (power, ground, remote, speaker). Verify the amplifier is powered on and receiving a signal. Check for blown fuses in the amplifier or power distribution block.
- **Distorted Sound:** Reduce amplifier gain. Check for proper crossover settings. Ensure the subwoofer is not over-powered or clipping. Verify the enclosure is sealed and free of leaks.
- **Weak Bass:** Verify amplifier gain is set correctly. Check wiring for correct impedance match. Ensure the enclosure volume is appropriate for the subwoofer.
- **Subwoofer Overheating:** This can indicate an impedance mismatch, insufficient power, or an enclosure issue. Ensure proper ventilation for the amplifier.

If problems persist after checking these points, contact Skar Audio customer support or a professional installer.

WARRANTY INFORMATION

The Skar Audio VD-12 D4 subwoofer comes with a 2-year limited warranty. This warranty covers defects in materials and workmanship under normal use. It does not cover damage caused by improper installation, abuse, accident, neglect, or unauthorized modifications. Please retain your proof of purchase for warranty claims.

CUSTOMER SUPPORT

For technical assistance, warranty inquiries, or further information regarding your Skar Audio VD-12 D4 subwoofer, please visit the official Skar Audio website or contact their customer support department directly. Refer to the contact information provided on the product packaging or the official brand website.