



[Manuals.plus](#) /

› [Command](#) /

› Command 5 lb Large Utility Hooks (Model 17003-MPES) Instruction Manual

Command 17003-MPES

Command 5 lb Large Utility Hooks (Model 17003-MPES) Instruction Manual

Damage-Free Hanging Solution

INTRODUCTION

The Command 5 lb Large Utility Hooks provide a damage-free solution for organizing and decorating your home, office, or dorm room. These hooks utilize advanced adhesive technology to hold strongly on various smooth surfaces and remove cleanly without leaving holes, marks, or sticky residue. Each large utility hook is designed to hold up to 5 pounds, offering versatile hanging options for a range of items.

SAFETY INFORMATION

- Do not hang over beds.
- Do not use on wallpaper.
- Do not use for hanging valuable items.
- Ensure indoor temperature is between 50°F (10°C) and 105°F (40°C) for optimal adhesion.
- Wait seven days after painting before using Command Hooks to allow paint to cure.

PACKAGE CONTENTS

Each package of Command 5 lb Large Utility Hooks includes:

- 14 x Large Utility Hooks
- 16 x Large Adhesive Strips

SETUP AND INSTALLATION

Follow these steps for proper installation to ensure maximum holding power and damage-free removal.

1. Surface Preparation

Clean the desired surface with rubbing alcohol to remove any grime and dust. This allows the adhesive strips to

bond effectively. Do not use household cleaners or water, as they can leave slippery residues that prevent proper adhesion.

2. Attaching Strips to Hooks

Separate the adhesive strips. Each strip has two sides. One side is marked for the wall, and the other for the hook.



Image: A hand demonstrates attaching the adhesive strip to the flat back of a Command Large Utility Hook. The strip is white with red 'Command' branding.

Press the adhesive strip firmly onto the back of the hook. Ensure the entire strip is pressed down for 30 seconds to create a strong bond.

3. Applying Hooks to the Wall

Remove the remaining liner from the adhesive strip, exposing the side that will attach to the wall.

SIZE COMPARISON

1 hook holds



Image: A hand presses a white Command Large Utility Hook firmly against a wall, demonstrating the application process. Press the hook firmly against the prepared surface for 30 seconds. Apply pressure evenly across the entire hook to ensure full contact with the adhesive.

4. Curing Time

After applying the hook, wait 1 hour before hanging any items. This allows the adhesive to reach its maximum holding strength.

Your browser does not support the video tag.

Video: Official Command Brand video demonstrating how to use Command Indoor and Outdoor Hooks, covering surface preparation, application, and removal.

OPERATING INSTRUCTIONS

Each Command Large Utility Hook can hold up to 5 pounds. They are suitable for a variety of items and surfaces.

HOLDS STRONG

on a variety of surfaces:



DO NOT USE ON: wallpaper, fabric, textured walls, brick, or rough surfaces

Image: A visual guide showing compatible surfaces for Command hooks (painted walls, metal, painted concrete, laminate & finished wood, tile, smooth surfaces & glass) and incompatible surfaces (wallpaper, fabric, textured walls, brick, rough surfaces).

- **Recommended Uses:** Hanging clipboards, brushes, dog leashes, kitchen utensils, home decor, accessories, and lightweight coats.
- **Surfaces:** Painted walls, finished wood, painted concrete cinder blocks, laminate, glass, metal, and tiles.
- **Surfaces to Avoid:** Wallpaper, fabric, textured walls, brick, or rough surfaces.

NO TOOLS

required, easy installation



STICK adhesive to the hanger

REMOVE black liner

PRESS hanger to the wall

STRETCH to remove

***Not all product instructions shown above.
Follow all use instructions.**

Image: A kitchen wall with several Command hooks holding kitchen items and a bag of fruit, demonstrating practical, damage-free organization.

MAINTENANCE

Command hooks require minimal maintenance. To clean the hooks, simply wipe them with a damp cloth. Avoid using harsh chemicals or abrasive cleaners, as these may damage the plastic or affect the adhesive properties if they come into contact with the strips.

REMOVAL PROCESS

To remove Command hooks without damaging your surfaces, follow these instructions carefully:

1. Lightly hold the top of the hook.
2. Slowly pull the adhesive strip straight down towards the floor. Do not pull the strip toward you or at an angle, as this may cause damage to the surface.
3. Continue pulling the strip until the hook releases from the wall. The strip will stretch up to several inches.



DAMAGE-FREE

hanging & decorating

Image: A close-up of hands pulling the tab of a Command adhesive strip downwards, illustrating the proper technique for damage-free removal.

You can reuse your hook with new Command Refill Strips.

TROUBLESHOOTING

Hook Not Sticking

- Ensure the surface was cleaned with rubbing alcohol only, not household cleaners or water.
- Verify the surface is smooth and not textured, wallpapered, or fabric.
- Confirm the indoor temperature is within the recommended range (50°F to 105°F).
- Ensure you waited 1 hour after application before hanging items.
- Check that the weight of the item does not exceed 5 pounds.

Strip Breaks During Removal

If the adhesive strip breaks during removal, it may be due to pulling it too quickly or at an angle. To remove the remaining strip:

- Gently slide a piece of dental floss or fishing line behind the hook/strip.
- Work the floss/line back and forth in a sawing motion to separate the adhesive from the wall.

SPECIFICATIONS

| | |
|--------------------------------|----------------------------|
| Brand | Command |
| Model Number | 17003-MPES |
| Color | White |
| Material | Plastic |
| Mounting Type | Wall Mount |
| Maximum Weight Capacity | 5 Pounds (2.2 kg) per hook |
| Included Components | 14 Hooks, 16 Strips |
| Item Dimensions | 2.11 x 3.9 x 7.15 inches |
| Item Weight | 6.08 ounces |

WARRANTY AND SUPPORT

3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and other limitations, and the user must take any action required under any recall, field action, or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, death, or property damage. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit www.3M.com.