

[manuals.plus](#) /

› [Command](#) /

› [Command Large Double Bathroom Wall Hook \(BATH36-SN-ES\) Instruction Manual](#)

Command BATH36-SN-ES

Command Large Double Bathroom Wall Hook (BATH36-SN-ES) Instruction Manual

Damage-Free Hanging with Adhesive Strip, Holds up to 4 lb

1. PRODUCT OVERVIEW

The Command Large Double Bathroom Wall Hook provides a damage-free solution for hanging items in your bathroom. Designed for hot, wet, and humid environments, this hook utilizes water-resistant adhesive strips to securely attach to various surfaces. It is engineered to hold better than traditional suction cups and can be removed cleanly without leaving holes, marks, or sticky residue.



Image 1: Command Large Double Bathroom Wall Hook, showing the product in its packaging and an unboxed view. The hook features a satin nickel finish and a double-hook design.

2. PRODUCT CONTENTS

- 1 x Command Large Double Bathroom Wall Hook (Satin Nickel)
- 1 x Command Water-Resistant Adhesive Strip

3. KEY FEATURES

- **Damage-Free Hanging:** Leaves no holes, marks, or sticky residue.
- **Water-Resistant:** Suitable for hot, wet, and humid bathroom environments.
- **Strong Hold:** Holds up to 4 pounds (1.8 kg).
- **Versatile:** Sticks to various smooth surfaces including painted walls, finished wood, tile, glass, and fiberglass.
- **Easy Removal:** Removes cleanly by stretching the adhesive strip.
- **Reusable Hook:** Can be reused with Command Water-Resistant Refill Strips.

4. INSTALLATION INSTRUCTIONS

4.1 Surface Preparation

1. Clean the surface with rubbing alcohol. This removes grime and dust, allowing the adhesive strip to bond effectively. Do not use household cleaners.
2. Ensure the indoor temperature is between 15°F and 125°F (-9°C and 52°C).
3. If the wall has been recently painted, wait seven days after painting before applying the Command Hook to allow the paint to cure.

4.2 Applying the Hook

4. Separate the hook from its base.
5. Remove the red liner from the adhesive strip and press the strip firmly onto the back of the hook's base.
6. Remove the black liner from the adhesive strip.
7. Press the hook firmly to the prepared wall surface for 30 seconds. Ensure the entire adhesive strip makes contact with the surface.
8. Slide the hook back onto its base.
9. Wait 1 hour before hanging any items on the hook. This allows the adhesive to reach maximum strength.

NO TOOLS
required, easy installation



STICK adhesive to the hook

REMOVE black liner

PRESS hook to the wall

STRETCH to remove

***Not all product instructions shown above.
Follow all use instructions.**

Image 2: Step-by-step visual guide for installing a Command Hook, illustrating the process of sticking the adhesive to the hook, removing the liner, pressing to the wall, and stretching to remove.

5. USAGE GUIDELINES

5.1 Weight Capacity

This Command Large Double Bathroom Wall Hook is designed to hold items weighing up to 4 pounds (1.8 kg). Exceeding this weight limit may cause the hook to detach from the surface.



Image 3: A white robe hanging on the Command Double Bathroom Wall Hook, demonstrating its capacity to hold up to 4 pounds.

5.2 Recommended Surfaces

The hook works effectively on a variety of smooth surfaces, including:

- Painted Walls
- Finished Wood
- Painted Concrete Cinder Blocks
- Laminate
- Tiles
- Glass
- Mirrors

- Fiberglass

5.3 Surfaces to Avoid

Do not use Command Hooks on:

- Wallpaper
- Textured Walls
- Brick
- Rough Surfaces
- Fabric

Avoid applying adhesive over grout lines. Do not hang over beds.



Image 4: Visual guide illustrating various surfaces where Command Hooks can be used (painted walls, metal, painted concrete, laminate & finished wood, tile, smooth surfaces & glass) and surfaces to avoid (wallpaper, fabric, textured walls, brick, or rough surfaces).

6. REMOVAL INSTRUCTIONS

To remove the Command Hook cleanly and without damage:

1. Lightly hold the top of the hook's base.
2. Slowly pull the adhesive strip straight down towards the floor. Pulling at an angle or too

quickly may damage the surface.

3. Continue pulling until the strip releases completely from the wall. The strip will stretch as it releases.



Image 5: A pair of hands demonstrating the removal process of a Command Strip, showing the strip being pulled downwards to release the hook from the wall without damage.

7. CARE AND MAINTENANCE

To maintain the appearance and functionality of your Command Hook:

- Clean the hook with a soft, damp cloth. Avoid abrasive cleaners or scouring pads, which can damage the satin nickel finish.
- Ensure the hook and surrounding area are dry after cleaning, especially in humid bathroom environments.
- If the adhesive strip loses its hold, replace it with a new Command Water-Resistant Refill Strip (sold separately).

8. TROUBLESHOOTING

8.1 Hook is not holding or falls off

- **Surface not clean:** Ensure the surface was thoroughly cleaned with rubbing alcohol and

allowed to dry completely before application.

- **Weight exceeded:** Verify that the weight of the items hung on the hook does not exceed 4 pounds (1.8 kg).
- **Improper application:** Ensure the adhesive strip was pressed firmly for 30 seconds and allowed to cure for 1 hour before use.
- **Unsuitable surface:** Confirm that the hook was applied to a recommended smooth surface and not on wallpaper, textured walls, or other unsuitable materials.
- **Temperature:** Ensure the installation temperature was within the recommended range of 15°F to 125°F.

9. PRODUCT SPECIFICATIONS

Attribute	Value
Brand	Command
Model Number	BATH36-SN-ES
Color	Satin Nickel
Material	Metal
Finish Type	Painted
Mounting Type	Wall Mount
Weight Limit	4 Pounds (1.8 Kilograms)
Number of Hooks	2
Item Weight	1.64 Ounces
Product Dimensions (L x W x H)	1.97 x 4.29 x 6.73 inches
Surface Recommendation	Glass, Mirrors, Tile, Fiberglass, Wood, Painted Surfaces
UPC	076308730826

10. WARRANTY INFORMATION

This product comes with a standard manufacturer's warranty. For specific details regarding warranty coverage, terms, and conditions, please refer to the warranty documentation included with your purchase or contact Command customer support directly.