

Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

Manuals.plus /

› [wellclima](#) /

› Wellclima Universal Air Conditioner Remote Control DOUBLE Instruction Manual

wellclima Wellclima Double E.S.

Wellclima Universal Air Conditioner Remote Control DOUBLE

Model: Wellclima Double E.S. | Brand: wellclima

PRODUCT OVERVIEW

The Wellclima DOUBLE universal remote control is designed to operate a wide range of air conditioning units, heat pumps, and inverters. Its unique dual-control capability allows it to manage two different air conditioning units simultaneously, eliminating the need for multiple remotes.

This remote features an elegant design with a large, clear display and user-friendly function keys. It includes an energy-saving function, ideal for commercial or hospitality settings, which allows for setting minimum and maximum temperature limits to optimize energy consumption.

Key functions include various operating modes (cooling, heating, dehumidification, fan-only, recirculation), adjustable fan speeds, and air direction control. It also offers quick access to "Fast Cool" and "Fast Heat" modes for rapid temperature adjustments. The integrated timer function allows for precise scheduling of unit operation. The remote retains its programmed settings even after battery replacement, thanks to its code memory feature.

PACKAGE CONTENTS

- 1 x Wellclima Universal Air Conditioner Remote Control DOUBLE
- 1 x Instruction Manual (this document)

Note: 1.5V AAA (UM-4, R03) batteries are not included and must be purchased separately.

SETUP AND BATTERY INSTALLATION

- 1. Open the Battery Compartment:** Locate the battery cover on the back of the remote control. Slide the cover downwards to open the compartment.
- 2. Insert Batteries:** Insert two 1.5V AAA (UM-4, R03) batteries, ensuring the correct polarity (+ and -) as indicated inside the compartment.
- 3. Close the Battery Compartment:** Slide the battery cover back into place until it clicks securely.
- 4. Initial Power On:** The remote control should power on automatically. The display will show default settings or prompt for initial setup.



Figure 1: Hand holding the Wellclima universal remote control, demonstrating its ergonomic design and button layout.

PROGRAMMING THE REMOTE CONTROL

The Wellclima DOUBLE remote offers three simple programming methods: manual, automatic, or by brand.

Method 1: Automatic Search

1. Ensure the air conditioner unit is powered on.
2. Point the remote control towards the air conditioner.
3. Press and hold the "SET" button (or equivalent programming button) until the code on the remote's display starts flashing.
4. The remote will automatically cycle through codes. Release the "SET" button immediately when the air conditioner responds (e.g., turns on, off, or changes mode).
5. Test all basic functions (On/Off, Mode, Fan Speed) to ensure correct programming. If not all functions work, repeat the process or try another programming method.

Method 2: Manual Code Entry

1. Refer to the comprehensive list of compatible brands and their corresponding codes (often provided in a separate document or online).
2. Press and hold the "SET" button until the code on the display flashes.
3. Use the temperature up/down buttons to manually enter the 3-digit code for your air conditioner's brand.
4. Press "OK" or "ENTER" (or "SET" again) to confirm the code.
5. Test all functions. If the unit does not respond or functions are incomplete, try the next code for your brand or another programming method.

ELENCO MARCHE COMPATIBILI

ACSONI	CARRIER	ENVIRACAIRE	ICEBERG	MULTISEVEN	SHOWNIC	VOLTAS
ACCORONI	CHAFFOTEAUX & MAURY	EQUATION	IDEAL STANDARD	MULTIWARM	SHUANGLU	VORTICE
ACXON	CHANGFENG	ESKIMO FOREST	IDEMA	MUNDOCLIMA	SIGMA	VORTIS
ADC	CHANGFU	FAGOR	INDESIT	NAKATOMY	SINCLAIR	WANBAO
AERMEC	CHANGHONG	FANAI - FAIR	INYCIN	NANKAJ	SIMAT	WANGZI
ACSION	CHANGLING	FANTINI COSMI	INNO-HIT	NEVADA CLIMA	SINGER	WEGA WHITE
AIDELONG	CHENGYUAN	FEDDERS	INVENTOR	NIKKEI	SIRGE	WEILI
AIRTEK	CHIGO	FEEL LINE	IRSAP	NIKKO	SKICE	WEITELI
AIRWELL	CHUANGHUA	FEELMAX	ISOCLIMA	NIKKU	SKYWORTH	WESTINGHOUSE
AIRTON	CHUANYAN	FEIEDRICH	ISUZU	NIMAKO	SOGO	WHIRLPOOL
AITE	CHUNLAN	FEIGE	JANGSU	NISO	SONGXING	WHITE WESTINGHOUSE
AKAI	CLIMAVENETA CLIMAPIU	FEILU	JET HAIR	NORCA	SOOKAI	WINIA
AKIRA	CLIMAX	FER-FERROLI	JIALE	OLIMPIA SPLENDID	SOVA	WINNER
ALPIN	CLIVET	FIRST	JIANGNAN	OLYMPUS	SOWA	WINS
ALPINA	COOLAIR	FIRSTLINE	JINBEIJING	OPAL	SOYEA	WUFENG
ALTECH	COOLIX	FRESTECH	JINDA	ORIEME	SPEED	XILENG
AMCOR	COOPER & HUNTER	FRIGIDAIRE	JINSONG	PANASONIC / NATIONAL	SRTC	XINGHE
AMICO	COMFEE	FUJI ELECTRIC	JMSTAR	PANDA	STAR ELECTRIC	XINLE
AMSTRAD	COMFORTSTAR	FUJIAIR	JOANNES	PENSONIC	STARCLIMA	XINLING
AOKE	COMPACTAIR	FUJITEAC	JOHNSO	PEREG	STAR	XIONGDI
AOLI	CONROWA	FUJITECH	JOYCARE	PHILCO	STARLIGHT - AIRCON	YAIR
APTON	CONSUL	FUJITHERMA	JUCKER CLIMA	PILOT	STARWAY	YAMA
ARCA	COROLLA	FUJITSU	KALVERT	PINSHANG, XINHUAABAO	STELBI	YAOMA
ARCO-AIR	CORONA	FUNIKI	KANGLI	PROTECNO	STEP	YASHIMA
ARGO	COSMOGAS	GALANZ	KAYSUN	PUYI	STORM	YIDONG
ARIAGEL	CROWN	GALETTI	KELON	QIXING	SUNBURG	YOKO
ARISTON	DAEWOO	GE	KELVINATOR	QLIMA	SUNSHINE	YORK
ARMONY	DAUER	GEER	KENDO	QUEEN	SUPERCLIMA	YUETU
ARTEL	DAYA	GENERAL	KENWOOD	RAYBO	SUSHIMA	YUTU
ARYA	DAIKIN	GIATSU	KLARSTEIN	RELAX	SUYAMA	ZENITH
ASHITA	DAITSU	GLEE	KLIMAWATT	REX	SYNTEK	ZEPHIR
ASJA	DAJINXING	GORENJE	KOMECO	RHEEM	TADIRAN - TADIAR	ZIBRO
ASR	DAKE	GOLDSTAR	KONKA	RHOSS	TAIYA	ZHONGYI
ATLANTIC	DAOTIAN	GREE	KOOLKING	RICAI	TANGO	ZUODAN
AUCMA	DAREL	GENERAL	KRIS	RIELLO	TASAKI	
AUFIT	DAUER	GIATSU	LAMBORGHINI	RIJIANG	TATA	
AUKIA	DAYSOL	GLEE	LAMINOX	ROADSTAR	TCL	
AUX	DE LONGHI	GORENJE	LAR.EL	ROWA	TEAC	
AURORA	DELCHI	GOLDSTAR	LENOIR	SACON	TECHAIR	
AZURI	DEMIRAD	GREE	LENNOX	SAECO	TECHNIBEL	
AZUKI	DIY	GUANGDA	LEVANTE	SAMSONIC	TECO	
BAIXUE	DICORE	GUQIAO	LG	SAMSUNG	TECNO MASTERS	
BALTUR	DILOC	HAIER	LIANGYU	SAMY	TECTRO	
BARTOLINI	DOLPHIN	HEC	LIKEAIR	SANSUI	TELEFUNKEN	
BAXI	DONGXIA	HELTON	LITTLEDUCK	SANT'ANDREA	TERMOTEK	
BECKEN	DONGXINBAO	HEMILTON	LITTLESWAN	SANYO - NEC	THERMOMEC	
BEIJING / JINGDIAN	DUCASA	HERMANN	LONGHE	SANZUAN	TIANJINKONGTIAO	
BEKO	DUNAN	HICON	LOREN-SEBO	SAPORO	TIANYUAN	
BELAIR IRRADIO	DYMANIC	HISENSE	MARIANI CLIMA	SAST	TOBO	
BENT	E-COLD	HITACHI	MAXA	SAUNIER DUVAL	TONGLU	
BERETTA	ECA TECHNOLOGY	HIYASU	MASTER CLIMA	SCHNEIDER	TOSHIBA	
BIG-THUMB	ECO AIR	HOKKAIDO	MCQUAY	SEKOM	TOTALINE	
BION	ECOFIX	HONGYI	MEILING	SENSOR	TOYO	
BLOWMASTER	ECOFLAM	HOWELL	MIDEA	SERENE	TOYOTOMI	
BLUE STAR	EG4	HTW	MINGXING, BOYIN	SHAMEI	TRANE	
BLUNORD	EINHELL	HUABAO	MIRAGE	SHANGLING	TUDOR	
BOERKA	EKOKAI	HUAGAO	MISTRAL	SHANXING	UNI-AIR	
BONNTO	ELCO	HUAKE	MITSUBISHI ELECTRIC	SHANYE	UNIONAIRE CLIMAPIU'	
BORLER	ELECTER	HUALING	MITSUI	SHARP	UNICAL	
BOSH	ELECTRA	HUAMEI	MITSUKA	SHAUB LORENZ	UNIVERSALCLIMA	
BOSHI	ELECTRIQ	HUANGHE	MITSUSHITO	SHENBAO	VAILLANT	
BOSHIGAO	ELECTROLUX	HUAWEI	MIZUSHI	SHENGFENG / FEILU	VIDEOCON	
BREEZE	ELIT	HUIFENG	MONDIALCASA	SHINCO	VISSMANN	
CAIXING	EMAILAIR	HYUNDAI	MONTANA	SHINELCO	VIESTA	
CARRERA	EMMETI	KLARSTEIN	MORGAN	SHINING	VIVAX	

Figure 2: Example of a comprehensive list of compatible air conditioner brands. Refer to your specific code list for detailed brand codes.

Dual Air Conditioner Control

The Wellclima DOUBLE remote can control two different air conditioning units. After programming the first unit, you can program the second unit using the same methods. The remote typically has a switch or button (e.g., "1/2" or "AC1/AC2") to toggle between controlling the two programmed units.

OPERATING INSTRUCTIONS





Figure 3: Overview of the Wellclima remote control's display and buttons.

Power Button (●): Press to turn the air conditioner ON or OFF.

MODE Button: Press to cycle through operating modes:

- Cool (Snowflake icon): For cooling the room.
- Heat (Sun icon): For heating the room (heat pump function).
- Dry (Water drop icon): For dehumidification.
- Fan (Fan icon): For circulating air without heating or cooling.
- Auto: The unit automatically selects the mode based on room temperature.

TEMP ▲ / ▼ Buttons: Press to increase or decrease the desired temperature.

FAN Button: Press to adjust fan speed (Low, Medium, High, Auto).

A.SWING / M.SWING Buttons: Control the vertical (A.SWING) and horizontal (M.SWING) airflow direction. Press to activate or adjust the swing function.

Timer ON / OFF Buttons:

- **Timer ON:** Press to set a time for the air conditioner to turn on. Use TEMP buttons to adjust the time, then press Timer ON again to confirm.
- **Timer OFF:** Press to set a time for the air conditioner to turn off. Use TEMP buttons to adjust the time, then press Timer OFF again to confirm.

Fast Cool / Fast Heat Buttons (if available): Activates a rapid cooling or heating function to quickly reach the desired temperature.

Energy Saving Function: This feature allows setting a minimum and maximum temperature range to prevent excessive heating or cooling. This is particularly useful in public or rental environments. Consult the remote's specific instructions for activating and setting these limits.

LED Flashlight: The remote control includes a built-in LED flashlight for convenience in low-light conditions.



Luce LED per visione notturna

Figure 4: The remote control's integrated LED flashlight for night vision.

COMPATIBILITY INFORMATION

The Wellclima DOUBLE remote control is designed for broad compatibility with most major air conditioner brands. However, certain models and brands are known to be incompatible.

Known Incompatibilities:

- Argo portable and Xfetto models.
- De Longhi Pinguino models.
- Mitsubishi Heavy Industries (Mitsubishi Electric is compatible).
- Specific older models from Aermec, Airwell, Sanyo, Electra, Ferroli Olimpia Splendid, Climaveneta, and Starclima. Refer to the image below for visual examples of non-compatible original remotes.
- Compatibility is not guaranteed for portable, ducted, or built-in air conditioners, or units older than 20 years. It is recommended to inquire before purchase for these specific cases.



Figure 5: Examples of original remote controls that are NOT compatible with the Wellclima DOUBLE universal remote.

MAINTENANCE

Battery Replacement:

When the remote control's display becomes dim or the unit becomes unresponsive, it is time to replace the batteries. Follow the battery installation steps outlined in the "Setup and Battery Installation" section. The remote's code memory ensures that settings are retained even when batteries are removed.

Cleaning:

To clean the remote control, use a soft, dry cloth. For stubborn dirt, a slightly damp cloth with mild soap can be used, followed by a dry cloth. Do not use abrasive cleaners, solvents, or immerse the remote in water.

TROUBLESHOOTING

Problem	Possible Cause	Solution
Remote does not power on or display is blank.	Dead or incorrectly inserted batteries.	Replace batteries with new 1.5V AAA batteries, ensuring correct polarity.
Air conditioner does not respond to remote.	Incorrect code programmed; remote not pointed at unit; obstruction between remote and unit; unit is incompatible.	Reprogram the remote using a different code or method. Ensure direct line of sight. Check compatibility list.
Only some functions work after programming.	Partially compatible code programmed.	Try another code for your brand, or use the automatic search method to find a more complete code.
Remote range is poor.	Low batteries; obstruction; excessive distance.	Replace batteries. Ensure no obstructions. Operate within 6 meters of the unit.

SPECIFICATIONS

Feature	Detail
Brand	wellclima
Model	Wellclima Double E.S.
Model Name	ONE
Product Dimensions	15.4 x 5.4 x 1.9 cm
Item Weight	74 grams
Compatible Devices	Air conditioner, Heat pump, Inverter, Portable air conditioner
Additional Features	Universal, Energy Saving Function, LED Flashlight
Battery Type	AAA (1.5V)
Batteries Required	Yes (2x AAA, not included)
Connector Type	Infrared
Maximum Range	Approximately 8 meters
Number of Buttons	16
Maximum Supported Devices	2 (simultaneously)

SUPPORT

For any questions, issues, or further assistance with your Wellclima DOUBLE universal remote control, please contact Wellclima customer support. Reliable assistance is available to help you with any problems you may encounter.

Please refer to the official Wellclima website or your purchase documentation for specific contact details and warranty information.