

Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

[manuals.plus](#) /

› [WOLTU](#) /

› [WOLTU No-Drill Pleated Blind Instruction Manual \(60x220cm, White\)](#)

WOLTU WOLTU Pleated Blind 60x220cm White

WOLTU No-Drill Pleated Blind Instruction Manual

Model: 60x220cm, White

1. SAFETY INFORMATION

Please read these instructions carefully before installation and use. Keep this manual for future reference.

- Ensure all components are present and undamaged before installation.
- Keep small parts away from children to prevent choking hazards.
- Do not modify the product in any way, as this may compromise its safety and functionality.
- This product is not compatible with roof windows, wooden windows, or sliding windows.

2. PRODUCT OVERVIEW

The WOLTU pleated blind offers a practical and stylish solution for window and door coverings. Designed for no-drill installation, it provides privacy and sun protection while allowing natural light to filter through. Its durable polyester fabric and aluminum rails ensure long-lasting performance.



Image: WOLTU pleated blinds installed in a living room setting.

3. PACKAGE CONTENTS

Verify that all the following items are included in your package:

- Pleated Blind Unit
- Mounting Kit
- 4 Metal Clamp Brackets
- 4 Tensioners for Drilling (optional use)



Image: Contents of the WOLTU pleated blind package.

4. MEASUREMENT GUIDE

Accurate measurement is crucial for proper fit and function. Follow these steps:

1. **Measure the glass width:** Measure the width of the window glass.
2. **Recommended order width:** Add approximately 4 cm to the glass width (e.g., glass width + 2 cm on each side) for better light blocking.
3. **Order height:** Measure the total height of the entire window frame.

Important: When measuring, ensure the blind will not interfere with the window handle.

Comment choisir la taille convenable ?



- **1. Largeur à commander :**
Largeur du verre + environ 4 cm (pour un meilleur effet)
- **2. Hauteur à commander :**
La hauteur totale du cadre de la fenêtre
- **3. Ne pas dépasser la poignée de la fenêtre !**



Fenêtre rectangulaire verticale



Lucarne



Porte-fenêtre

Image: Detailed measurement instructions for the pleated blind.

5. SETUP AND INSTALLATION

The WOLTU pleated blind features a no-drill installation method using adjustable clamp brackets. This allows for secure attachment to window frames with a thickness of 10 to 23 mm without the need for tools or drilling.

No-Drill Installation Steps:

1. Attach the clamp brackets to the top and bottom rails of the pleated blind.
2. Position the blind on the window frame.
3. Adjust the clamp brackets to securely grip the window frame (10-23mm thickness).
4. Ensure the blind is level and firmly in place.



Image: Detail of the Klemmfix clamp bracket for no-drill installation.

For a more permanent installation, the included tensioners and screws can be used to fix the blind directly to the window frame by drilling.

6. OPERATING INSTRUCTIONS

The pleated blind is operated manually using a handle system, allowing for flexible positioning.

Adjusting the Blind Height:

- Grasp the handle located on the bottom rail of the blind.
- Gently push or pull the handle to move the blind up or down to your desired height.
- The double cord system and aluminum rails ensure smooth and stable adjustment.

Systeme de levage avec poignée



Image: Lifting system with handle for height adjustment.

Translucide mais pas transparent



Image: The pleated blind provides privacy while allowing light to filter through.

7. MAINTENANCE

The WOLTU pleated blind is designed for easy care.

- **Cleaning:** Wipe the fabric with a damp cloth to remove dust and light stains. Avoid harsh chemicals or abrasive cleaners.
- **General Care:** Regularly check the cords and rails for any signs of wear.

8. TROUBLESHOOTING

If you encounter any issues with your pleated blind, refer to the following common problems and solutions:

Problem	Possible Cause	Solution
Blind does not stay at desired height	Cords are not properly tensioned or mechanism is loose.	Check the tension of the cords. Ensure the handle mechanism is clean and free of obstructions.

Problem	Possible Cause	Solution
Blind is difficult to move	Rails are obstructed or dirty.	Inspect the rails for any debris or damage. Clean the rails with a damp cloth.
Blind falls off the window frame	Clamp brackets are not securely tightened or window frame thickness is incompatible.	Re-tighten the clamp brackets. Ensure your window frame thickness is between 10-23 mm.

9. SPECIFICATIONS

- **Brand:** WOLTU
- **Model Number:** WOLTU
- **Product Dimensions (L x W x H):** 220 x 60 x 0.01 cm
- **Weight:** 660 grams
- **Material:** 100% Polyester
- **Color:** White (Pleated)
- **Opacity:** Semi-transparent
- **Operation Mode:** Manual
- **Special Feature:** Dimming (light filtering)
- **Care Instructions:** Wipe with a damp cloth
- **Included Components:** Mounting kit, 4 metal clamp brackets, 4 tensioners for drilling
- **Recommended Uses:** Privacy protection
- **Specific Uses:** Office, Kitchen, Garden, Dining Room, Living Room
- **Room Type:** Kitchen (also suitable for other rooms as listed)

10. WARRANTY AND SUPPORT

For warranty information or technical support, please contact WOLTU customer service through the retailer where you purchased the product. Keep your proof of purchase for warranty claims.

Return Policy: This product typically includes a 30-day return/replacement policy. Please refer to your retailer's specific return policy for details.