

[Manuals.plus](#) /

> [GORILLA](#) /

> Gorilla Tough & Clear 1" x 60" Double Sided Mounting Tape Instruction Manual

## GORILLA Tough & Clear 1" x 60" Mounting Tape

# Gorilla Tough & Clear Double Sided Mounting Tape Instruction Manual

Model: Tough & Clear 1" x 60" Mounting Tape

### 1. PRODUCT OVERVIEW

Gorilla Tough & Clear Mounting Tape is a clear, double-sided tape designed for instant, long-lasting, and weatherproof bonding. This crystal clear tape resists yellowing over time and can hold objects weighing up to 15 pounds. It is suitable for both indoor and outdoor projects and adheres effectively to a variety of smooth and rough surfaces.

#### Key Features:

- **Crystal Clear:** Maintains clarity over time, ideal for applications where visibility is important.
- **Super Strong:** Capable of holding up to 15 lbs, providing a reliable alternative to traditional fasteners.
- **Weatherproof:** Industrial strength for durable indoor and outdoor use.
- **Permanent, Two-Way Bond:** Bonds to surfaces like glass, plastic, metal, wood, brick, ceramic, and stone in just 60 seconds.
- **Versatile:** Effective on both smooth and rough surfaces.





Image 1.1: Front view of Gorilla Tough & Clear Mounting Tape packaging.

## 2. PREPARATION AND APPLICATION

### Surface Preparation:

Ensure the surface where the tape will be applied is clean, dry, and free from dirt, dust, and oil. For optimal adhesion, clean surfaces with isopropyl alcohol and allow to dry completely.

### Application Steps:

1. **Determine Tape Length:** Apply approximately 4 inches of tape per 1 pound of weight for Gorilla Tough & Clear Mounting Tape. For Heavy-Duty Gorilla Mounting Tape, use 2 inches of tape per pound of weight.
2. **Apply Tape to Object:** Cut the desired length of tape. Apply the tape to the back of the object vertically, ensuring even

distribution of weight. Avoid touching the adhesive surfaces of the tape with your fingers. Press firmly to secure the tape to the object.



Image 2.1: Applying tape to the back of an object.

3. **Remove Liner:** Carefully remove the clear protective liner from the tape.



## FEATURES & BENEFITS

**Double-Sided Tape:** Coated with adhesive on both sides for easy hanging

**15lb. Strong Hold:** Sticks to smooth & rough surfaces\*

**Instant Hold, Permanent Bond:** Fast & Easy

**Weatherproof:** For indoor and outdoor use

**Crystal Clear Adhesive:** Won't yellow over time

\* Weight limits may vary depending on surface texture, porosity and flatness of surface. Both surfaces must be completely flat to make full contact with adhesive.

**Tip for easier liner removal:** Pinch and stretch a corner of the adhesive until the liner lifts from the tape.



## Tough & Clear Mounting Tape – 60"



## BONDS

- Plastic\*
- Metal
- Wood
- Glass
- Brick
- Ceramic
- Stone
- Drywall

And More!

\* Not for use on wallpaper, delicate surfaces, polyethylene, and polypropylene plastics, Teflon® or other non-stick surfaces



Image 2.2: Removing the clear liner.

4. **Position and Press:** Align the object to your desired placement on the surface. Press the object firmly against the surface for at least 60 seconds. Gorilla Mounting Tape conforms to the surface and creates a strong, permanent bond.



Image 2.3: Pressing the object firmly onto the surface.

#### **Important Application Guidelines:**

- Apply tape vertically for even weight distribution.
- Ensure the object depth does not exceed 0.75 inches for optimal hold.
- Tape must make complete contact with the surface.



Image 2.4: Visual guide for proper tape application and surface contact.

### 3. IMPORTANT CONSIDERATIONS

- This is a permanent tape and may cause damage or leave residue if removed.
- Not for use on applications where injury could result if mounted item falls.
- Not for use on wallpaper, delicate surfaces, polyethylene, and polypropylene plastics, Teflon® or other non-stick surfaces.
- Holding weight is based on objects with a maximum depth of 0.75 inches. Objects over 0.75 inches in depth put more stress on the bond and have an increased chance of failure.
- Tape must make contact with the surface. If the surface is uneven, the tape will not be able to make full contact and will not hold.
- Apply when the temperature is above 50°F (10°C).
- In-use temperature range: -40°F to 248°F (-40°C to 120°C).
- For easier liner removal, pinch and stretch a corner of the adhesive until the liner lifts from the tape.



manufacturer's instructions. Use 4" of tape per pound of weight.

1. Apply tape to back of object vertically, allowing for even distribution of weight. Avoid touching surface of tape.
2. Cut tape and press to secure tape to object.
3. Remove clear liner and align object to desired placement.
4. Press firmly for 60 seconds as Gorilla Mounting Tape conforms to the surface and creates a strong, permanent bond.

### IMPORTANT

- This is a permanent tape and may cause damage or leave residue if removed.
- Not for use in applications where injury could result if mounted item fell.
- \* Not for use on wallpaper, delicate surfaces, polyethylene and polypropylene plastics, Teflon® or other non-stick surfaces.

MADE IN KOREA © 2020 THE GORILLA GLUE CO.  
CINCINNATI, OH 45241 • 1-800-966-3458  
www.gorillatough.com  
104732



separation of the object over time. In separation, more stress on the bond and have an increased chance of failure.

- Tape must make contact with surface. If surface is uneven, tape will not be able to make contact & will not hold.
- Apply when temperature is above 50° F.  
In-use temperature range: -40°F to 248°F.
- For easier liner removal - Pinch and stretch a corner of the adhesive until the liner lifts from the tape.



Image 3.1: Back view of product packaging showing detailed instructions and tips.

## 4. PRODUCT SPECIFICATIONS

| Specification          | Detail                                                      |
|------------------------|-------------------------------------------------------------|
| Brand                  | GORILLA                                                     |
| Color                  | Clear                                                       |
| Material               | Acrylic                                                     |
| Number of Items        | 8 (Pack)                                                    |
| Recommended Uses       | Indoor, Outdoor                                             |
| Surface Recommendation | Glass, Metal, Plastic, Wood, Brick, Ceramic, Stone, Drywall |
| Item Type Name         | Mounting Tape                                               |
| Included Components    | (8) 60" Rolls of Clear Mounting Tape                        |

|                        |                 |
|------------------------|-----------------|
| Item Weight            | 1.12 Pounds     |
| Unit Count             | 40.0 Feet       |
| Water Resistance Level | Water Resistant |
| Tensile Strength       | 15 Pounds       |
| GTIN (UPC)             | 052427010780    |

5. PRODUCT VIDEO GUIDE

Watch the official product video for a visual demonstration of how to use Gorilla Mounting Tape effectively.

Your browser does not support the video tag.

Video 5.1: Official guide on using Gorilla Mounting Tape, demonstrating application for various projects.

6. WARRANTY AND SUPPORT

For specific warranty information or product support, please refer to the manufacturer's official website or contact their customer service directly. General return policies may vary based on the retailer.

Manufacturer: Gorilla Glue

Contact: 1-800-966-3456

Website: [www.gorillatough.com](http://www.gorillatough.com)

ASK A QUESTION ABOUT THIS MANUAL

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page’s manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. [Privacy details](#).

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question