

[Manuals.plus](#) /

› [Touch Up Express](#) /

› Touch Up Express Paint Kit User Manual for Ford Mustang PA Deep Jewel Green Metallic

Touch Up Express IE-PA-Ford-Mustang-DJ-Gal-8LIX-AS-K

Touch Up Express Paint Kit User Manual

Compatible with Ford Mustang PA Deep Jewel Green Metallic

PRODUCT OVERVIEW

This Touch Up Express paint kit is designed for small touch-ups, rock chips, scratches, or even larger areas on your vehicle. It provides an easy-to-apply, fast-drying solution with a precise color match to your original Ford Mustang PA Deep Jewel Green Metallic finish. The kit includes a 12 oz. can of base coat paint and a 12 oz. can of durable clear coat, formulated for absolute durability.

Key Features:

- Original factory paint color for a perfect match to your Green Mustang.
- Super easy application designed for professional results.
- Ideal for various types of body damage.
- High-quality urethane basecoat for durability.



Image: Two white aerosol spray cans with black caps. Each can features the 'Touch Up Express' logo, which includes a green and blue road-like symbol. These cans represent the base coat and clear coat components of the paint kit.

SETUP AND PREPARATION

1. **Safety First:** Work in a well-ventilated area. Wear appropriate personal protective equipment, including gloves, eye protection, and a respirator.
2. **Surface Cleaning:** Thoroughly clean the area to be painted. Remove all dirt, grease, wax, rust, and loose paint. Use a degreaser or wax and grease remover if necessary. Allow the surface to dry completely.
3. **Sanding (Optional but Recommended):** For best adhesion and a smooth finish, lightly sand the repair area with fine-grit sandpaper (e.g., 600-800 grit wet/dry). Feather the edges of the repair into the surrounding paint. Clean off any sanding dust.
4. **Masking:** Mask off the surrounding areas that you do not wish to paint using automotive masking tape and paper or plastic sheeting. Ensure clean, crisp edges.
5. **Temperature and Humidity:** Ensure the ambient temperature is between 60°F (15°C) and 80°F (27°C) and

humidity is low. Avoid painting in direct sunlight or extremely cold/hot conditions.

- 6. **Shake Cans:** Before use, vigorously shake both the base coat and clear coat cans for at least one minute after the mixing ball begins to rattle. Continue shaking periodically during application.

OPERATING INSTRUCTIONS (PAINT APPLICATION)

Applying the Base Coat:

- 1. **Test Spray:** Always perform a test spray on a piece of scrap material (e.g., cardboard) to check spray pattern and color match.
- 2. **First Coat:** Hold the can approximately 8-12 inches (20-30 cm) from the surface. Apply a light, even mist coat. This coat should be thin and may appear somewhat transparent.
- 3. **Subsequent Coats:** Allow 5-10 minutes flash time between coats. Apply additional light to medium coats, moving the can smoothly and consistently across the repair area. Overlap each pass by about 50%.
- 4. **Color Coverage:** Continue applying coats until the desired color coverage is achieved and the repair area blends seamlessly with the surrounding paint. Avoid applying heavy coats to prevent runs or drips.
- 5. **Drying Time:** Allow the base coat to dry for at least 30-60 minutes before applying the clear coat. Drying time may vary depending on temperature and humidity. The base coat should appear dull and flat when ready for clear coat.

Applying the Clear Coat:

- 1. **Shake Can:** Vigorously shake the clear coat can for at least one minute before use.
- 2. **First Coat:** Apply a light mist coat of clear coat over the base coat.
- 3. **Subsequent Coats:** After 5-10 minutes flash time, apply 2-3 medium wet coats of clear coat. Hold the can 8-12 inches (20-30 cm) from the surface and apply with smooth, even passes. The clear coat should appear glossy as it is applied.
- 4. **Final Drying:** Allow the clear coat to dry for at least 24 hours before handling or exposing to moisture. Full cure can take several days to weeks, depending on conditions.

MAINTENANCE

Once the paint has fully cured, treat the repaired area like the rest of your vehicle's finish. Avoid harsh chemicals or abrasive cleaning for the first few weeks. Regular washing with mild automotive soap and water is recommended. For optimal protection and shine, consider waxing or sealing the entire vehicle, including the repaired area, after the paint has fully cured (typically 30 days).

TROUBLESHOOTING

Problem	Possible Cause	Solution
Runs or Sags	Too much paint applied in one coat; can held too close; painting in cold conditions.	Apply thinner coats. Hold can at recommended distance. Ensure proper temperature. Allow to dry, then sand smooth and reapply.
Uneven Finish / Orange Peel	Can held too far; insufficient paint; improper surface preparation; painting in hot/dry conditions.	Hold can at recommended distance. Apply even, consistent coats. Ensure proper surface prep. Adjust conditions or technique.

Problem	Possible Cause	Solution
Poor Adhesion / Peeling	Improper surface cleaning (grease, wax); not sanding; painting over incompatible paint.	Thoroughly clean and degrease surface. Lightly sand for mechanical adhesion. Ensure compatibility.
Dull Finish (Clear Coat)	Insufficient clear coat applied; clear coat not fully cured; painting in high humidity.	Apply recommended number of clear coats. Allow full cure time. Ensure low humidity. Can be buffed/polished after full cure.

SPECIFICATIONS

Brand	Touch Up Express
Model Number	IE-PA-Ford-Mustang-DJ-Gal-8LIX-AS-K
Color	Green (PA Deep Jewel Green Metallic)
Finish Type	Gloss
Size	2 can kit (1 base coat, 1 clear coat)
Item Volume	12 Fluid Ounces (per can)
Paint Type	Spray (Aerosol)
Material	Urethane
Item Weight	21 pounds (shipping weight)
Product Dimensions	15 x 15 x 15 inches (package dimensions)
UPC	719695642449

WARRANTY INFORMATION

This product is covered by the manufacturer's standard warranty against defects in materials and workmanship. For specific warranty terms and conditions, please refer to the packaging or contact Touch Up Express directly. Keep your purchase receipt as proof of purchase.

CUSTOMER SUPPORT

For technical assistance, product inquiries, or support regarding your Touch Up Express paint kit, please contact the manufacturer directly. Contact information can typically be found on the product packaging or on the official Touch Up Express website.

Note: Always refer to the specific instructions on the product cans for the most accurate and up-to-date application guidelines.

ASK A QUESTION ABOUT THIS MANUAL

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. [Privacy details](#).

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question

Open the live page

<https://manuals.plus/asin/B01N4B3Q10>

More documents and user manuals: <https://manuals.plus/>