

[Manuals.plus](#) /

› [Yale Security](#) /

› Yale AU4602LN x 626 Cylindrical Lockset, Grade 2, Privacy Function, 2 3/4" Backset, 626 Satin Chrome Finish AU4602LN x 626-Privacy Function Satin Chrome Finish

Yale Security 085091

Yale AU4602LN x 626 Cylindrical Lockset User Manual

Brand: Yale Security | Model: 085091

PRODUCT OVERVIEW

The Yale AU4602LN x 626 Cylindrical Lockset is a Grade 2 privacy function lever handle lockset, featuring a satin chrome finish (626) and fire rating for up to three hours. It is designed with a 2 3/4" backset, offering both security and an elegant appearance for various applications.

Key Features

- UL Fire Listed for Doors Rated up to and Including Three Hours
- ADA Uniform Federal Accessibility Standards and ANSI A117.1 Compliant
- Durable Cast Zinc, Wrought Brass, and Steel Construction
- Easy to Install Design



Image: Yale AU4602LN x 626 Cylindrical Lockset, showcasing its satin chrome finish and lever design.

SETUP

The Yale Cylindrical Lockset is designed for straightforward installation, typically taking less than five minutes to assemble. The package includes the necessary locking sets, handles, the tongue (latch bolt), and the strike plate for a complete setup.

Installation Steps:

1. Ensure the door is prepped with the correct bore holes for a standard cylindrical lockset.
2. Insert the latch bolt (tongue) into the door edge, securing it with screws.
3. Align the exterior and interior lever assemblies with the latch bolt, ensuring the spindle engages correctly.
4. Secure the assemblies with the provided through-bolts or screws.
5. Install the strike plate on the door frame, aligning it with the latch bolt.
6. Test the operation of the lockset to ensure smooth opening, closing, and locking.

OPERATING INSTRUCTIONS

Normal Operation:

To open the door, simply depress the lever handle. The latch bolt will retract, allowing the door to open. Release the handle to allow the latch bolt to extend and secure the door when closed.

Privacy Function:

The lockset features a privacy button on the interior side of the handle. To engage the privacy lock, press the button. This

will prevent the exterior handle from operating the latch, securing the room. The interior handle will always operate the latch for emergency egress.

Emergency Unlocking:

In case of an emergency or if someone is locked inside, the privacy lock can be disengaged from the exterior. Locate the small slot on the exterior handle's spindle. Insert a coin or a flat-head tool into this slot and twist to unlock the mechanism, allowing the door to be opened.

MAINTENANCE

To ensure the longevity and optimal performance of your Yale Cylindrical Lockset, regular maintenance is recommended:

- **Cleaning:** Wipe the lockset surfaces with a soft, damp cloth. Avoid abrasive cleaners or solvents that could damage the finish.
- **Lubrication:** Periodically apply a small amount of graphite lubricant or a silicone-based spray to the latch mechanism and internal moving parts to ensure smooth operation. Do not use oil-based lubricants as they can attract dust and debris.
- **Inspection:** Regularly check all screws and fasteners to ensure they are tight. Inspect the handles and latch for any signs of wear or damage.

TROUBLESHOOTING

If you encounter issues with your Yale Cylindrical Lockset, consider the following:

- **Sticking Latch:** If the latch bolt is sticking, ensure it is clean and properly lubricated. Check if the strike plate on the door frame is correctly aligned with the latch.
- **Loose Handles:** If the handles feel loose, check and tighten the mounting screws or through-bolts that secure the lockset to the door.
- **Privacy Button Malfunction:** If the privacy button does not engage or disengage properly, inspect for any obstructions or debris. If the issue persists, the internal mechanism may require professional inspection.
- **Door Not Latching:** Verify that the strike plate on the door frame is aligned with the latch bolt. Adjust the strike plate position if necessary.

For persistent issues not resolved by these steps, please contact Yale Security customer support.

SPECIFICATIONS

Feature	Detail
Brand	Yale Security
Model Number	085091
Product Dimensions	7.3 x 6.8 x 3.8 inches; 3.55 Pounds
Lock Type	Cylindrical
Material	Cast Zinc, Wrought Brass, Steel
Special Feature	Easy to Install
Manufacturer	ASSA ABLOY

Date First Available

April 23, 2015

WARRANTY AND SUPPORT

For information regarding product warranty, returns, or technical support, please refer to the official Yale Security website or contact their customer service directly. Details on specific protection plans may also be available through your point of purchase.

ASK A QUESTION ABOUT THIS MANUAL

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. [Privacy details](#).

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question