

[Manuals.plus](#) /

› [HeoSolution](#) /

› HEOSafe Typ 12646 f. Ducato 250/Boxer/Jumper ab Bj. 2006 - Standard

HeoSolution 12646



HEOSafe Typ 12646 Door Lock Instruction Manual

Model: 12646 | Brand: HeoSolution

1. PRODUCT OVERVIEW

The HEOSafe Typ 12646 is a robust deadbolt lock designed for vehicle doors, specifically for Fiat Ducato 250, Peugeot Boxer, and Citroen Jumper models from year 2006 onwards. This standard version is non-lockable and provides enhanced security by being mounted directly to the door frame. It is supplied as a pair, offering protection for both driver and passenger cabin doors.

- Integrated anti-theft devices for cabin doors.
- Made from durable cast aluminum.
- Supplied as a pair for two doors.
- Color: Black.

2. SAFETY INFORMATION

Please read all instructions carefully before installation and use. Improper installation or use may lead to damage or injury. Always ensure the lock is fully engaged before driving. Do not attempt to modify the product.

- Ensure the vehicle is parked safely and the engine is off before installation.
- Keep small parts away from children.
- Use appropriate tools for installation to prevent damage to the vehicle or product.

3. PACKAGE CONTENTS

The HEOSafe Typ 12646 package includes the following items:

- 2 x HEOSafe Typ 12646 Standard Door Locks (non-lockable)
- Mounting hardware (screws, washers, etc.)
- Installation instructions (this manual)

4. SETUP AND INSTALLATION

The HEOSafe Typ 12646 locks are designed for quick and easy mounting on the vehicle's door frame. No special tools are typically required beyond standard hand tools.

1. **Identify Mounting Location:** The locks are installed on the inside of the cabin doors, integrated into the armrest area or similar sturdy part of the door frame. Refer to your vehicle's specific interior design for optimal placement.
2. **Prepare Surface:** Ensure the mounting surface on the door frame is clean and free of debris.
3. **Position the Lock:** Place the HEOSafe lock against the door frame in the desired position. Ensure it does not obstruct any vehicle functions (e.g., window operation, door handle). The bolt should align with a secure point on the door itself when closed.
4. **Mark Drilling Points:** Use a pencil or marker to mark the positions for the mounting screws through the holes on the lock's base plate.
5. **Drill Pilot Holes:** Carefully drill pilot holes at the marked positions. Use a drill bit appropriate for the screw size and the material of your door frame.
6. **Secure the Lock:** Attach the HEOSafe lock to the door frame using the provided screws. Tighten securely, but do not overtighten to avoid damaging the frame or the lock.
7. **Test Operation:** After installation, close the door and test the lock's operation. Ensure the bolt extends and retracts smoothly and securely engages with the door.



Image: HEOSafe lock installed on the vehicle's door frame, showing its position near the window.



Image: Close-up view of the HEOSafe lock, highlighting the white knob for manual operation.

5. OPERATING INSTRUCTIONS

The HEOSafe Typ 12646 Standard version is a manually operated deadbolt. It does not require a key for operation.



Image: The HEOSafe Typ 12646 Standard lock, showing its black body and white manual knob.

1. **To Engage the Lock:** With the vehicle door closed, turn the white knob on the HEOSafe lock. This will extend the bolt from the lock body into the corresponding receiver on the door, securing it. Ensure the bolt is fully extended for maximum security.
2. **To Disengage the Lock:** Turn the white knob in the opposite direction. This will retract the bolt, allowing the door to be opened normally.

Always ensure the lock is disengaged before attempting to open the door to prevent damage to the lock or door mechanism.

6. MAINTENANCE

The HEOSafe Typ 12646 is designed for durability and requires minimal maintenance. Regular inspection and cleaning will ensure its longevity and reliable operation.

- **Cleaning:** Wipe the lock body with a soft, damp cloth to remove dust and dirt. Avoid using abrasive cleaners or solvents that could damage the finish.
- **Lubrication:** Periodically apply a small amount of silicone spray or a light lubricant to the moving parts of the bolt mechanism to ensure smooth operation. Do not over-lubricate.
- **Inspection:** Regularly check the mounting screws to ensure they are tight. Inspect the lock body for any signs of damage or wear. If any damage is observed, contact the manufacturer or a qualified technician.

7. TROUBLESHOOTING

If you encounter issues with your HEOSafe Typ 12646 lock, refer to the following common problems and solutions:

- **Lock is difficult to engage/disengage:**

- Check for any obstructions preventing the bolt from moving freely.
 - Apply a small amount of lubricant to the bolt mechanism.
 - Ensure the door is fully closed and aligned correctly when attempting to engage the lock.
- **Lock feels loose after installation:**
 - Check and tighten all mounting screws. Do not overtighten.
 - Ensure the mounting surface is stable and not damaged.

If the problem persists after attempting these solutions, please contact HeoSolution customer support.

8. SPECIFICATIONS

Feature	Specification
Model Number	12646
Brand	HeoSolution
Product Type	Vehicle Door Deadbolt Lock
Version	Standard (non-lockable)
Material	Aluminum
Quantity	2 pieces (for a pair of doors)
Color	Black
Compatibility	Fiat Ducato 250, Peugeot Boxer, Citroen Jumper (from 2006 onwards)

9. WARRANTY AND SUPPORT

For information regarding warranty coverage, terms, and conditions for your HEOSafe Typ 12646 door locks, please refer to the documentation provided with your purchase or visit the official HeoSolution website. For technical support, installation assistance, or spare parts inquiries, please contact HeoSolution customer service directly through their official channels.

© 2024 HeoSolution. All rights reserved.

ASK A QUESTION ABOUT THIS MANUAL

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page’s manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. [Privacy details](#).

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question