

Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

[manuals.plus](#) /

› [Taylor](#) /

› [Taylor 1476FDA Compact Folding Probe Digital Thermometer User Manual](#)

Taylor 1476FDA

Taylor 1476FDA Compact Folding Probe Digital Thermometer

Model: 1476FDA

PRODUCT OVERVIEW

The Taylor 1476FDA Compact Folding Probe Digital Thermometer is designed for accurate temperature measurement in various applications, particularly in commercial kitchen environments. Its compact, folding design, along with a magnet and lanyard, ensures convenient storage and accessibility. This thermometer features a digital display for clear readings and an auto-off function to conserve battery life.



Image: The Taylor 1476FDA thermometer with its probe extended, displaying a temperature. This compact device is blue with a clear digital screen.

SETUP

The Taylor 1476FDA thermometer comes with one LR44 battery included and pre-installed. Before first use, ensure the battery is properly seated and remove any protective tabs if present.

Battery Installation/Replacement

1. Locate the battery compartment on the back of the thermometer.
2. Use a small screwdriver to open the battery cover.

3. Insert one LR44 battery, ensuring the correct polarity (+/-) as indicated inside the compartment.
4. Replace the battery cover and secure it with the screw.



Image: A visual representation of various button cell batteries, emphasizing the type of battery used in the device. A warning about ingestion hazard is visible, highlighting the importance of keeping batteries away from children.

WARNING: This product contains a button cell or coin battery. Ingestion can cause severe injury or death. Keep batteries out of reach of children. If swallowed, seek immediate medical attention.

OPERATING INSTRUCTIONS

Taking a Temperature Reading

1. Unfold the probe from the thermometer body. This action typically turns the unit on.
2. Insert the stainless steel probe into the center of the food or liquid being measured. Ensure the probe tip is fully immersed and not touching the bottom or sides of the container.
3. Wait for the digital display to stabilize. The temperature will be shown on the LCD screen.
4. The thermometer has a temperature range of -40°F to 392°F (-40°C to 200°C).
5. To switch between Fahrenheit (°F) and Celsius (°C), locate the F/C button, usually on the back or side of the unit, and press it.

- Once the reading is complete, remove the probe.
- Fold the probe back into the thermometer body to turn the unit off. The auto-off feature will also turn the unit off after a period of inactivity to conserve battery life.

MAINTENANCE

Cleaning and Storage

- After each use, wipe the stainless steel probe with a damp cloth and mild detergent.
- Do not immerse the entire thermometer body in water. The main unit is not waterproof.
- Dry the probe thoroughly before folding it back into the unit.
- Store the thermometer in a clean, dry place. The integrated magnet allows for convenient storage on metallic surfaces, and the lanyard provides an additional carrying option.

TROUBLESHOOTING

- Display shows 'Lo' or 'Hi' / Out of Range:** This indicates the temperature being measured is outside the thermometer's operating range (-40°F to 392°F).
- Inaccurate Readings:** Ensure the probe is inserted correctly into the center of the item and not touching the container. Check battery level; a low battery can affect accuracy. This thermometer is designed to be factory calibrated and does not feature user calibration.
- Display is Blank or Faint:** Replace the LR44 battery. Ensure the battery is inserted with correct polarity.
- Unit Does Not Turn On/Off:** Ensure the probe is fully extended to turn on and fully folded to turn off. If the issue persists, replace the battery.
- Cannot Switch Between °F/°C:** Press the F/C button firmly. If the display momentarily changes then reverts, try replacing the battery.

SPECIFICATIONS

| Feature | Detail |
|---------------------|--|
| Model Number | 1476FDA |
| Temperature Range | -40°F to 392°F (-40°C to 200°C) |
| Power Source | 1 x LR44 Battery (included) |
| Display Type | Digital LCD |
| Material | Plastic body, Stainless Steel probe |
| Special Features | Folding Probe, Auto-Off, Magnet, Lanyard |
| Dimensions (folded) | Approx. 6.60" H x 5.06" W x 0.75" L |

WARRANTY AND SUPPORT

For warranty information or technical support, please refer to the contact details provided on the product packaging or visit the official Taylor brand website. Keep your purchase receipt as proof of purchase for any warranty claims.

© 2025 Taylor. All rights reserved.