

[Manuals.plus](#) /

› [WorkZone](#) /

› WorkZone 6" Olive WP COMP Toe - C640OLV User Manual

WorkZone C640OLV

WorkZone 6" Olive WP COMP Toe - C640OLV User Manual

Model: C640OLV

INTRODUCTION

This manual provides essential information for the proper use, care, and maintenance of your WorkZone 6" Olive WP COMP Toe safety boots. Please read this manual thoroughly before using the product to ensure optimal performance and safety.



Image: A WorkZone 6-inch Olive Waterproof Composite Toe Boot, C640OLV, shown from the side. The boot features a brown nubuck leather upper, dark brown laces, and a black sole. White stitching and a reflective stripe are visible on the side. The word "WATERPROOF" is embossed on the side of the boot.

PRODUCT FEATURES

- 6" Waterproof Nubuck Leather Hiker Safety Boot
- Non-Metallic Composite Toe (C640) for safety
- Reflective Trim for enhanced visibility and safety
- COMFORTTUF Removable Footbed for cushioning and support

- Moisture Absorbent Lining to keep feet dry
- Lightweight PU Dual Density Sole for comfort and durability
- Electrical Hazard (EH) protection
- Oil and Slip Resistant Rubber Sole for improved traction
- Shaft measures approximately mid calf from arch
- Heel measures approximately 6 inches

SETUP

Your WorkZone safety boots are designed for immediate use. Follow these steps for initial setup:

1. **Unpacking:** Remove the boots from their packaging. Inspect them for any visible damage or defects.
2. **Lacing:** Ensure the laces are properly threaded through all eyelets. Adjust the lacing to achieve a snug, comfortable fit around your foot and ankle. Do not overtighten, as this can restrict circulation.
3. **Initial Fit:** Wear the boots with the type of socks you typically use for work. Walk around to assess the fit. Your toes should have room to wiggle, and your heel should not slip excessively. The removable COMFORTTUF footbed can be adjusted or replaced if needed for personalized comfort.

OPERATING INSTRUCTIONS

These boots are intended for use in environments requiring safety footwear, offering protection against various hazards. Always ensure the boots are properly laced and fitted before beginning work.

- **Intended Use:** These boots are designed for industrial, construction, and general work environments where foot protection, slip resistance, and electrical hazard protection are required.
- **Safety Features:** The non-metallic composite toe provides impact and compression protection. The electrical hazard (EH) sole reduces the risk of electric shock on dry surfaces. The oil and slip-resistant rubber sole enhances traction on various surfaces.
- **Proper Wear:** Always wear appropriate socks to prevent blisters and manage moisture. Ensure the boots are securely fastened to provide ankle support and prevent tripping hazards.

MAINTENANCE AND CARE

Proper maintenance will extend the life and performance of your WorkZone safety boots.

- **Cleaning:**
 - For general dirt, wipe the nubuck leather with a damp cloth.
 - For stubborn stains, use a specialized nubuck cleaner and a soft brush.
 - Clean the soles regularly to remove debris that could affect slip resistance.
- **Drying:** If boots become wet, allow them to air dry naturally at room temperature. Avoid direct heat sources like radiators or hair dryers, as this can damage the leather and adhesives.
- **Conditioning:** Periodically apply a waterproof and conditioning spray specifically designed for nubuck leather to maintain its water resistance and appearance.
- **Storage:** Store boots in a cool, dry place away from direct sunlight when not in use.
- **Footbed Care:** The removable COMFORTTUF footbed can be removed and air-dried if it becomes damp.

TROUBLESHOOTING

Issue	Possible Cause	Solution
Discomfort or rubbing	Improper lacing, incorrect size, or new boot break-in period.	Adjust lacing for a snug but not tight fit. Ensure you are wearing appropriate socks. Allow time for boots to break in. If discomfort persists, verify size.
Reduced water resistance	Wear and tear, lack of conditioning.	Clean boots and apply a suitable waterproofing spray for nubuck leather. Inspect for physical damage.
Slipping on surfaces	Accumulation of dirt/debris on sole, worn sole tread.	Clean the sole thoroughly. If the tread is significantly worn, consider replacing the boots for safety.

SPECIFICATIONS

Feature	Detail
Model	C640OLV
Brand	WorkZone
Department	Unisex-Adult
Outer Material	Nubuck Leather
Sole Material	Rubber (Dual Density PU)
Toe Type	Non-Metallic Composite Toe
Shaft Height	Mid Calf (approx. 6 inches from arch)
Closure Type	Lace-Up
Special Features	Waterproof, Reflective Trim, COMFORTTUF Removable Footbed, Moisture Absorbent Lining, Electrical Hazard (EH) Protection, Oil and Slip Resistant Sole
Manufacturer	WORK ZONE
First Available	August 10, 2017

WARRANTY AND SUPPORT

For information regarding warranty coverage or product support, please refer to the documentation provided at the time of purchase or contact WorkZone customer service directly. Specific warranty terms may vary.

ASK A QUESTION ABOUT THIS MANUAL

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page’s manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. [Privacy details](#).

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question