

MOUNTO AM30LO C

MOUNTO 1/4 HP 1200 CFM Low Profile Air Mover (Model AM30LO C) Instruction Manual

Brand: MOUNTO | Model: AM30LO C

1. INTRODUCTION

This manual provides essential information for the safe and effective operation, maintenance, and troubleshooting of your MOUNTO 1/4 HP 1200 CFM Low Profile Air Mover. Designed for efficient drying and air circulation, this unit is suitable for various applications including water damage restoration, construction, and general cleaning tasks. Please read this manual thoroughly before operating the unit and retain it for future reference.

2. SAFETY INFORMATION

WARNING: To reduce the risk of fire, electric shock, or injury, always follow basic safety precautions when using electrical appliances.

- Always connect to a properly grounded outlet.
- Do not operate any fan with a damaged cord or plug. Discard fan or return to an authorized service facility for examination and/or repair.
- Do not run cord under carpeting. Do not cover cord with throw rugs, runners, or similar coverings. Arrange cord away from traffic area and where it will not be tripped over.
- Do not use the air mover in wet or damp conditions where water can enter the motor or electrical components.
- Keep children and pets away from the operating unit.
- Always unplug the unit before cleaning or performing any maintenance.
- Ensure proper ventilation when operating in enclosed spaces.
- Do not block air intakes or outlets.

3. PRODUCT OVERVIEW

The MOUNTO Low Profile Air Mover is a powerful and durable unit designed for efficient air circulation and

drying. Key features include:

- **Powerful Motor:** Equipped with a 1/4 HP 2-speed motor, delivering up to 1200 CFM airflow.
- **Low Profile Design:** Allows the unit to fit into tight spaces, such as under furniture or inside cabinets.
- **Stackable:** Designed for easy storage and transportation, allowing up to 5 units to be stacked.
- **Integrated GFCI Outlets:** Dual GFCI outlets provide additional safety and allow for daisy-chaining multiple units.
- **Durable Construction:** Crafted with high-quality Roto-Molding Plastic for demanding environments.
- **Long Power Cord:** Features a 25ft 14AWG power cord for extended reach.
- **ETL Certified:** Ensures superior safety and quality standards.



Figure 1: Top-down view of the MOUNTO Low Profile Air Mover.



Figure 2: Angled view of the MOUNTO Low Profile Air Mover, showcasing its compact design.

4. SETUP

1. **Unpack the Unit:** Carefully remove the air mover from its packaging. Inspect for any shipping damage.
2. **Positioning:** Place the air mover on a stable, level surface. The low-profile design allows for placement under cabinets or in confined spaces. The unit can also be positioned on its side or angled using its integrated stand for directing airflow upwards or across walls.
3. **Power Connection:** Uncoil the 25ft power cord and plug it into a standard 120V AC grounded electrical outlet. Ensure the outlet is rated for the unit's power requirements (230 watts).
4. **Daisy-Chaining (Optional):** For larger areas or increased airflow, multiple MOUNTO air movers can be daisy-chained using the dual GFCI outlets located on the control panel. Ensure the total current draw does not exceed 10 amps for the daisy-chained units.



Figure 3: Multiple MOUNTO Air Movers stacked for storage or transport.

5. OPERATING INSTRUCTIONS

1. **Power On/Off:** Locate the red rocker switch on the control panel. Press the "I" side of the switch to turn the unit ON, and the "O" side to turn it OFF.
2. **Speed Selection:** The unit features two speed settings. The rocker switch allows you to select between Speed 1 (lower airflow) and Speed 2 (higher airflow). Adjust as needed for your drying requirements.
3. **GFCI Outlets:** The integrated dual GFCI outlets are protected by a 12-amp circuit breaker. If the breaker trips (power to outlets cuts off), press the "RESET" button on the control panel to restore power.
4. **Monitoring:** Allow the air mover to operate until the desired area is dry. Periodically check the drying progress.

Your browser does not support the video tag.

Video 1: Demonstration of the MOUNTO Air Mover in operation, showing the power switch and airflow.



Figure 4: Close-up of the control panel, highlighting the power switch, dual GFCI outlets, and reset button.

6. MAINTENANCE

Regular maintenance ensures optimal performance and extends the lifespan of your air mover.

- **Cleaning:** Periodically wipe down the exterior of the unit with a damp cloth. Do not use harsh chemicals or abrasive cleaners. Ensure the unit is unplugged before cleaning.
- **Air Intake/Outlet:** Keep the air intake and outlet grilles free from dust, debris, and obstructions. Use a vacuum cleaner or compressed air to clear any blockages.
- **Cord Inspection:** Regularly inspect the power cord for any signs of damage, fraying, or cuts. If damaged, discontinue use and have it repaired by a qualified technician.
- **Storage:** When not in use, coil the power cord neatly around the unit. Store the air mover in a clean, dry place. Its stackable design allows for efficient storage.



Figure 5: MOUNTO Air Mover with its power cord neatly wrapped for storage.

7. TROUBLESHOOTING

Problem	Possible Cause	Solution
Unit does not turn on.	No power to the outlet; Power switch is OFF; Circuit breaker tripped.	Check power supply; Ensure switch is ON; Press the "RESET" button on the control panel.
Reduced airflow.	Air intake/outlet blocked; Fan blades dirty.	Clear any obstructions; Clean grilles and fan blades (ensure unit is unplugged).

Problem	Possible Cause	Solution
Unusual noise or vibration.	Loose components; Debris in fan; Unit not on a stable surface.	Inspect for loose parts; Remove debris (unplug first); Place on a stable surface. If problem persists, contact support.

8. SPECIFICATIONS

Feature	Detail
Brand	MOUNTO
Model Name	AM30LO C
Power Source	Corded Electric
Motor Horsepower	1/4 HP
Air Flow Capacity	1200 Cubic Feet Per Minute (CFM)
Number of Power Levels	2
Voltage	120 Volts (AC)
Wattage	230 watts
Noise Level	65 Decibels
Product Dimensions	21"D x 9.5"W x 16"H
Item Weight	22 Pounds
Included Components	25ft Power Cord, Dual GFCI Outlet
Material	Roto-Molding Plastic
Certification	ETL

9. WARRANTY AND SUPPORT

For warranty information or technical support, please contact MOUNTO customer service. Keep your purchase receipt and model number (AM30LO C) handy for faster service.

Manufacturer: MOUNTO

Website: [Visit the MOUNTO Store on Amazon](#)