



Manuals.plus /

- › ODI /
- › ODI ATV X-Treme Lock-On Grips (Graphite) Instruction Manual

ODI J30XTH-U

ODI ATV X-Treme Lock-On Grips

Model: J30XTH-U

INTRODUCTION

This manual provides comprehensive instructions for the installation, operation, and maintenance of your ODI ATV X-Treme Lock-On Grips. Please read this manual thoroughly before installation and use to ensure proper function and longevity of your product.

PRODUCT OVERVIEW

The ODI X-Treme Lock-On Grips are engineered for optimal traction and control on ATVs. Featuring a unique design, these grips ensure a secure hold in various conditions.

Key Features:

- Designed for optimal traction regardless of condition.
- Tacky diamond plate pads provide exceptional grip.
- Small 3/4 flange helps keep hands securely on the bars.
- 100% slip-free performance guaranteed with ODI's Patented Lock-On system.
- Available in 130mm length.



Image of the ODI ATV X-Treme Lock-On Grip, showcasing its design and texture. The grip features a diamond plate pattern for enhanced traction and a small 3/4 flange.

SETUP AND INSTALLATION

Proper installation is crucial for the performance and safety of your ODI Lock-On Grips. Follow these steps carefully:

- 1. Prepare Handlebars:** Ensure your ATV handlebars are clean and free from any old grip residue, dirt, or grease. Use a suitable cleaner if necessary and allow to dry completely.
- 2. Remove Old Grips (if applicable):** If replacing existing grips, carefully cut or slide off the old grips. Remove any old glue or adhesive.
- 3. Install Throttle Side Grip:** Slide the grip onto the throttle tube. Ensure the grip is fully seated against the throttle housing. The lock-on clamp should be positioned correctly.
- 4. Install Clutch Side Grip:** Slide the grip onto the clutch side of the handlebar. Ensure it is fully seated.
- 5. Tighten Lock-On Clamps:** Using an appropriate hex key, tighten the lock-on clamps on both grips. Do not overtighten; tighten until the grips are secure and do not rotate. Refer to your ATV's manual for specific torque specifications if available, or tighten firmly by hand.
- 6. Test Grips:** Before riding, ensure both grips are firmly in place and do not slip or rotate. Check throttle operation for smooth movement.

Note: Always ensure the throttle operates freely and returns to the idle position without obstruction after grip installation.

OPERATING INSTRUCTIONS

The ODI X-Treme Lock-On Grips are designed for immediate use after proper installation. Their primary function is to provide a secure and comfortable interface between the rider and the ATV handlebars.

- **Secure Hold:** The patented Lock-On system ensures the grips remain firmly in place, preventing unwanted rotation or slipping during aggressive riding.
- **Enhanced Traction:** The tacky diamond plate pattern provides superior grip, allowing for better control and reduced hand fatigue, especially in wet or muddy conditions.
- **Comfort:** The material and design are optimized for rider comfort, absorbing vibrations and providing a consistent feel.

No special operating procedures are required beyond standard ATV riding practices. Focus on maintaining a firm but relaxed grip for optimal control.

MAINTENANCE

Regular maintenance will extend the life and performance of your ODI X-Treme Lock-On Grips.

- **Cleaning:** Clean grips regularly with mild soap and water. Avoid harsh chemicals or solvents that could degrade the grip material. Rinse thoroughly and allow to air dry.
- **Inspection:** Periodically inspect the grips for signs of wear, tears, or damage. Check the lock-on clamps to ensure they remain tight. If any damage is observed, consider replacing the grips for safety.
- **Storage:** When not in use for extended periods, store your ATV in a clean, dry environment away from direct sunlight and extreme temperatures to prevent material degradation.

TROUBLESHOOTING

If you encounter issues with your ODI X-Treme Lock-On Grips, refer to the following common problems and solutions:

Problem	Possible Cause	Solution
Grips rotate or slip on handlebars.	Lock-on clamps are not sufficiently tightened.	Ensure clamps are tightened firmly with an appropriate hex key. Do not overtighten.
Grips feel loose after installation.	Incorrect grip size for handlebars, or clamps not fully engaged.	Verify grip size matches handlebar diameter. Re-install, ensuring grips are fully seated and clamps are properly engaged and tightened.
Reduced traction or worn surface.	Normal wear and tear, or accumulation of dirt/oil.	Clean grips thoroughly. If wear is significant, consider replacing the grips for optimal performance and safety.

SPECIFICATIONS

Model Name	ATV Xtreme Lock-On Grips
Part Number	J30XTH-U
Brand	ODI (Old Dutch International)
Vehicle Service Type	ATV
Color	Graphite
Size	130mm
Item Weight	0.35 Pounds
Number of Items	2
UPC	711484187766
Item Dimensions (LxWxH)	7.9 x 4.7 x 2.3 inches
Package Dimensions (LxWxH)	8 x 8 x 3 inches

WARRANTY AND SUPPORT

For warranty information or technical support regarding your ODI ATV X-Treme Lock-On Grips, please contact the manufacturer directly. Details can typically be found on the official ODI website or through your authorized dealer.

Please retain your proof of purchase for any warranty claims.