Saved from manuals.plus.
Open the live page for links to other documents and user manuals.

Biker's Choice 351027

Instruction Manual

Biker's Choice 351027 Legacy Gas Tank Rubber Pads

Introduction

This manual provides essential information for the proper installation, use, and maintenance of your Biker's Choice 351027 Legacy Gas Tank Rubber Pads. Adhering to these instructions will ensure optimal performance and longevity of the product. Please read this manual thoroughly before proceeding with installation.

Safety Information

Always prioritize safety when working on your motorcycle. Ensure the motorcycle is stable and secure before beginning any installation. Wear appropriate personal protective equipment, such as gloves and eye protection, if necessary. Keep all tools and materials away from moving parts and hot surfaces. If you are unsure about any step, consult a qualified motorcycle technician.

Package Contents

- One (1) pair of Biker's Choice 351027 Legacy Gas Tank Rubber Pads

Setup and Installation

The Biker's Choice 351027 Legacy Gas Tank Rubber Pads are designed for straightforward installation. Follow these steps carefully:

1. **Prepare the Surface:** Ensure the surface of your motorcycle's gas tank where the pads will be applied is clean, dry, and free of any wax, grease, oil, or debris. Use a suitable degreaser or alcohol wipe to thoroughly clean the area. Allow the surface to dry completely.
2. **Test Fit:** Before removing the adhesive backing, carefully position each rubber pad on the gas tank to determine the desired placement. Mark the position with a non-permanent marker or masking tape if needed.
3. **Apply the Pads:** Peel off the protective backing from the adhesive side of one pad. Carefully align the pad with your pre-determined position on the gas tank. Begin by pressing one edge down and slowly work your way across the pad, applying firm, even pressure to ensure full contact and to eliminate air bubbles.

4. **Repeat for Second Pad:** Follow the same procedure for the second rubber pad on the opposite side of the gas tank.
5. **Curing Time:** After installation, avoid washing the motorcycle or exposing the pads to excessive moisture for at least 24-48 hours to allow the adhesive to fully cure and bond to the tank surface.



This image displays two black rubber pads, designed with a textured, ribbed surface for grip and a smooth outer edge for adhesion. These pads are specifically for motorcycle gas tanks.

Operating

Once installed, the Legacy Gas Tank Rubber Pads provide enhanced grip and protection for your motorcycle's gas tank. They are designed to offer a comfortable and secure contact point for your knees, reducing fatigue and improving control during rides. The rubber material also helps to protect the tank's paint finish from scratches and wear caused by riding gear.

Maintenance

To ensure the longevity and appearance of your gas tank rubber pads, follow these maintenance guidelines:

- **Cleaning:** Clean the pads regularly with mild soap and water. Avoid harsh chemicals or abrasive cleaners, as these

can damage the rubber material or the adhesive. Rinse thoroughly and allow to air dry.

- **Inspection:** Periodically inspect the pads for any signs of wear, cracking, or peeling. Ensure the edges remain firmly adhered to the gas tank.
- **Adhesion Check:** If any part of the pad begins to lift, gently press it back into place. If the adhesive has lost its effectiveness, the pad may need to be re-adhered with a suitable automotive-grade adhesive or replaced.

Troubleshooting

- **Pads Not Adhering Properly:**
  - Ensure the gas tank surface was thoroughly cleaned and dry before application. Any residue (wax, oil, dirt) will prevent proper adhesion.
  - Verify that sufficient, even pressure was applied during installation.
  - Allow adequate curing time (24-48 hours) before exposing to moisture or stress.
- **Pads Showing Premature Wear:**
  - Inspect for abrasive contact with riding gear or other objects.
  - Ensure proper cleaning methods are used; harsh chemicals can degrade the rubber.

Specifications

Brand	Biker's Choice
Model Number	351027
Material	Rubber
Fit Type	Universal
Vehicle Service Type	Motorcycle
Item Weight	1 Pound (approximate, for packaging)
Product Dimensions	12 x 10 x 6 inches (approximate, for packaging)
UPC	887337309316

Warranty Information

Specific warranty details for the Biker's Choice 351027 Legacy Gas Tank Rubber Pads are not provided in this manual. For information regarding warranty coverage, terms, and conditions, please refer to the original product packaging or contact Biker's Choice directly through their official website or customer service channels.

Support

If you have any questions, require assistance with installation, or encounter issues not covered in this manual, please contact the manufacturer, Biker's Choice, or the retailer from whom you purchased the product. Provide your product model number (351027) and a detailed description of your inquiry for efficient support.

© 2023 Biker's Choice. All rights reserved.

Ask a question about this manual

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. Privacy details.

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question

Open the live page

https://manuals.plus/asin/B0722TSPDT

More documents and user manuals: **https://manuals.plus/**