**Saved from manuals.plus.**
**Open the live page for links to other documents and user manuals.**



**TRUE VALUE MFG COMPANY PDS125-AER**

# TRUE VALUE MFG COMPANY PDS125-AER PD 12OZ Fossil Satin Enamel Instruction Manual

## 1. Introduction

This manual provides instructions for the safe and effective use of TRUE VALUE MFG COMPANY PDS125-AER PD 12OZ Fossil Satin Enamel spray paint. This product is a quick-drying decorative spray enamel designed for various surfaces, including wood, metal, wicker, masonry, crafts, and plastic. Please read all instructions carefully before use.




Image 1: TRUE VALUE MFG COMPANY PDS125-AER PD 12OZ Fossil Satin Enamel spray can. This image displays the product in its aerosol can format, featuring the brand and product name.

## 2. Safety Information

Always prioritize safety when using spray paint. Failure to follow these guidelines may result in injury or property damage.

- **Ventilation:** Use in a well-ventilated area. Avoid inhaling vapors. If working indoors, ensure adequate airflow by opening windows and doors, or use an exhaust fan.
- **Flammability:** This product is extremely flammable. Keep away from heat, sparks, open flames, and other ignition sources. Do not smoke while using.
- **Personal Protective Equipment (PPE):** Wear appropriate eye protection (safety glasses or goggles) to prevent accidental spray contact. Wear gloves to protect skin.
- **Storage:** Store in a cool, dry place, away from direct sunlight and temperatures above 120°F (49°C). Keep out of reach of children and pets.
- **Disposal:** Dispose of empty cans and unused product according to local regulations. Do not puncture or incinerate cans, even when empty.

- **First Aid:** In case of eye contact, flush immediately with plenty of water for at least 15 minutes. If swallowed, do not induce vomiting; call a poison control center or doctor immediately. If inhaled, move to fresh air.

## 3. Preparation

1. **Surface Cleaning:** Ensure the surface to be painted is clean, dry, and free of dust, grease, wax, rust, or loose paint. For best adhesion, lightly sand glossy surfaces.
2. **Masking:** Protect surrounding areas and objects not intended for painting with painter's tape and drop cloths.
3. **Temperature and Humidity:** For optimal results, apply when air and surface temperatures are between 50°F (10°C) and 90°F (32°C) and humidity is below 85%. Avoid painting in direct sunlight or on hot surfaces.
4. **Shake Can:** Shake the can vigorously for at least one minute after the mixing ball begins to rattle. Continue to shake occasionally during use.

## 4. Operating (Application)

1. **Test Spray:** Before applying to your project, test spray on a scrap piece of material to check color and spray pattern.
2. **Hold Distance:** Hold the can upright approximately 10-12 inches (25-30 cm) from the surface.
3. **Apply Thin Coats:** Apply paint in light, even, sweeping strokes. Overlap each stroke slightly. Avoid applying a single heavy coat, as this can lead to drips and uneven drying.
4. **Multiple Coats:** For best coverage and durability, apply multiple thin coats rather than one thick coat. Allow 5-10 minutes between coats.
5. **Drying Time:** The paint is typically dry to touch in 15-30 minutes. Allow 24 hours for full cure before handling or exposing to heavy use. Drying times may vary based on temperature, humidity, and film thickness.

## 5. Maintenance and Storage

- **Clear Nozzle:** After each use, invert the can and spray for 2-3 seconds until only clear propellant comes out. This prevents the nozzle from clogging. If the nozzle clogs, remove and clean with mineral spirits or paint thinner. Do not insert pins or other objects into the spray valve.
- **Storage:** Store the can in a cool, dry, well-ventilated area, away from extreme temperatures and direct sunlight. Ensure the cap is securely placed on the can.

## 6. Troubleshooting

| Problem | Possible Cause | Solution |
|---|---|---|
| Clogged Nozzle | Paint dried in the nozzle opening. | Remove the nozzle and clean it with mineral spirits or paint thinner. Replace the nozzle. Always clear the nozzle after use by inverting the can and spraying. |
| Uneven Spray / Spitting | Insufficient shaking; can too cold; nozzle partially clogged. | Shake the can vigorously for at least one minute. Warm the can to room temperature (do not use direct heat). Clean the nozzle as described above. |
| Drips or Runs | Applying paint too heavily or holding the can too close to the surface. | Apply lighter, more even coats. Maintain a distance of 10-12 inches from the surface. |

## 7. Specifications

- **Product Name:** TRUE VALUE MFG COMPANY PDS125-AER PD 12OZ Fossil Satin Enamel
- **Model Number:** PDS125-AER
- **Brand:** TRUE VALUE MFG COMPANY
- **Finish Type:** Satin
- **Item Volume:** 12 Fluid Ounces
- **Paint Type:** Enamel
- **Drying Formula:** Quick Drying
- **Ideal Surfaces:** Wood, metal, wicker, masonry, crafts, plastic
- **Country of Origin:** United States

## 8. Support

For further assistance or inquiries regarding the TRUE VALUE MFG COMPANY PDS125-AER PD 12OZ Fossil Satin Enamel, please refer to the contact information provided on the product label or visit the official TRUE VALUE MFG COMPANY website. Keep your product's model number (PDS125-AER) available when seeking support.

© 2023 TRUE VALUE MFG COMPANY. All rights reserved.

### Ask a question about this manual

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

**Name**

Anonymous

**Email**

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. Privacy details.

**Question**

Example: How do I reset this device or fix this error?

**Details**

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question

**Open the live page**

**https://manuals.plus/asin/B072L3LV19**

More documents and user manuals: **https://manuals.plus/**