

Simmons S8P3940

Simmons Truplex .22 Mag Riflescope Instruction Manual

Model: S8P3940

INTRODUCTION

Thank you for choosing the Simmons Truplex .22 Mag Riflescope. This manual provides essential information for the proper setup, operation, and maintenance of your new riflescope. Designed for precision and durability, this riflescope is an excellent choice for enhancing your shooting accuracy with rimfire firearms. Please read this manual thoroughly before use to ensure optimal performance and safety.

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

KEY FEATURES

- **One-piece tube construction:** Ensures lighter handling, greater strength, and enhanced durability.
- **Fully coated high-quality optical glass:** Delivers bright, sharp images with high contrast for clear viewing.
- **Waterproof, fogproof, and shockproof:** Built to withstand various environmental conditions and recoil.
- **QTA (Quick Target Acquisition) eyepiece:** Allows for fast and easy target acquisition.
- **SureGrip adjustments:** Provides effortless windage and elevation adjustments, even when wearing gloves.
- **TrueZero windage and elevation adjustment system:** Stays locked tight to zero through strenuous conditions.
- **Truplex Reticle:** Standard reticle for precise aiming.

SETUP

Mounting the Riflescope

The Simmons Truplex .22 Mag Riflescope comes with mounting rings. These rings are designed to fit a narrow width rail, such as a 3/8" dovetail rail. Please note that they may not fit a standard Weaver/Picatinny rail. If your rifle has a

Weaver/Picatinny rail, you may need to acquire compatible 1-inch Weaver/Picatinny rings for proper installation. Ensure the rings are securely fastened to the rifle's base and the riflescope is level before tightening completely.



Image: Top view of the Simmons Truplex .22 Mag Riflescope, showing its compact design and mounting rings.

Eyepiece Adjustment (Diopter)

To achieve a clear reticle image, adjust the eyepiece. Point the riflescope at a plain, bright background (like a wall or the sky) and rotate the eyepiece until the reticle appears sharp and clear. This adjustment compensates for individual eyesight differences.

Windage and Elevation Adjustments

The riflescope features capped windage and elevation turrets. Remove the protective caps to access the adjustment dials. Each click of the dial adjusts the point of impact by 1/4 MOA (Minute of Angle) at 100 yards. Turn the dials to move the point of impact as needed for zeroing. The adjustments are designed to be precise and hold their position even under recoil.



Image: Angled view of the riflescope, showing the windage and elevation adjustment turrets with their protective caps.

OPERATING THE RIFLESCOPE

Magnification Adjustment

The Simmons Truplex .22 Mag Riflescope offers a variable magnification range of 3-9x. To change the magnification, rotate the knurled ring located near the eyepiece. Adjust to your desired power setting based on target distance and shooting conditions.

Target Acquisition

Utilize the QTA eyepiece for quick target acquisition. With proper eye relief (approximately 3.75 inches), you should be able to quickly and clearly see your target through the scope. The Truplex reticle provides a clear aiming point.

Maintenance

Cleaning the Lenses

To clean the lenses, first use a soft brush or compressed air to remove any loose dust or debris. Then, apply a small amount of lens cleaning solution to a microfiber lens cloth and gently wipe the lens surfaces. Avoid using harsh chemicals or abrasive materials, as these can damage the lens coatings.

Storage

Store your riflescope in a cool, dry place, away from direct sunlight and extreme temperatures. Use the provided lens caps to protect the objective and eyepiece lenses from dust and scratches when not in use.

Troubleshooting

Blurry Image

- Ensure the eyepiece (diopter) is correctly adjusted for your vision.
- Check for condensation or debris on the lenses. Clean as per the maintenance section.

Adjustments Not Holding Zero

- Verify that the mounting rings are securely tightened to both the riflescope and the rifle's rail.
- Ensure the windage and elevation turret caps are securely replaced after adjustment.

If you encounter persistent issues, please refer to the warranty and support information for assistance.

Specifications

Feature	Specification
Brand	Simmons
Model Name	Simmons 8 Point Riflescope
Magnification	3-9x
Objective Lens Diameter	32 mm
Eye Relief	3.75 inches (95 mm)
Exit Pupil	10.7 / 3.6 mm
Weight	10 ounces (284 g)
Click Value (at 100Y)	0.25 MOA
Adjustment Range (at 100Y)	60 MOA

Reticle Type	Truplex
Tube Construction	One-piece
Finish	Hard Anodized
Waterproof/Fogproof/Shockproof	Yes

WARRANTY AND SUPPORT

The Simmons Truplex .22 Mag Riflescope comes with a Limited Warranty. For specific details regarding warranty coverage, claims, or technical support, please refer to the official Simmons Optics website or contact their customer service directly. Keep your purchase receipt as proof of ownership.

For additional information or assistance, visit the [Simmons Optics official website](#).

ASK A QUESTION ABOUT THIS MANUAL

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page’s manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. [Privacy details](#).

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question