John Deere CQM20142

John Deere Original Equipment Moisture Tester CQM20142 User Manual

Model: CQM20142

1. Introduction

The John Deere Original Equipment Moisture Tester CQM20142 is a precision instrument designed to accurately measure moisture content in various materials. This manual provides essential information for the proper setup, operation, maintenance, and troubleshooting of your moisture tester, ensuring optimal performance and longevity. Please read this manual thoroughly before using the device to ensure safe and effective operation.

2. Setup

2.1 Unpacking and Inspection

- Carefully remove the moisture tester and all accessories from the packaging.
- Inspect the device for any signs of damage during transit. If damage is found, contact your dealer immediately.
- Retain the packaging for future storage or transport.

2.2 Battery Installation

1. Locate the battery compartment cover on the back of the device.
2. Slide or unscrew the cover to open.
3. Insert the required batteries (e.g., 4 x AA batteries, not included) observing the correct polarity (+/-) as indicated inside the compartment.
4. Replace the battery compartment cover securely.

2.3 Initial Calibration (if applicable)

Some moisture testers may require initial calibration for optimal accuracy. Refer to the specific instructions provided with your device for calibration procedures. If no specific calibration steps are mentioned, the device is factory calibrated and ready for use.

3. Operating Instructions

3.1 Powering On/Off

- To power on the device, press and hold the **POWER** button until the display illuminates.
- To power off, press and hold the **POWER** button again until the display turns off. The device may also have an auto-off feature to conserve battery life.

3.2 Taking a Measurement

1. Ensure the device is powered on and the display is active.
2. Select the appropriate measurement mode or material type if your device offers this feature (e.g., wood, soil, concrete). Refer to the device's interface for mode selection.
3. Carefully insert the probes or sensor into the material you wish to test. Ensure good contact between the probes and the material. For soil, insert probes to the desired depth.
4. Wait for the reading to stabilize on the display. This usually takes a few seconds.
5. Record the moisture content reading.
6. Remove the probes from the material and clean them as per maintenance instructions.

3.3 Interpreting Readings

Moisture readings are typically displayed as a percentage (%). The optimal moisture content varies significantly depending on the material being tested and its intended use. Consult relevant industry standards or guidelines for specific material moisture requirements.

4. Maintenance

4.1 Cleaning

- After each use, especially when testing damp or dirty materials, clean the probes or sensor with a soft, dry cloth.
- For stubborn residue, a slightly damp cloth may be used, but ensure the device is completely dry before storage.
- Do not use abrasive cleaners, solvents, or immerse the device in water.

4.2 Storage

- Store the moisture tester in a cool, dry place, away from direct sunlight and extreme temperatures.
- If the device will not be used for an extended period, remove the batteries to prevent leakage and damage.
- Keep the device in its original packaging or a protective case to prevent physical damage.

4.3 Battery Replacement

When the battery indicator on the display shows low power, replace all batteries with new ones of the same type. Refer to section 2.2 for battery installation instructions.

5. Troubleshooting

Problem	Possible Cause	Solution
Device does not power on.	Dead or incorrectly installed batteries.	Replace batteries, ensuring correct polarity.

Problem	Possible Cause	Solution
Inaccurate or inconsistent readings.	Probes not fully inserted or poor contact. Probes are dirty or corroded. Device not calibrated (if applicable). Testing material outside device's range.	Ensure probes are fully inserted and make good contact. Clean probes thoroughly. Perform calibration as per instructions. Verify material is within the device's specified measurement range.
Display shows error message.	Specific error condition (e.g., out of range, sensor fault).	Consult the device's specific error codes (if provided) or contact customer support. Try restarting the device.

6. Specifications

Feature	Detail
Model Number	CQM20142
Product Type	Moisture Tester
Brand	John Deere Original Equipment
Power Source	Battery operated (e.g., 4 x AA, not included)
Measurement Range	Typically 0-50% (varies by material)
Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-10°C to 50°C (14°F to 122°F)
ASIN	B074JM8SRT

7. Warranty Information

This John Deere Original Equipment product is covered by a limited warranty against defects in materials and workmanship. The specific terms and duration of the warranty may vary. Please refer to the warranty card included with your product or visit the official John Deere website for detailed warranty information.
Keep your proof of purchase for warranty claims.

8. Customer Support

For technical assistance, service, or questions regarding your John Deere Original Equipment Moisture Tester CQM20142, please contact John Deere customer support.

- **Online Support:** Visit the official John Deere Support Website.
- **Phone Support:** Refer to your product packaging or the John Deere website for regional contact numbers.
- **Authorized Dealers:** Contact your local authorized John Deere dealer for service and parts.

© 2024 John Deere. All rights reserved. Information in this manual is subject to change without notice.

Ask a question about this manual

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. Privacy details.

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question