

Saved from manuals.plus.

Open the live page for links to other documents and user manuals.

[Manuals.plus](#) /

› [Spares2go](#) /

› SPARES2GO Door Glass Seal for Hotpoint - Ariston Aqualtis Washing Machines Instruction Manual

Spares2go 09-DVF-277

SPARES2GO Door Glass Seal for Hotpoint - Ariston Aqualtis Washing Machines Instruction Manual

INTRODUCTION

This manual provides detailed instructions for the installation, care, and troubleshooting of your new SPARES2GO Door Glass Seal, designed as a high-quality, fully compatible replacement part for various Hotpoint - Ariston Aqualtis washing machine models. Please read these instructions carefully before proceeding with installation to ensure safe and correct usage.



Image: The SPARES2GO replacement door glass seal, designed for Hotpoint - Ariston Aqualtis washing machines.

COMPATIBILITY

This SPARES2GO door glass seal (Model 09-DVF-277) is compatible with a wide range of Hotpoint - Ariston Aqualtis series washing machines. Below is a partial list of compatible models:

- AQ102F 29 IT, AQ102F 49 FR, AQ102F 497 FR, AQ102F 49H EU
- AQ103D 49 EU/A, AQ103D 49 EU/B, AQ103D 49 FR, AQ103F 49 FR
- AQ104D 49 EU/B, AQ104F 29 EU
- AQ105D 49D EU/A, AQ105D 49D EU/B, AQ105D 49D FR, AQ105D 69D EU/A, AQ105F 29D IT
- AQ113D 69 EH/A, AQ113D 69 EU/A, AQ113D 69 FR, AQ113D 697 EU/A, AQ113D 697 EU/B, AQ113D 697 FR
- AQ114D 697D EU/B, AQ114D 69D EU/A, AQ114D 69D FR, AQ114D 69D IT
- AQ72L 09 S EU, AQ73F 49 EU
- AQ82F 29 FR, AQ82F 49 FR, AQ82L 09 IT, AQ82L 09C TK, AQ82L 29 FR, AQ82L 49 FR
- AQ83D 29 EU/B, AQ83D 29C TK, AQ83D 29X EU/B, AQ83D 497 EU/B

- AQ83F 09 EU, AQ83F 29 C EU, AQ83F 29 IT, AQ83F 29C TK, AQ83F 49 EU, AQ83F 497 EU
- AQ92F 09 IT, AQ92F 29 EU, AQ92F 29 FR, AQ92F 29 IT, AQ92F 29H IT, AQ92F 49 FR
- AQ93D 297SC TK, AQ93D 29SC TK, AQ93D 49 EU/A
- AQ93F 29 EU, AQ93F 29 FR, AQ93F 29 IT, AQ93F 29 TK, AQ93F 297 EU, AQ93F 297 TK, AQ93F 29X EU, AQ93F 29X TK, AQ93F 49 FR, AQ93F 69 EU
- And many other Aqualtis series models. Please verify your washing machine's model number against the full compatibility list provided by SPARES2GO or consult your appliance manual.

Safety Precautions

Always prioritize safety when working with electrical appliances. Failure to follow these precautions may result in injury or damage to the appliance.

- **Disconnect Power:** Before beginning any work, always unplug the washing machine from the main power supply.
- **Turn Off Water Supply:** Close the water inlet valves to prevent water leaks.
- **Drain Water:** Ensure the washing machine is completely drained of water before attempting to remove the door seal.
- **Wear Protective Gear:** Use gloves to protect your hands from sharp edges or old detergent residue.
- **Professional Assistance:** If you are unsure about any step, consult a qualified appliance technician.

Installation Guide

This section outlines the general steps for replacing the door glass seal. Specific steps may vary slightly depending on your washing machine model.

Tools Required

- Screwdriver (flathead and/or Phillips, depending on your machine)
- Pliers (optional, for spring clamps)
- Small container or towel (to catch residual water)
- Mild detergent and cloth (for cleaning)

Preparation

1. Ensure the washing machine is unplugged and the water supply is turned off.
2. Open the washing machine door.
3. Locate the outer retaining spring or clamp that holds the door seal to the front panel of the machine.

Removing the Old Seal

1. Carefully pry off the outer retaining spring/clamp using a flathead screwdriver or pliers. Some models may have a screw to loosen.
2. Pull the outer lip of the old door seal away from the front panel.
3. Reach inside the drum and locate the inner retaining spring/clamp that secures the seal to the drum. This may be more challenging to access.
4. Remove the inner retaining spring/clamp.
5. Carefully pull the old door seal completely out of the washing machine.
6. Clean the area where the seal sits, both on the drum and the front panel, to remove any dirt, mold, or detergent residue.

Installing the New Seal

1. Orient the new SPARES2GO door seal correctly. There is usually a drain hole or a mark at the bottom of the seal that should align with the drain hole at the bottom of the washing machine drum.
2. Carefully fit the inner lip of the new seal around the drum opening. Ensure it is seated evenly and securely.
3. Reinstall the inner retaining spring/clamp to secure the seal to the drum. This step often requires patience and careful manipulation.
4. Pull the outer lip of the new seal over the front panel opening.
5. Reinstall the outer retaining spring/clamp, ensuring the seal is held firmly in place against the front panel.



Image: A close-up view of the SPARES2GO door glass seal, showing its flexible design and grooves for proper fitting.

Final Checks

1. Gently push on the seal all around to ensure it is seated correctly and there are no gaps or twists.
2. Close the washing machine door and check that it latches properly and the seal forms a tight closure.
3. Reconnect the water supply and plug the machine back into the power outlet.

4. Run a short, empty wash cycle (e.g., a rinse cycle) to check for any leaks. Observe the seal area carefully during the cycle.

CARE AND MAINTENANCE

Proper care of your door seal will extend its lifespan and prevent common issues like mold and odors.

- **Wipe After Each Use:** After each wash cycle, wipe down the inside of the door seal with a clean cloth to remove any moisture, lint, or detergent residue.
- **Leave Door Ajar:** When the washing machine is not in use, leave the door slightly ajar to allow air circulation and prevent moisture buildup, which can lead to mold and mildew.
- **Regular Cleaning:** Periodically clean the seal thoroughly with a mild detergent solution or a washing machine cleaner. Pay attention to any folds or crevices where residue can accumulate.
- **Avoid Harsh Chemicals:** Do not use abrasive cleaners or harsh chemicals on the seal, as these can damage the rubber material.

TROUBLESHOOTING

If you encounter issues after replacing the door seal, consider the following common problems and solutions:

Problem	Possible Cause	Solution
Water Leakage	Seal not seated correctly; retaining clamps loose; seal damaged during installation.	Recheck seal alignment and ensure both inner and outer clamps are securely fastened. Inspect the seal for any tears or punctures.
Door Not Closing Properly	Seal is twisted or not fully pushed into place.	Open the door and carefully adjust the seal, ensuring it is not twisted and is evenly seated around the drum and front panel.
Mold or Odor Buildup	Moisture trapped in the seal; infrequent cleaning.	Clean the seal regularly as per the maintenance section. Leave the door ajar after use to allow drying.

PRODUCT SPECIFICATIONS

Brand	Spares2go
Model Number	09-DVF-277
Item Weight	1.1 kg
Manufacturer	SPARES2GO
Manufacturer Reference	09-DVF-277
ASIN	B075439SG2
First Available Date	March 13, 2019

SUPPORT AND WARRANTY

For any questions regarding your SPARES2GO Door Glass Seal, or for information on warranty coverage, please contact SPARES2GO customer support directly. Refer to your purchase documentation for contact details.

Always ensure you are using genuine SPARES2GO replacement parts to maintain product performance and validity of any existing appliance warranties.

ASK A QUESTION ABOUT THIS MANUAL

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page’s manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. [Privacy details](#).

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question

Open the live page

<https://manuals.plus/asin/B075439SG2>

More documents and user manuals: <https://manuals.plus/>