

Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

manuals.plus /

- › [Spare parts KM](#) /
- › [Replacement Belt for Bread Machine, 570 x 8 mm Silver - Instruction Manual](#)

Spare parts KM 570 x 8 mm

Replacement Belt for Bread Machine, 570 x 8 mm Silver

Instruction Manual

INTRODUCTION

This manual provides detailed instructions for the installation, operation, and maintenance of the Spare parts KM replacement belt for bread machines. This belt is designed to replace worn or broken drive belts in compatible bread maker models, ensuring proper function and longevity of your appliance. Please read this manual thoroughly before attempting any installation or maintenance.

Compatible Models: Princess 1936, Princess 1934, Amstrad CM02, Riviera & Bar QD782A.

PRODUCT OVERVIEW



Figure 1: Spare parts KM Replacement Belt (570 x 8 mm)

This image displays the black replacement belt, characterized by its ribbed inner surface designed for optimal grip on the bread machine's pulleys. The belt is shown against a teal background, highlighting its flexible and durable construction. Its dimensions are 570 mm in length and 8 mm in width, making it suitable for various bread machine models.

The replacement belt is a crucial component for the proper functioning of your bread machine, transmitting power from the motor to the kneading paddle. This specific belt features a toothed profile for efficient power transfer and reduced slippage.

SETUP AND INSTALLATION

Replacing the bread machine belt requires careful attention. It is recommended to consult your bread machine's original service manual for specific disassembly instructions. Always ensure the appliance is unplugged from the power outlet before beginning any work.

Required Tools:

- Screwdriver set (Phillips and/or flathead, depending on your bread machine model)
- Pliers (optional, for tight connections)
- Gloves (optional, for grip and protection)

Installation Steps:

1. **Disconnect Power:** Unplug the bread machine from the electrical outlet.
2. **Access Internal Components:** Carefully disassemble the bread machine casing to gain access to the motor and drive mechanism. This typically involves removing screws from the bottom or back panel.
3. **Remove Old Belt:** Locate the old, broken, or worn belt. Gently remove it from the motor pulley and the larger drive pulley.
4. **Install New Belt:**
 - First, place the new belt onto the smaller motor pulley.
 - Next, stretch the belt over the larger drive pulley. This may require some force as the belt is designed to be taut. Some users find it helpful to slightly loosen the motor mounting screws to allow for minor adjustment, then re-tighten them once the belt is in place.
 - Ensure the teeth of the belt align correctly with the grooves on both pulleys.
5. **Check Tension:** The belt should be taut but not excessively tight, allowing for smooth rotation of the pulleys without slippage.
6. **Reassemble:** Carefully reassemble the bread machine casing, ensuring all screws are securely fastened.
7. **Test Functionality:** Plug the bread machine back in and run a short cycle (e.g., kneading cycle) to confirm the new belt is functioning correctly and quietly.

OPERATING CONSIDERATIONS

Once the new belt is installed, the bread machine should operate as intended. No specific operational changes are required for the belt itself. However, observe the machine during its first few uses after replacement to ensure smooth and consistent kneading.

- Listen for any unusual noises, such as squealing or grinding, which might indicate improper belt alignment or tension.
- Ensure the kneading paddle rotates freely and consistently throughout the kneading cycle.

MAINTENANCE

The replacement belt is designed for durability and requires minimal maintenance. Regular inspection can help prolong its lifespan and prevent future issues.

Inspection Schedule:

- **Annual Check:** If you frequently use your bread machine, consider opening the casing annually to inspect the belt.

- **Signs of Wear:** Look for cracks, fraying, or missing teeth on the belt. Also, check for excessive slack or stiffness.
- **Cleanliness:** Ensure no dough residue or foreign objects are caught in the belt or pulleys, as this can cause premature wear.

If any significant wear or damage is observed, it is advisable to replace the belt to avoid operational failure during a baking cycle.

TROUBLESHOOTING

This section addresses common issues related to the replacement belt.

Problem	Possible Cause	Solution
Kneading paddle not turning or turning intermittently.	Belt is too loose or has slipped off a pulley.	Re-open the casing and re-seat the belt. Ensure proper tension. If the motor mounting screws were loosened, ensure they are tightened securely.
Loud squealing or grinding noise during operation.	Belt is too tight, misaligned, or rubbing against casing.	Check belt alignment on pulleys. If too tight, slightly loosen motor mounting screws (if applicable) to relieve tension, then re-tighten. Ensure no parts of the casing are obstructing the belt.
Belt appears to be too short during installation.	This is a common perception; the belt is designed to be taut.	Apply firm, even pressure to stretch the belt over the larger pulley. As mentioned in Setup, slightly loosening motor screws can assist. Once installed, the tension is correct for operation.

If issues persist after troubleshooting, consider consulting a qualified appliance repair technician or contacting the manufacturer of your bread machine.

SPECIFICATIONS

Attribute	Value
Brand	Spare parts KM
Product Type	Replacement Belt for Bread Machine
Dimensions (Length x Width)	570 mm x 8 mm
Belt Profile	Toothed Belt
Material	Plastic
Color	Silver (Note: The physical belt is black, 'Silver' refers to the product listing's color attribute)
Item Weight	20 grams
ASIN	B075QLQX4N

WARRANTY AND SUPPORT

Specific warranty information for this replacement part may vary depending on the retailer and region of purchase. Please refer to your purchase receipt or the retailer's website for details regarding warranty coverage.

For technical support or further inquiries regarding this product, please contact the manufacturer, Spare parts KM, through their official channels or the platform where the product was purchased.