Colibri 43237-2

Colibri EVO Angled Single Jet Flame Butane Lighter

Model: 43237-2

Introduction

The Colibri EVO Angled Single Jet Flame Butane Lighter is designed for effortless and reliable ignition. Featuring a user-friendly single-action ignition, a secure Pachmayr grip, and a large fuel capacity with a visible window, this lighter is built for performance and convenience. It is wind-resistant and functions effectively at high altitudes, making it a versatile tool for various lighting needs.



The Colibri EVO lighter, showcasing its sleek black design and angled jet flame mechanism.

Safety Information

WARNING: Keep out of reach of children. Lighters contain flammable butane gas under pressure. Improper use can cause injury or fire.

- Do not expose to heat above 120°F (49°C) or prolonged sunlight.
- Do not puncture or incinerate.
- Ensure flame is extinguished after each use.
- Do not attempt to disassemble or repair the lighter.
- Use only high-quality butane fuel for refilling.

- Statements regarding dietary supplements have not been evaluated by the FDA and are not intended to diagnose, treat, cure, or prevent any disease or health condition.

Components

The Colibri EVO lighter features several key components designed for optimal performance and user comfort:

- **Angled Jet Flame Nozzle:** Provides a precise and powerful flame.
- **Single-Action Ignition:** Activates the flame with a simple press.
- **Pachmayr Grip:** Textured body for secure and comfortable handling.
- **Blue Fuel Window:** Allows for easy monitoring of butane fuel levels.
- **Flame Adjuster:** Located at the base for adjusting flame height.



The angled jet flame in action, providing a strong and consistent burn.



Side profile highlighting the ergonomic design and fuel window.

Setup

Fueling the Lighter

The Colibri EVO lighter is refillable with butane fuel. For best performance and longevity, use premium quality butane.

1. Ensure the lighter is completely cool before refilling.
2. Invert the lighter and locate the refill valve at the base.
3. Hold the butane fuel can upright and firmly press its nozzle into the lighter's refill valve.
4. Apply firm, even pressure for 5-10 seconds. Repeat 2-3 times, allowing a few seconds between each press for the fuel to settle.
5. Once refilled, allow the lighter to rest for 2-3 minutes before attempting to ignite, allowing the gas to reach room temperature.



The Colibri EVO is designed for easy and efficient butane refilling.

Operating Instructions

Ignition

1. Open the lighter's lid.
2. Press the single-action ignition button firmly. The angled jet flame will ignite.
3. Release the button to extinguish the flame and close the lid.

Flame Adjustment

The flame height can be adjusted to suit your preference.

1. Locate the flame adjustment screw at the base of the lighter.
2. Use a small flathead screwdriver or a similar tool to turn the screw.
3. Turn towards the '+' sign for a larger flame, and towards the '-' sign for a smaller flame.
4. Test the flame after each adjustment until the desired height is achieved.



The lighter features a powerful single torch flame.



Flame height can be easily adjusted for various uses.

Maintenance

Cleaning

To maintain the appearance and functionality of your Colibri EVO lighter:

- Wipe the exterior with a soft, dry cloth.
- Avoid using abrasive cleaners or solvents, which can damage the finish.
- Periodically clear any debris from the flame nozzle using a can of compressed air.

Fuel Management

Regularly check the fuel level using the blue fuel window. Refill the lighter before it runs completely dry to prevent air from entering the fuel system, which can affect performance.

Troubleshooting

Problem	Possible Cause	Solution
Lighter does not ignite or produces a weak flame.	Low or no butane fuel. Air in the fuel tank. Flame adjustment too low.	Refill with premium butane. Purge air from the tank (see advanced tips). Adjust flame higher.
Flame is inconsistent or sputters.	Low quality butane. Air in the fuel tank.	Drain existing fuel and refill with high-purity butane. Purge air from the tank.
Lighter leaks butane.	Overfilled. Damaged refill valve.	Ensure not to overfill. If leaking persists, contact customer support.

Advanced Tip: Purging Air from the Tank

If your lighter has been completely emptied or is performing poorly after refilling, it may have air trapped in the fuel tank. To purge:

1. Invert the lighter.
2. Using a small, pointed tool (like a pen tip), gently press the refill valve to release any remaining gas and air until no more hissing sound is heard.
3. Refill the lighter as per the fueling instructions.

Specifications

- **Model Number:** 43237-2
- **Product Dimensions:** 2.88"L x 1.38"W x 0.75"Th
- **Item Weight:** 11.36 ounces
- **Color:** Black & Black
- **Material:** Rubber
- **Fuel Type:** Liquefied Petroleum Gas (Butane)
- **Altitude Performance:** Functions effectively up to 12,000 feet

Warranty and Support

The Colibri EVO lighter is backed by a **two-year warranty**, demonstrating Colibri's commitment to quality and customer satisfaction. This warranty covers manufacturing defects under normal use.
For warranty claims, technical support, or any inquiries regarding your Colibri product, please visit the official Colibri website or contact their customer service department. Keep your proof of purchase for warranty validation.
Visit the Colibri Store: Colibri Official Store

© 2025 Colibri. All rights reserved.

Ask a question about this manual

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. Privacy details.

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question