

Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

manuals.plus /

› [Eisl](#) /

› [Eisl Lyon Low-Pressure Kitchen Faucet NI183ESCRNI-LP-PR-A User Manual](#)

Eisl NI183ESCRNI-LP-PR-A

Eisl Lyon Low-Pressure Kitchen Faucet NI183ESCRNI-LP-PR-A User Manual

Brand: Eisl | Model: NI183ESCRNI-LP-PR-A

INTRODUCTION AND OVERVIEW

This instruction manual provides detailed information for the Eisl Lyon Low-Pressure Kitchen Faucet, model NI183ESCRNI-LP-PR-A. It covers installation, operation, maintenance, and troubleshooting to ensure proper use and longevity of your faucet. Designed for low-pressure water systems, this faucet features a modern aesthetic with practical functionality, including a 360-degree swivel pull-out spray. Please read all instructions carefully before installation and use.

Eisl Sanitär GmbH has been a trusted partner for kitchen and bathroom fittings since 1980, committed to providing innovative and high-quality products.

PRODUCT FEATURES

- **Modern Design:** Elegant low-pressure faucet with a nickel finish and a high swivel spring spout.
- **Flexible Movement:** Offers a highly flexible radius of movement in the sink area with a 360-degree swivel range.
- **Integrated Spray:** Features a two-way adjustable dish cleaner with a stainless steel spring shower arm, combining design and function.
- **Dimensions:** Spiral spring spout height approximately 54 cm, and projection approximately 20 cm.
- **Quality Materials:** Manufactured using high-quality brass raw materials, adhering to German drinking water regulations for safety and optimal water quality.





Image of the Eisl Lyon Low-Pressure Kitchen Faucet in stainless steel, featuring a high swivel spring spout and a pull-out spray.

SETUP AND INSTALLATION

This faucet is designed for low-pressure water systems and requires an under-sink water heater or boiler for hot water supply. Ensure your plumbing system is compatible before proceeding with installation.

Required Tools (Not Included):

- Adjustable wrench
- Screwdriver
- Sealant tape (PTFE tape)
- Bucket and towels (for potential water spills)

Installation Steps:

1. **Prepare the Installation Area:** Turn off the main water supply. Clear the area under the sink.
2. **Mount the Faucet:** Insert the faucet into the designated hole on your sink or countertop. Secure it from underneath using the quick-fix set provided.
3. **Connect Water Hoses:**
 - Connect the cold water hose (typically blue marking) directly to your cold water supply line.
 - Connect the hot water hoses (typically red marking) to your under-sink water heater/boiler as per the heater's instructions. The faucet's flexible hoses are approximately 40 cm long.
4. **Check Connections:** Ensure all connections are tight and sealed with sealant tape to prevent leaks.
5. **Test Faucet:** Slowly turn on the main water supply. Check for any leaks. Operate the faucet to ensure both hot and cold water flow correctly.

Important Note: For detailed assembly instructions, refer to the specific assembly guide included in your product packaging. If you are unsure about any step, it is recommended to consult a qualified plumber.

OPERATING INSTRUCTIONS

The Eisl Lyon Low-Pressure Kitchen Faucet is designed for ease of use with a single lever handle.

- **Water Flow Control:** Lift the lever handle to turn on the water flow. The further you lift, the higher the flow rate.
- **Temperature Control:** Move the lever handle left for hot water and right for cold water. For low-pressure systems, cold water is supplied directly, while hot water is heated by your under-sink unit.
- **Pull-Out Spray:** The faucet features a pull-out spray head for extended reach and versatile cleaning. Pull the spray head from the spout to use. Press the button on the spray head to switch between different spray patterns (if applicable).
- **360-Degree Swivel:** The spout can be rotated 360 degrees, providing flexibility for various sink tasks.

Note on Low-Pressure Systems: It is normal for low-pressure faucets to exhibit a slight dripping after use. This is not a defect but an indication that the under-sink water heater is functioning correctly by compensating for pressure changes. Do not attempt to overtighten the faucet to stop this dripping, as it is part of the system's normal operation.

MAINTENANCE

Regular cleaning and maintenance will help preserve the appearance and functionality of your Eisl faucet.

- **Cleaning:** Clean the faucet regularly with a soft cloth and mild soap or a non-abrasive liquid cleaner. Avoid using abrasive cleaners, scouring pads, or cleaners containing alcohol, ammonia, or bleach, as these can damage the finish.
- **Limescale Removal:** For limescale deposits, use a mild descaling agent specifically designed for faucets. Follow the product instructions carefully and rinse thoroughly after use.
- **Aerator Maintenance:** Periodically unscrew the aerator at the tip of the spout and clean any debris or mineral buildup. This helps maintain optimal water flow.
- **Hose Inspection:** Regularly check the flexible hoses under the sink for any signs of wear, kinks, or leaks.

Always dry the faucet after cleaning to prevent water spots and maintain its shine.

TROUBLESHOOTING

Problem	Possible Cause	Solution
Slight dripping from spout after use	Normal operation for low-pressure systems with under-sink water heaters.	No action required. This is not a defect. Do not overtighten.
No water flow or low flow	Main water supply off; clogged aerator; kinked hose.	Check main water supply. Clean aerator. Inspect hoses for kinks.
Leaks from connections	Loose connections; worn seals.	Ensure connections are tight. Replace seals if necessary. Use sealant tape.
No hot water	Under-sink water heater issue; incorrect temperature setting.	Check under-sink water heater's power and settings. Refer to heater's manual.

If the problem persists after attempting these solutions, please contact Eisl customer support.

SPECIFICATIONS

Specification	Detail
Manufacturer	Eisl Sanitär GmbH
Model Number	NI183ESCRNI-LP-PR-A
Part Number	NI183ESCRNI-LP-PR-A
Item Weight	2.12 Kilograms
Product Dimensions	25.3 x 5.5 x 52 cm
Size	Low Pressure
Color	Stainless Steel

Specification	Detail
Style	Lever
Finish	Brass
Material	Stainless Steel
Mounting Type	Single Hole
Number of Pieces	1
Hose Length	50 Centimeters
Number of Holes	1
Faucet Height	54 Centimeters
Faucet Reach	222 Millimeters
Lever/Handle Placement	Right
Number of Handles	1
Handle Material	Stainless Steel
Measurement System	Metric
Plug Type	Countertop Mount
Special Features	360 Degree Rotation
Included Components	Faucet, Assembly Set, Assembly Instructions
Batteries Included?	No
Batteries Required?	No
Recommended Uses	Kitchen
Date First Available	March 15, 2022

WARRANTY AND SUPPORT

Eisl Sanitär GmbH is committed to providing high-quality products. While specific warranty details are not provided in this document, Eisl has been a trusted partner in kitchen and bathroom fittings since 1980.

For technical support, service inquiries, or questions regarding your Eisl faucet, please contact:

Eisl Customer Service: +43/662 879346 0

Please have your model number (NI183ESCRNI-LP-PR-A) available when contacting support.

