

## Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

manuals.plus /

> [VTech](#) /

> [VTech VM3252-2 Digital Video Baby Monitor User Manual](#)

## VTech VM3252-2

# VTech VM3252-2 Digital Video Baby Monitor User Manual

Model: VM3252-2

[Setup](#)

[Operation](#)

[Features](#)

[Maintenance](#)

[Troubleshooting](#)

[Specifications](#)

[Warranty](#)

[Support](#)

## INTRODUCTION

This user manual provides comprehensive instructions for the VTech VM3252-2 Digital Video Baby Monitor. Please read this manual thoroughly before using the product to ensure proper operation and safety. Keep this manual for future reference.

## PACKAGE CONTENTS

Your VTech VM3252-2 package includes:

- One (1) Parent Unit with 2.8-inch color LCD screen
- Two (2) Baby Units (cameras)
- Three (3) Power Adapters (one for Parent Unit, two for Baby Units)
- One (1) Rechargeable Battery (pre-installed in Parent Unit)
- User's Manual (this document)



Image: The VTech VM3252-2 Digital Video Baby Monitor system, showing the parent unit and two baby units.

## SETUP

### 1. Charging the Parent Unit Battery

The parent unit operates on a rechargeable battery or AC power. To maximize battery life, charge the parent unit for at least 12 hours before initial use. The battery icon on the screen indicates the charge level.

- Connect the small plug of the parent unit power adapter to the power jack on the side of the parent unit.
- Connect the large end of the power adapter to a wall outlet.

### 2. Connecting the Baby Units (Cameras)

The baby units operate on AC power only. Ensure they are placed within range of the parent unit and have a clear line of sight to the baby.

- Connect the small plug of the baby unit power adapter to the power jack on the back of the baby unit.
- Connect the large end of the power adapter to a wall outlet.
- Position the baby unit at least 3 feet (1 meter) away from the baby.
- Adjust the camera angle manually to get the desired view.



Image: A hand demonstrates adjusting the camera angle of the baby unit.

### 3. Powering On/Off

- To turn on the parent unit, press and hold the **POWER** button until the VTech logo appears.
- To turn off the parent unit, press and hold the **POWER** button until the screen turns off.
- To turn on a baby unit, slide the **ON/OFF** switch to the **ON** position.
- To turn off a baby unit, slide the **ON/OFF** switch to the **OFF** position.

## OPERATION

### 1. Monitoring Your Baby

Once both units are powered on and linked, the parent unit will automatically display video from the baby unit. If you have two cameras, the parent unit will cycle between them or allow manual selection.

## High-resolution, 2.8-inch color LCD screen



*Image: The parent unit's 2.8-inch color LCD screen showing a clear view of a baby.*

### 2. Two-Way Talk Intercom

You can speak to your baby through the baby unit from the parent unit.

- Press and hold the **TALK** button on the parent unit.
- Speak clearly into the microphone on the parent unit.
- Release the **TALK** button to stop speaking and hear your baby.

## Two-way, talk-back intercom



*Image: A user interacting with the parent unit, demonstrating the two-way talk feature.*

### 3. Soothing Sounds and Lullabies

The baby unit can play pre-set lullabies and soothing sounds to help calm your baby.

- Access the menu on the parent unit.
- Navigate to the Lullaby/Sound option.
- Select a melody or sound to play.

# Soothing sounds and lullabies

- 5 calming melodies
- White noise
- Trickling stream
- Plus 2 more ambient sounds



*Image: The baby unit, illustrating its ability to play soothing sounds and lullabies.*

## 4. Volume Control

Adjust the listening volume on the parent unit using the volume buttons.

- Press the **VOLUME UP** button to increase the volume.
- Press the **VOLUME DOWN** button to decrease the volume.
- The parent unit features a 6-level sound indicator to visually represent the sound level detected by the baby unit.

## KEY FEATURES

- **High-Resolution 2.8-inch Color LCD Screen:** Provides a clear video feed of your baby.
- **Automatic Infrared Night Vision:** Automatically activates in low-light conditions for clear viewing in the dark.
- **Temperature Sensor:** Monitors the room temperature around the baby unit and displays it on the parent unit. Alerts can be set for temperature fluctuations.
- **Adjustable Camera Angle:** Manually adjust the baby unit's camera to achieve the optimal viewing angle.
- **2x Digital Zoom:** Zoom in on your baby for a closer look.

- **Up to 1,000 feet of Range:** Stay connected to your baby from various rooms in your home.



*Image: A visual summary of key features including temperature monitoring, night vision, adjustable camera, and sound indicators.*

## MAINTENANCE

### Cleaning the Monitor

- Wipe the surfaces of the parent unit and baby units with a soft, damp cloth.
- Do not use cleaning sprays or liquid cleaners.
- Ensure the units are dry before reconnecting to power.

### Battery Care

- The parent unit uses a rechargeable battery. If the battery life significantly decreases, it may need replacement.
- Only use the specified replacement battery type.
- Do not dispose of batteries in fire. Check local regulations for proper battery disposal.

## TROUBLESHOOTING

## No Link / Out of Range

If the parent unit displays "No Link" or "Out of Range":

- Ensure both the parent unit and baby units are powered on.
- Move the parent unit closer to the baby unit.
- Relocate the baby unit to a position with fewer obstructions (e.g., walls, furniture).
- Avoid placing the monitor near other electronic devices that may cause interference (e.g., Wi-Fi routers, cordless phones).

## Poor Picture Quality / Blurry Night Vision

- Ensure the camera lens is clean and free from dust or smudges.
- Check for adequate lighting in the room during daytime use.
- During night vision, ensure there are no direct light sources near the baby unit that could interfere with the infrared sensors.
- Adjust the position of the baby unit for a clearer view.

## Short Battery Life on Parent Unit

- Ensure the parent unit is fully charged for at least 12 hours before use.
- Reduce screen brightness to conserve battery.
- If the battery life remains significantly short after full charging, the rechargeable battery may need to be replaced.
- Keep the parent unit plugged into the power adapter for continuous use.

## Monitor Randomly Turns Off

- Check if the parent unit battery is low. Recharge the unit.
- Ensure the power adapter is securely connected to both the parent unit and the wall outlet.
- If the issue persists, contact customer support.

## SPECIFICATIONS

Feature	Detail
Model Number	VM3252-2
Screen Size	2.8 inches
Video Capture Resolution	720p
Number of Cameras	2
Connectivity Technology	Wireless
Power Source	AC Powered (Baby Units), Rechargeable Battery / AC Powered (Parent Unit)
Night Vision	Automatic Infrared Night Vision
Digital Zoom	2x

Feature	Detail
Intercom	Two-way talk
Temperature Sensor	Yes
Lullabies/Sounds	Yes
Item Dimensions	4.89 x 4.77 x 2.83 inches
Item Weight	1.88 Pounds
Color	White

## WARRANTY INFORMATION

---

VTech products are designed with quality and reliability in mind. For detailed warranty information, please refer to the warranty card included in your product packaging or visit the official VTech website. Keep your purchase receipt as proof of purchase.

## CUSTOMER SUPPORT

---

If you have any questions or require assistance with your VTech VM3252-2 Digital Video Baby Monitor, please contact VTech customer support:

- **Website:** [www.vtechbabycare.com](http://www.vtechbabycare.com)
- **Email:** [support@vtechbabycare.com](mailto:support@vtechbabycare.com)

For additional resources and FAQs, please visit the VTech support page online.

## PRODUCT OVERVIEW VIDEO

---

Your browser does not support the video tag.

*Video: An official VTech overview of the VM3252-2 Digital Video Baby Monitor, highlighting its features and ease of use.*