

[Manuals.plus](#) /

› [Siser](#) /

› Siser EasyPSV Permanent Self-Adhesive Craft Vinyl User Manual

Siser PEPSV12x12-6blackcat

Siser EasyPSV Permanent Self-Adhesive Craft Vinyl User Manual

Model: PEPSV12x12-6blackcat

INTRODUCTION

Siser EasyPSV Permanent is a pressure-sensitive adhesive vinyl designed for various crafting projects. This vinyl is suitable for application on hard, smooth surfaces such as glass, plastic, wood, and more. It offers a durable, permanent bond for long-lasting designs.



Image: The Siser EasyPSV logo, featuring "Siser" in red with a glitter effect on "EasyPSV" below it, indicating the product type.

SETUP AND PREPARATION

1. **Clean Surface:** Ensure your application surface is clean, dry, and free of dust, oils, or debris. Use rubbing alcohol for best results on non-porous surfaces.
2. **Design Creation:** Create your design using a vinyl cutter software. Remember to mirror your design if you are cutting from the back, though for adhesive vinyl, you typically cut right-side up.
3. **Loading Vinyl:** Place the EasyPSV vinyl onto your cutting mat with the colored side facing up. Adjust your cutting machine settings according to the manufacturer's recommendations for adhesive vinyl. A test cut is always recommended.
4. **Cutting:** Load the mat into your cutting machine and cut your design.

OPERATING INSTRUCTIONS (APPLICATION)

1. **Weeding:** After cutting, remove the excess vinyl from around your design using a weeding tool. Carefully peel away the unwanted parts, leaving only your desired design on the liner.
2. **Applying Transfer Tape:** Cut a piece of transfer tape slightly larger than your design. Place the transfer tape over your weeded design and use a squeegee or credit card to firmly burnish (rub) the tape onto the vinyl, ensuring good adhesion.
3. **Peeling from Liner:** Slowly peel the transfer tape away from the vinyl liner at a 45-degree angle. The vinyl design should lift off the liner and stick to the transfer tape. If parts don't lift, lay the tape back down and burnish again.
4. **Applying to Surface:** Position your design (with transfer tape) onto your prepared surface. Once positioned, firmly burnish the design onto the surface using a squeegee or credit card, working from the center outwards to remove air bubbles.
5. **Removing Transfer Tape:** Slowly and carefully peel the transfer tape away from the applied vinyl at a 45-degree angle. The vinyl design should remain adhered to the surface. If any part lifts, lay the tape back down, burnish, and try again.



Image: Examples of finished projects using Siser EasyPSV vinyl, showcasing various designs applied to ceramic mugs.

MAINTENANCE AND CARE

- **Curing Time:** Allow the vinyl to cure for at least 24-48 hours after application before washing or exposing to harsh conditions.
- **Washing (for items like mugs):** Hand washing is recommended for items decorated with EasyPSV Permanent vinyl. Avoid abrasive scrubbers or harsh detergents. Do not soak.
- **Dishwasher Use:** While EasyPSV Permanent is durable, dishwasher use is not recommended as high heat and harsh detergents can degrade the adhesive over time.
- **Storage:** Store unused vinyl sheets flat in a cool, dry place away from direct sunlight to prevent curling or damage to the adhesive.

TROUBLESHOOTING

Vinyl not cutting cleanly:

Adjust your blade depth and pressure settings. Perform a test cut to find the optimal settings for your machine and the specific vinyl color/finish.

Vinyl not sticking to transfer tape:

Ensure you are burnishing firmly and evenly over the entire design. Try peeling the transfer tape slower and at a sharper angle (closer to 180 degrees) if needed. Ensure the vinyl is not too cold.

Vinyl not sticking to the application surface:

Verify the surface is clean, dry, and smooth. Burnish the design onto the surface very firmly. Allow adequate cure

time before handling. Some textured surfaces may not be suitable for adhesive vinyl.

Air bubbles under the applied vinyl:

Apply the vinyl slowly, working from the center outwards. For small bubbles, you can gently prick them with a fine needle and smooth them out.

PRODUCT SPECIFICATIONS

Feature	Detail
Brand	Siser
Model Number	PEPSV12x12-6blackcat
Material	Polyvinyl Chloride (Vinyl)
Color	Black
Sheet Dimensions	12 inches x 12 inches (approx. 30.48 cm x 30.48 cm)
Number of Sheets	6
Adhesive Type	Permanent, Pressure Sensitive
Water Resistance	Waterproof
Recommended Surfaces	Fabric, Glass, Plastic, Wood (smooth, hard surfaces)
Indoor/Outdoor Usage	Indoor
Item Weight	9.12 ounces (approx. 258.5 grams)
UPC	611856518337

WARRANTY AND SUPPORT

For specific warranty information or product support, please refer to the official Siser website or contact Siser customer service directly. Keep your purchase receipt for any warranty claims.

Siser Official Website: www.siser.com

Contact Information: Refer to the Siser website for the most current contact details.

ASK A QUESTION ABOUT THIS MANUAL

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page’s manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. [Privacy details](#).

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question