Saved from manuals.plus.
Open the live page for links to other documents and user manuals.

TOP VACUUM PARTS NV650, NV650W, NV651, NV652, NV750W, NV751, NV752

TOP VACUUM PARTS Replacement Filter Set Instruction Manual

For Shark Rotator Powered Lift-Away Vacuums

Models: NV650, NV650W, NV651, NV652, NV750W, NV751, NV752

1. Introduction

This instruction manual provides guidance for the proper installation, maintenance, and care of your TOP VACUUM PARTS replacement filter set. These filters are designed to maintain the performance of your compatible Shark Rotator Powered Lift-Away vacuum cleaner by effectively capturing dust and allergens.

Regular filter replacement is crucial for optimal vacuum suction and air filtration. Please read this manual thoroughly before proceeding with installation or maintenance.

2. Compatibility

This replacement filter set is compatible with the following Shark Rotator Powered Lift-Away vacuum models:

- NV650
- NV650W
- NV651
- NV652
- NV750W
- NV751
- NV752

Important: Please verify your vacuum cleaner's model number before installing these replacement filters. The model number is typically located on a sticker on the back or bottom of your vacuum unit. Do not rely solely on visual appearance for compatibility.

3. Installation (Filter Replacement)

To replace the filters in your Shark Rotator Powered Lift-Away vacuum, follow these general steps. For precise filter locations and removal instructions, refer to your original Shark vacuum cleaner's instruction manual.

1. **Power Off and Unplug:** Always ensure your vacuum cleaner is turned off and unplugged from the power outlet before performing any maintenance or filter replacement.
2. **Locate Filter Compartments:** Shark Rotator vacuums typically have multiple filters. The foam and felt filters are usually located in the motor housing, often accessible by removing the dust cup.
3. **Remove Old Filters:** Carefully remove the old foam and felt filters. Note their orientation for correct installation of the new filters.
4. **Insert New Filters:** Place the new TOP VACUUM PARTS foam filter and felt filter into their respective compartments. Ensure they are seated correctly and snugly. The foam filter is typically cylindrical, and the felt filter is flat and circular.



Image 1: This image displays the TOP VACUUM PARTS replacement filter set, including a foam filter and a felt filter, alongside its product packaging. The packaging features the brand logo and product information.



Image 2: A close-up view of the TOP VACUUM PARTS replacement filter components: a cylindrical foam filter and a flat, circular felt filter. These filters are designed to capture dust and debris.

- **Reassemble:** Reattach any covers or the dust cup that were removed during the process. Ensure all components are securely in place before operating the vacuum.

4. Maintenance

To prolong the life of your filters and maintain vacuum performance, regular cleaning is recommended.

Cleaning Instructions:

- **Frequency:** It is recommended to rinse the foam and felt filters every 3 months, or more frequently with heavy use.
- **Rinsing:** Rinse the filters under running water until the water runs clear. Do not use soap or detergents.
- **Drying:** Allow the filters to air dry completely for at least 24 hours before reinstalling them into the vacuum. Do not use a dryer or other heating elements, as this can damage the filter material.
- **Reinstallation:** Ensure filters are completely dry before placing them back into the vacuum to prevent mold or damage to the motor.

Replacement Frequency:

Even with regular cleaning, filters wear out over time. It is generally recommended to replace your foam and felt filters every 6 to 12 months, depending on usage, to ensure optimal filtration and vacuum performance.

5. Specifications

Brand	TOP VACUUM PARTS
Part Number	TVPF661

Compatible Devices	Shark Rotator Powered Lift-Away models NV650, NV650W, NV651, NV652, NV750W, NV751 & NV752 Vacuums
Reusability	Reusable (with proper cleaning)
Number of Pieces	1 set (typically includes 1 foam filter and 1 felt filter)
Item Weight	0.5 ounces

6. Troubleshooting

If you experience issues after replacing your filters, consider the following:

- **Reduced Suction:** Ensure all filters are correctly installed and completely dry. Check for any blockages in the vacuum's hose or brush roll.
- **Unusual Odors:** If filters were not completely dry before reinstallation, mold or mildew could develop. Remove and thoroughly dry filters, or replace them if odors persist.
- **Filters Not Fitting:** Double-check your vacuum's model number against the compatibility list. Ensure the filters are oriented correctly as per your original vacuum manual.

For further assistance, refer to your original Shark vacuum cleaner's user manual or contact customer support.

7. Warranty and Support

TOP VACUUM PARTS offers a 30-day money-back guarantee with your purchase. If you are not satisfied with your filter set, please contact the seller within 30 days of purchase for return instructions. The buyer is responsible for return shipping costs.

For product support or inquiries, please refer to the contact information provided by your retailer or on the product packaging.

Ask a question about this manual

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. Privacy details.

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question

Open the live page

https://manuals.plus/asin/B07BF3Y9BB

More documents and user manuals: **https://manuals.plus/**