

## Evenflo 3892

# Evenflo Advanced Zuri Travel System User Manual

Model: 3892

## 1. INTRODUCTION

---

Thank you for choosing the Evenflo Advanced Zuri Travel System. This comprehensive system is designed for convenience and versatility, adapting to your child's growth from infancy through toddlerhood. It features a stroller that converts into a bassinet, an extendable canopy with an observation window, a multi-position handle, a protective bar, a cup holder, and a foot cover. Additionally, it includes an infant car seat with a base for seamless transitions from car to stroller. This manual provides essential information for the safe and proper assembly, operation, and maintenance of your travel system.



Figure 1.1: The Evenflo Advanced Zuri Travel System, showing both the stroller and the infant car seat with its base.

## 2. SAFETY INFORMATION

---

Please read all instructions carefully before assembly and use. Failure to follow these instructions could result in serious injury or death. Keep this manual for future reference.

- **WARNING:** Never leave child unattended.
- Always use the restraint system. Ensure the 5-point harness is properly secured around your child at all times when using the stroller or car seat.
- Do not overload the stroller or storage basket. Refer to specifications for weight limits.
- Ensure all locking devices are engaged before use.
- Do not use accessories or replacement parts other than those approved by Evenflo.
- The infant car seat is suitable for children weighing from 2.2 kg (4.8 lbs) to 13 kg (28.7 lbs).
- The stroller is suitable for children weighing from 6.5 kg (14.3 lbs) to 15 kg (33 lbs).
- Avoid placing hot liquids in the cup holder.
- Always engage the brakes when the stroller is stationary.

### 3. COMPONENTS

---

Your Evenflo Advanced Zuri Travel System includes the following components:

- Stroller Frame (Aluminum structure)
- Convertible Stroller Seat / Bassinet
- Infant Car Seat
- Infant Car Seat Base
- Canopy
- Protective Bar
- Cup Holder
- Foot Cover
- Wheels (Front and Rear)

### 4. SETUP AND ASSEMBLY

---

#### 4.1 Stroller Assembly

1. **Unfold the Frame:** Release the folding latch and unfold the stroller frame until it clicks into place, ensuring it is fully open and locked.
2. **Attach Rear Wheels:** Slide the rear wheels onto the axle until they click securely. Pull on the wheels to ensure they are firmly attached.
3. **Attach Front Wheels:** Insert the front wheel assemblies into the designated slots on the front of the frame until they click.
4. **Attach Stroller Seat:** Align the seat connectors with the frame receivers and push down until the seat clicks securely into place. Ensure the seat is facing the desired direction (forward or parent-facing).
5. **Attach Canopy:** Secure the canopy to the seat frame by snapping it into the designated attachment points.
6. **Attach Protective Bar:** Insert the protective bar into the slots on the side of the seat until it clicks.
7. **Attach Cup Holder:** Clip the cup holder onto the handle or designated attachment point.



Figure 4.1: Stroller with seat in upright position, ready for use.

## 4.2 Infant Car Seat Base Installation

Refer to the separate infant car seat manual for detailed installation instructions for the car seat base in your vehicle. Ensure the base is securely installed using either the vehicle's seat belt or LATCH system, following all local regulations and car seat instructions.

## 5. OPERATING INSTRUCTIONS

---

## 5.1 Converting Stroller Seat to Bassinet

The stroller seat can be easily converted into a comfortable bassinet for newborns.

1. Ensure the seat is reclined to its lowest position.
2. Adjust the footrest upwards to create a flat surface.
3. Fasten any internal straps or zippers to form the bassinet shape.







Figure 5.1: Stroller in bassinet configuration (front and side views).

## 5.2 Adjusting the Handle

The handle features multiple positions for comfortable pushing.

1. Locate the adjustment buttons on either side of the handle.

2. Press the buttons simultaneously and pivot the handle to your desired height.
3. Release the buttons to lock the handle in place.

### **5.3 Folding the Stroller**

For compact storage and transport, the stroller can be folded.

1. Ensure the seat is in an upright position (or removed, depending on model).
2. Locate the folding mechanisms (usually levers or buttons on the handle or frame).
3. Follow the specific folding sequence for your model, typically involving pressing buttons and pushing the handle forward or down.
4. Secure the folding latch to keep the stroller compact.

### **5.4 Using the Infant Car Seat with Stroller**

The infant car seat can be easily attached to the stroller frame.

1. Remove the stroller seat if necessary (check your specific model's compatibility).
2. Align the car seat with the stroller frame receivers.
3. Push the car seat down firmly until it clicks securely into place.
4. Pull up on the car seat to ensure it is properly locked before placing your child inside.





Figure 5.2: Infant car seat attached to the stroller frame.

## 6. MAINTENANCE

---

- **Cleaning Fabric:** Spot clean fabric parts with a mild soap and cold water. Air dry. Do not bleach.
- **Cleaning Frame:** Wipe the aluminum frame with a soft, damp cloth. Dry thoroughly. Do not use abrasive cleaners.
- **Wheels:** Periodically check wheels for debris and ensure they rotate freely. Lubricate axles if necessary with a

silicone-based lubricant.

- **Storage:** Store the travel system in a clean, dry place away from direct sunlight and extreme temperatures.
- **Inspections:** Regularly inspect all parts for wear, damage, or loose fasteners. Discontinue use if any part is damaged.

## 7. TROUBLESHOOTING

Problem	Possible Cause / Solution
Stroller does not fold easily.	Ensure all folding mechanisms are properly disengaged. Check for obstructions in the folding path.
Wheels squeak or are difficult to turn.	Clean wheels and axles of dirt and debris. Apply a silicone-based lubricant to the axles.
Car seat does not click into stroller frame.	Ensure the car seat is correctly aligned with the receivers. Push down firmly until you hear a click. Check for any obstructions.
Harness is difficult to adjust.	Ensure the harness straps are not twisted. Refer to the specific instructions for harness adjustment in the car seat or stroller section.

## 8. SPECIFICATIONS

Feature	Detail
Model Number	3892
Stroller Minimum Weight Recommendation	6.5 kg (14.3 lbs)
Stroller Maximum Weight Recommendation	15 kg (33 lbs)
Infant Car Seat Minimum Weight Recommendation	2.2 kg (4.8 lbs)
Infant Car Seat Maximum Weight Recommendation	13 kg (28.7 lbs)
Overall Maximum Weight Recommendation	50 kg (110 lbs)
Material Type	Aluminum (Frame)
Harness Type	5-point
Seat Capacity	1
Product Dimensions (L x W x H)	52 x 50 x 78 cm (20.5 x 19.7 x 30.7 inches)
Product Weight	13.5 kg (29.8 lbs)
Stroller Type	Modular Stroller
Car Seat Compatibility	Yes (Included)

## 9. WARRANTY AND SUPPORT

---

Evenflo products are manufactured to high-quality standards and are backed by a limited warranty. For specific warranty details, including coverage period and terms, please refer to the warranty card included with your product or visit the official Evenflo website.

For customer support, replacement parts, or further assistance, please contact Evenflo Customer Service through their official website or the contact information provided on your product packaging.

**Evenflo Official Website:** [www.evenflo.com](http://www.evenflo.com)

