Emtek Modern Rectangular Flush Pull 1-3/4" x 6"

Emtek Modern Rectangular Flush Pull - Installation and Care Manual

Model: 1-3/4" x 6" Satin Nickel

1. Introduction

Thank you for choosing the Emtek Modern Rectangular Flush Pull. This manual provides essential information for the proper installation, operation, and maintenance of your new flush pull. Please read these instructions carefully before beginning installation to ensure optimal performance and longevity of the product. Retain this manual for future reference.

2. Product Overview

The Emtek Modern Rectangular Flush Pull is designed for applications where a recessed handle is desired, such as sliding doors, pocket doors, or cabinet doors. Its sleek, minimalist design integrates seamlessly into modern interior aesthetics, providing a clean and unobtrusive look. This flush pull is constructed from durable metal and finished in Satin Nickel, offering both aesthetic appeal and functional reliability.



This image shows the Emtek Modern Rectangular Flush Pull in a Satin Nickel finish. The pull features a minimalist rectangular design, ideal for modern interiors. It is designed to be recessed into a door or drawer surface, providing a sleek, flush appearance.



This image displays four Emtek Modern Rectangular Flush Pulls in different finishes: Flat Black, Satin Nickel, Polished Brass, and Oil Rubbed Bronze. They are arranged on a white surface, highlighting the variety of available aesthetic options.

3. Setup and Installation

Proper installation is crucial for the functionality and appearance of your flush pull. If you are unsure about any step, it is recommended to consult a professional installer.

Tools Required:

- Measuring Tape or Ruler
- Pencil
- Drill
- Router (for recessing) or Chisel
- Screwdriver (appropriate for mounting screws)
- Safety Glasses

Installation Steps:

1. **Prepare the Surface:** Determine the desired location for the flush pull on your door or drawer. Ensure the surface is clean and free of obstructions.
2. **Mark the Cutout:** Using the flush pull as a template, carefully mark the outline of the recess area on the door or drawer surface with a pencil. Ensure precise measurements for a snug fit.
3. **Create the Recess:** Using a router or chisel, carefully cut out the marked area to the appropriate depth, allowing the flush pull to sit flush with the surface. Test fit the pull periodically to ensure a proper fit.
4. **Drill Pilot Holes:** Once the recess is complete, mark and drill pilot holes for the mounting screws. Ensure the pilot holes are slightly smaller than the screw diameter to prevent splitting the wood.

5. **Secure the Flush Pull:** Place the flush pull into the recess and align the screw holes. Insert the mounting screws and tighten them securely with a screwdriver. Do not overtighten, as this can damage the pull or the door material.



An Emtek Modern Rectangular Flush Pull is shown installed on a dark-colored sliding door, demonstrating its recessed design and how it sits flush with the door surface. The surrounding area features a light-colored wall and a bench.

4. Operating Instructions

To operate the Emtek Modern Rectangular Flush Pull, simply grasp the recessed area with your fingers and apply gentle, consistent pressure to slide or pull the door/drawer open or closed. The design allows for a comfortable and secure grip.

5. Maintenance

To maintain the finish and functionality of your Emtek flush pull, follow these guidelines:

- **Cleaning:** Clean regularly with a soft, damp cloth. For stubborn marks, a mild soap solution can be used.
- **Avoid Harsh Chemicals:** Do not use abrasive cleaners, solvents, or polishes containing harsh chemicals, as these can damage the Satin Nickel finish.
- **Regular Inspection:** Periodically check the mounting screws for tightness. If they become loose, gently tighten them to prevent wobbling or damage.

6. Troubleshooting

If you encounter any issues with your flush pull, consider the following common solutions:

- **Pull is Loose:** Check the mounting screws. If they are loose, tighten them carefully. Avoid overtightening.
- **Difficulty Operating Door/Drawer:** Ensure the door or drawer mechanism itself is functioning correctly. The flush pull should not impede movement if properly installed.
- **Finish Discoloration:** This is often due to exposure to harsh cleaning agents or environmental factors. Refer to the maintenance section for proper cleaning techniques.

7. Specifications

Feature	Detail
Brand	Emtek
Model	Modern Rectangular Flush Pull
Material	Metal
Finish	Satin Nickel
Style	Modern
Product Dimensions	4"L x 6"W (Overall)
Size	1-3/4" x 6"

8. Warranty and Support

Emtek products are manufactured to high-quality standards and are backed by a manufacturer's warranty. For specific warranty details, claims, or technical support, please refer to the official Emtek website or contact their customer service directly. Keep your purchase receipt as proof of purchase.
For further assistance, visit: www.emtek.com

© 2023 Emtek. All rights reserved. Information subject to change without notice.