

[manuals.plus](#) /› [DELTA](#) /› [DELTA FAUCET CO Ashton Single Handle High Arc Pull Down ShieldSpray Kitchen Faucet User Manual](#)

DELTA 19922-SSSD-DST

DELTA FAUCET CO Ashton Single Handle High Arc Pull Down ShieldSpray Kitchen Faucet User Manual

Model: 19922-SSSD-DST

Brand: DELTA

1. INTRODUCTION

This manual provides comprehensive instructions for the installation, operation, and maintenance of your DELTA FAUCET CO Ashton kitchen faucet. Please read this manual thoroughly before installation and use to ensure proper function and longevity of your product.

2. SAFETY INFORMATION

- Always turn off the water supply before beginning any installation or maintenance.
- Wear safety glasses during installation.
- If you are unsure about any part of the installation, consult a qualified plumber.
- Ensure all connections are secure to prevent leaks.

3. PACKAGE CONTENTS

Verify that all components are present before beginning installation:

- Kitchen faucet (Main unit)
- Soap dispenser
- Mounting hardware
- Installation instructions (this manual)

4. INSTALLATION

This section provides general guidance for installing your new kitchen faucet. For detailed, step-by-step instructions, please refer to the separate installation guide included with your product or consult the official DELTA website.

1. **Prepare the Sink:** Ensure the sink area is clean and dry. If replacing an old faucet, remove it and clean any residue.
2. **Mount the Faucet:** Insert the faucet body into the designated hole(s) on your sink or countertop. Secure it from underneath using the provided mounting hardware.

3. **Connect Water Lines:** Attach the hot and cold water supply lines to the corresponding inlets on the faucet. Ensure connections are hand-tightened, then use a wrench for a quarter turn. Do not overtighten.
4. **Install Soap Dispenser:** If included, install the soap dispenser into its designated hole and secure it. Fill with liquid soap.
5. **Test for Leaks:** Slowly turn on the main water supply and check all connections for leaks. Tighten any leaking connections as necessary.



Figure 1: DELTA Ashton Faucet installed in a kitchen setting. The high arc design provides ample clearance.

5. OPERATING INSTRUCTIONS

Your DELTA Ashton faucet is designed for ease of use with its single-handle operation and versatile pull-down sprayer.

5.1. Water Flow and Temperature Control

The single handle controls both water flow and temperature:

- To turn the water on, lift the handle upwards.
- To increase water flow, lift the handle further.
- To adjust temperature, move the handle left for hot water and right for cold water.
- To turn the water off, push the handle downwards.

5.2. Pull-Down Sprayer Operation

The pull-down sprayer offers enhanced functionality:

- **Extend the Sprayer:** Gently pull the spray wand down from the spout. The flexible hose allows for extended reach within and around the sink.
- **Switch Spray Modes:** Use the buttons on the spray wand to toggle between different water patterns (e.g., stream, spray, ShieldSpray).

- **Retract the Sprayer:** When finished, guide the spray wand back into the spout. The Magnatite Docking system will securely hold it in place.



Figure 2: The pull-down sprayer in action, providing flexibility for various kitchen tasks.

6. MAINTENANCE

6.1. Cleaning the Faucet

To maintain the finish and performance of your faucet:

- Clean with a soft, damp cloth and mild soap.
- Avoid abrasive cleaners, harsh chemicals, or scouring pads, as these can damage the finish.
- For the Touch-Clean spray holes, simply wipe away mineral residue with your finger.

6.2. Soap Dispenser Refill

To refill the integrated soap dispenser, lift the pump head and pour liquid soap directly into the reservoir from above the counter.

7. TROUBLESHOOTING

Problem	Possible Cause	Solution
Low Water Flow	Clogged aerator; partially closed shut-off valve.	Clean or replace aerator; fully open shut-off valves.
Leaking from Spout	Worn out O-rings or seals.	Replace O-rings or seals.
Sprayer Not Retracting Properly	Obstruction in hose path; weight not properly attached.	Check for obstructions; ensure sprayer weight is correctly installed.

8. SPECIFICATIONS

- **Brand:** DELTA
- **Model Name:** Kitchen faucet
- **Model Number:** 19922-SSSD-DST
- **Finish Type:** Brilliance Finish (Stainless Steel)
- **Material:** Stainless Steel
- **Mounting Type:** Deck Mount
- **Number of Handles:** 1
- **Spout Design:** High Arc
- **Maximum Flow Rate:** 1.8 Gallons Per Minute
- **Special Features:** Pull Down Sprayer, Magnatite Docking, Diamond Seal Technology, Touch Clean Spray Holes, ADA Compliant
- **Item Weight:** 5.5 Pounds
- **Product Dimensions:** 24 x 13.13 x 3.38 inches

9. WARRANTY & SUPPORT

For warranty information, product registration, or technical support, please visit the official DELTA FAUCET CO website or contact their customer service. Ensure you retain your proof of purchase for warranty claims.

Protection Plans: Extended protection plans are available for purchase separately. Refer to your retailer for details on 3-Year or 4-Year Protection Plans.