#### Manuals+

Q & A | Deep Search | Upload

#### manuals.plus /

- > SILENCER /
- > 2-Button SILENCER (MAGNADYNE) Keyfob Remote SLRF412 FCC ID H5OT25

## **SILENCER SLRF412**

## **SILENCER Keyfob Remote Instruction Manual**

Model: SLRF412 | FCC ID: H5OT25

## INTRODUCTION

This manual provides detailed instructions for the setup, operation, and maintenance of your SILENCER SLRF412 2-Button Keyfob Remote. This is an OEM replacement part designed for user programming. Proper programming is essential for the remote's functionality with your vehicle's control module.

## **PRODUCT OVERVIEW**



Figure 1: Front View of Keyfob Remote

This image displays the front of the SILENCER SLRF412 keyfob remote. It features two distinct buttons: an asterisk (\*) button at the top and an unlock (padlock) button below it. The SILENCER brand logo is visible along the left side.



Figure 2: Back View of Keyfob Remote

This image shows the back of the SILENCER SLRF412 keyfob remote. Clearly visible are the engraved part number "P/N: SL-RF412" and the FCC ID "FCC ID: H5OT25". This information is crucial for identification and compliance.

## SETUP AND PROGRAMMING

The SILENCER SLRF412 keyfob remote is user-programmable. The control module in your vehicle must be programmed to accept this replacement part. Detailed DIY instructions are included with the part. Please follow them carefully.

## **Important Prerequisites:**

- Working Valet Button or Switch: Programming requires that your vehicle's alarm system has a functional valet button or switch. This is essential for entering programming mode.
- Working Siren (Recommended): While not strictly essential, a working siren on your alarm system is very helpful during the programming process as it often provides audible feedback for successful steps.

Refer to the specific programming instructions provided with your remote for the exact steps. Typically, this involves entering a programming mode in your vehicle's alarm system using the valet button, then pressing buttons on the new

## **OPERATING INSTRUCTIONS**

Once successfully programmed, your SILENCER SLRF412 keyfob remote will control your vehicle's alarm and keyless entry system. The remote features two primary buttons:

- Asterisk (\*) Button: This button typically controls the arming/disarming functions of your alarm system. Pressing it once usually arms the system, and pressing it again (or a specific sequence) disarms it. Refer to your vehicle's alarm system manual for exact functionality.
- Unlock (Padlock) Button: This button is generally used for unlocking your vehicle's doors. A single press typically
  unlocks all doors.

Note: The exact functions of these buttons may vary slightly depending on the specific alarm system installed in your vehicle. Always consult your vehicle's alarm system manual for comprehensive operational details.

## **MAINTENANCE**

#### **Battery Replacement:**

The SILENCER SLRF412 keyfob remote requires 1 Lithium Metal battery (included). When the remote's range decreases or it becomes unresponsive, it may be time to replace the battery.

- 1. Carefully open the remote casing. This may require a small flat-head screwdriver or a prying tool.
- 2. Note the orientation of the existing battery before removing it.
- 3. Insert the new Lithium Metal battery, ensuring correct polarity.
- 4. Close the remote casing securely.

Dispose of old batteries responsibly according to local regulations.

## **TROUBLESHOOTING**

#### Remote Not Responding After Programming:

- Ensure the battery is correctly installed and has sufficient charge.
- Re-attempt the programming procedure carefully, ensuring all steps are followed precisely.
- Verify that your vehicle's valet button/switch is functioning correctly.
- Confirm that the remote is compatible with your specific vehicle alarm system model.

## • Reduced Range:

- Replace the battery with a new one.
- Ensure there are no significant obstructions between the remote and the vehicle.

#### • Buttons Not Functioning:

- · Check for physical damage to the buttons or casing.
- If the remote was recently opened, ensure all internal components are seated correctly.

## **SPECIFICATIONS**

Model Number	SLRF412	
--------------	---------	--

FCC ID	H5OT25
Brand	SILENCER (Manufactured by MAGNADYNE)
Product Dimensions	3.5 x 1.5 x 0.5 inches
Item Weight	4 ounces
Batteries	1 Lithium Metal battery (included)
Number of Buttons	2 (Asterisk, Unlock)
Connectivity Technology	Radio Frequency
Compatible Devices	Vehicle Alarm/Keyless Entry Systems
Special Feature	Ergonomic Design

## WARRANTY AND SUPPORT

Information regarding specific warranty terms or direct manufacturer support for the SILENCER SLRF412 keyfob remote was not available in the provided product data. For warranty claims or technical support, please refer to the documentation that came with your original vehicle alarm system or contact the vendor from whom you purchased this replacement remote.

This product is an OEM remote, not an aftermarket replacement, and is intended to function as a direct replacement for the original part number SLRF412.

© 2024 SILENCER. All rights reserved.

This manual is for informational purposes only. Specifications are subject to change without notice.

#### **Related Documents - SLRF412**



## Silencer 552SSR Remote Start, Security, and Keyless Entry System Quick Reference Install Guide

A quick reference guide for installing the Silencer 552SSR remote start, security, and keyless entry system. This guide covers mounting the receiver/control center, programming system features via the RCC button or PC/App, wireless tach learning, remote start shutdown diagnostics, shock sensor programming, and remote control pairing.



#### Silencer 662 Remote Start System: Quick Reference Installation Guide

This guide provides essential information for the professional installation of the Silencer 662 Remote Start, Security, and Keyless Entry System, including wiring diagrams, programming features, and troubleshooting tips.



# Silencer 56SL Two-Way 3-Channel Extended Range Remote Start Keyless Entry System User Manual

Comprehensive user manual for the Silencer 56SL Two-Way 3-Channel Extended Range Remote Start Keyless Entry System, detailing operation, features, and troubleshooting.




#### SILENCER 58SL Remote Start Keyless Entry System Quick Reference Install Guide

Quick reference installation guide for the SILENCER 58SL Remote Start and Keyless Entry System. Covers programming features, wiring, learning modes, and diagnostics for professional installers.



## Silencer 55SL Two Way 3-Channel 915 MHz Extended Range Remote Start Keyless Entry System User Manual

User manual for the Silencer 55SL Two Way 3-Channel 915 MHz Extended Range Remote Start Keyless Entry System. This guide provides detailed instructions on operation, programming, features, and warranty information from Magnadyne Corporation.



#### Scorpion Exhaust Fitting and Cleaning Instructions for Honda CBR 125 R (2011-2016)

Detailed fitting and cleaning instructions for the Scorpion Serket Silencer (RHA-151) for the Honda CBR 125 R motorcycle, model years 2011-2016. Includes parts list, installation steps, and care advice.

#### Documents - SILENCER - SLRF412



#### [pdf] User Manual Instructions Warranty

SL 51X 2 Channel Remote Start USERS MANUAL with Unlock System This unit is designed for professional installation only For Warranty information Please visit our website at magnadyne F5 REMOTE CONTROL TRANSMITTERS CHANGING THE BATTERY IN YOUR SilencerSL UsersManual Manual content manuals

SL- 5 1X 2-Channel Remote Start with Remote Unlock System USERS MANUAL This unit is designed for professional installation only. For Warranty information: Please visit our website at www.magnadyne.com REMOTE CONTROL TRANSMITTERS: CHANGING THE BATTERY IN YOUR TRANSMITTERS SLRF412: The transmitter u...

lang:en score:26 filesize: 425.13 K page\_count: 8 document date: 2017-10-30



#### [pdf] User Manual Installation Guide Warranty

INSTALLATION MANUAL Magnadyne This Remote Starter with Alarm and Keyless Entry System has been designed to be installed BY PROFESSIONAL INSTALLERS on fuel injected vehicles an SilencerSL 51X InstallationManual Manual magnadyne content manuals

SL- 5 1X 2-Channel Remote Start with Remote Unlock System INSTALLATION MANUAL This unit is designed ... shown . IM\_FULL\_SL-51X\_REV-A 11 PROFESSIONAL SERIES CHANGING THE BATTERY IN YOUR TRANSMITTERS SLRF412: The transmitter uses one 1 3-volt lithium ion battery #CR2450 with the side facing ...

lang:en score:23 filesize: 767.06 K page\_count: 21 document date: 2017-10-30