



Manuals.plus /

› Rohl /

› Rohl Perrin & Rowe Georgian Era Pulldown Faucet U.4743ULB-2 Instruction Manual

Rohl U.4743ULB-2

Rohl Perrin & Rowe Georgian Era Pulldown Faucet

MODEL U.4743ULB-2 INSTRUCTION MANUAL

Introduction

This manual provides essential information for the installation, operation, and maintenance of your Rohl Perrin & Rowe Georgian Era Pulldown Bar/Food Prep Faucet, Model U.4743ULB-2. Please read these instructions carefully before beginning installation or use to ensure proper function and longevity of the product.

The Georgian Era Pulldown Faucet combines classic design with modern functionality, featuring a single-hole deck mount installation and a durable unlacquered brass finish. Its design is inspired by the gentility and decorum of the Georgian period, offering a timeless aesthetic for your kitchen or bar area.

Key Features:

- Dual-spray functionality with ability to toggle between stream and spray settings.
- Retractable pull-down handspray with secure docking system.
- Silent braided nylon hose reduces friction for quieter operation.
- Flow rate of 1.75 GPM at 60 PSI for effective cleaning.
- Ceramic disc cartridge for durability and long-lasting performance.
- Solid brass construction for beauty, durability, and performance.
- Water activates by pushing the handle inwards toward the spout.
- Unlacquered Brass finish naturally ages over time, developing a unique patina.

Setup and Installation

Installation of this faucet requires basic plumbing knowledge. If you are unsure about any steps, it is recommended to consult a qualified professional plumber.

Before Installation:

- Ensure all necessary tools are available.
- Turn off the main water supply to the installation area.
- Clear the area under the sink for easy access.

Installation Steps (General Overview):

1. Position the faucet body into the single-hole opening on your deck or countertop. The faucet is designed for a single-hole installation type.
2. Secure the faucet from underneath the sink using the provided mounting hardware. Ensure the maximum deck thickness of 2-1/2 inches is not exceeded.
3. Connect the hot and cold water supply lines to the appropriate inlets on the faucet.
4. Connect the pull-down spray hose to the faucet body and ensure it can retract smoothly.
5. Once all connections are secure, slowly turn on the main water supply and check for leaks.

Included Components: Handle, Lid.



Image: Full view of the Rohl Perrin & Rowe Georgian Era Pulldown Faucet, showcasing its design and unlacquered brass finish, ready for installation.

Operating Instructions

Your Georgian Era Pulldown Faucet is designed for ease of use with a single lever handle and versatile spray functions.

Water Flow and Temperature Control:

- The single lever handle controls both water flow and temperature.
- To activate water flow, push the handle inwards toward the spout.
- Move the handle left for hot water and right for cold water.
- Adjust the handle's position to achieve the desired water temperature and flow rate.

Pulldown Spray Operation:

- Gently pull down the spray head from the spout. The retractable handspray features a secure docking system.
- The spray head offers dual-spray functionality. Press the button on the spray head to toggle between a steady stream and a powerful spray.
- The spout swivels 180 degrees, allowing for greater access to all areas of the sink.
- After use, guide the spray head back into the spout until it securely docks. The silent braided nylon hose ensures smooth and quiet retraction.



Image: Close-up view of the faucet's metal lever handle, illustrating the control mechanism for water flow and temperature.

Maintenance

Proper care and maintenance will help preserve the appearance and functionality of your Rohl Perrin & Rowe faucet.

Unlacquered Brass Finish Care:

- The Unlacquered Brass finish is a living finish designed to naturally age and develop a unique patina over time. This is a characteristic feature and not a defect.
- To maintain the original luster, polish regularly with a high-quality brass cleaner. Follow the cleaner manufacturer's instructions carefully.
- To allow the patina to develop naturally, simply clean with a soft, damp cloth and mild soap. Avoid abrasive cleaners or harsh chemicals, as these can damage the finish.
- Always rinse thoroughly with clean water and dry with a soft cloth after cleaning.

General Faucet Care:

- Clean the exterior of the faucet regularly with a soft, damp cloth and mild soap.
- Avoid using abrasive sponges, scouring pads, or harsh chemical cleaners, as these can scratch or damage the surface.
- The ceramic disc cartridge is designed for long-lasting, drip-free performance and typically requires no maintenance.
- Periodically check all connections for tightness to prevent leaks. Do not overtighten.



Image: A craftsman engaged in hand-polishing a brass faucet component, illustrating the attention to detail in manufacturing that contributes to the product's finish quality.

Troubleshooting

If you encounter issues with your faucet, refer to the following common troubleshooting steps. For problems not listed here, please contact customer support.

Common Issues and Solutions:

- **Low Water Flow:**
 - Check if the main water supply valves are fully open.
 - Inspect the aerator at the end of the spray head for mineral buildup or debris. Clean if necessary.
 - Ensure supply lines are not kinked or obstructed.

- **Leaks from Faucet Base:**
 - Check the tightness of the mounting nut under the sink. Do not overtighten.
 - Ensure the O-rings and gaskets are properly seated during installation.

- **Dripping from Spout:**
 - The ceramic disc cartridge is designed to prevent drips. If dripping occurs, it may indicate a need for professional inspection or cartridge replacement.

- **Spray Head Not Retracting Properly:**
 - Check for obstructions under the sink that might be interfering with the hose weight or hose movement.
 - Ensure the hose weight is correctly positioned on the pull-down hose.

Technical Specifications

Brand	Rohl
Manufacturer	Perrin & Rowe
Model Name	Georgian Era
Model Number	U.4743ULB-2
Material	Brass
Finish Type	Unalacquered Brass
Mounting Type	Deck Mount
Installation Type	Single Hole
Number of Handles	1
Maximum Flow Rate	1.8 Gallons Per Minute (GPM)
Spout Height (deck to spout outlet)	7.5 Inches
Spout Reach (center of faucet body to center of spout outlet)	7.25 Inches
Faucet Height (deck to top of faucet)	14 Inches
Max Deck Thickness	2.5 Inches
Item Weight	7 Pounds
Product Dimensions	1 x 1 x 1 inches (packaging/shipping dimensions)
UPC	824438385634

Warranty Information

Please note that this product comes with **NO EXPRESS WARRANTY**. For specific details regarding any implied warranties or consumer rights, please refer to the terms and conditions provided at the point of purchase or contact the retailer.

Customer Support

For further assistance, technical support, or inquiries regarding your Rohl Perrin & Rowe Georgian Era Pulldown Faucet, please contact the manufacturer or your authorized retailer.

Manufacturer: Perrin & Rowe

Brand: Rohl

Please have your model number (U.4743ULB-2) and purchase information available when contacting support.