

## Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

manuals.plus /

> [Moen](#) /

> [Moen T908 Genta LX Two-Handle Deck Mounted Modern Roman Tub Faucet, Valve Required, Chrome - Instruction Manual](#)

## Moen T908

# Moen Genta LX Two-Handle Deck Mounted Modern Roman Tub Faucet

Model: T908 | Brand: Moen

## 1. INTRODUCTION

Thank you for choosing the Moen Genta LX Two-Handle Deck Mounted Modern Roman Tub Faucet. This faucet is designed to bring a sleek, contemporary style to your bathroom with its curved edges and highly reflective chrome finish. This manual provides essential information for the proper installation, operation, and maintenance of your new faucet, ensuring years of reliable performance.



Figure 1.1: The complete Moen Genta LX two-handle Roman tub faucet in a polished chrome finish, featuring a wide, flat spout and two lever handles.

## 2. SAFETY INFORMATION

Please read all instructions carefully before installation and use. Failure to follow these instructions may result in personal injury, property damage, or product malfunction.

- Always turn off the main water supply before beginning any work on the faucet.
- Wear safety glasses during installation to protect your eyes.
- If you are unsure about any part of the installation, consult a qualified plumber.
- Ensure all connections are secure and leak-free before turning on the water supply.
- Do not use abrasive cleaners or harsh chemicals on the chrome finish, as this may damage the surface.

### 3. PARTS LIST

Verify that all components are present before beginning installation. This trim kit requires a separate Moen M-PACT valve (models 4792, 4793, 4794, 4796, 4797, or 4798) for complete installation.

- Tub Faucet Trim (Spout and Handles)
- Plug Button
- Hex Wrench (5/32")
- Instruction Manual



Figure 3.1: The separate valve assembly required for the installation of the Moen Genta LX tub faucet, showing the hot and cold water inlets and the main valve body.

## 4. TOOLS REQUIRED

---

The following tools are typically required for installation:

- Adjustable Wrench
- Phillips Screwdriver
- Plumber's Putty or Silicone Sealant
- Tape Measure
- Safety Glasses
- Flashlight (optional)

## 5. SETUP AND INSTALLATION

---

This section outlines the general steps for installing the Moen Genta LX tub faucet trim. Refer to the specific instructions provided with your Moen M-PACT valve for valve body installation.

1. **Prepare the Deck:** Ensure the mounting surface is clean, dry, and free of debris. The faucet requires three holes for installation.
2. **Install the Valve Body:** Follow the instructions provided with your Moen M-PACT valve (sold separately) to install the valve body into the tub deck. Ensure it is securely fastened and properly connected to the hot and cold water lines.
3. **Install the Spout:** Apply a thin bead of plumber's putty or silicone sealant around the base of the faucet spout. Insert the spout into the center hole on the tub deck. From underneath the deck, secure the spout with the provided mounting hardware, tightening it firmly but carefully to avoid overtightening.
4. **Install the Handles:** Place the handle escutcheons over the side holes. Connect the handle assemblies to the valve stems, ensuring the hot and cold handles are on the correct sides (typically hot on the left, cold on the right). Secure the handles with the provided screws or set screws, using the 5/32" hex wrench if applicable.
5. **Test for Leaks:** Once all components are installed and secured, slowly turn on the main water supply. Check all connections for any signs of leaks. If leaks are detected, tighten the connections as necessary.
6. **Verify Operation:** Operate both handles to ensure smooth water flow and proper temperature control.

## 6. OPERATING INSTRUCTIONS

---

The Moen Genta LX tub faucet features two lever handles for precise control over water flow and temperature.

- **Turning On/Off:** Lift the lever handles to turn on the water. Push them down to turn off the water.
- **Adjusting Temperature:** The left handle controls hot water, and the right handle controls cold water. Adjust both handles simultaneously to achieve your desired water temperature.
- **Adjusting Flow:** The further you lift the handles, the greater the water flow.

## 7. MAINTENANCE

---

Proper care and cleaning will help maintain the finish and performance of your Moen faucet.

- **Cleaning the Finish:** Clean the chrome finish with a soft, damp cloth and mild soap. Rinse thoroughly with warm water and dry with a soft cloth to prevent water spots.
- **Avoid Harsh Cleaners:** Do not use abrasive cleaners, harsh chemicals, ammonia-based cleaners, or polishing agents, as these can damage the finish.
- **Aerator Maintenance:** If water flow becomes restricted, the aerator may need cleaning. Unscrew the aerator from the spout, rinse out any debris, and reattach.

## 8. TROUBLESHOOTING

If you experience issues with your faucet, refer to the following common problems and solutions:

Problem	Possible Cause	Solution
Low Water Flow	Clogged aerator; partially closed shut-off valve; debris in water lines.	Clean aerator; ensure shut-off valves are fully open; flush water lines.
Leaking from Spout	Worn cartridge; debris in cartridge.	Replace cartridge; clean cartridge.
Leaking at Base of Faucet	Loose mounting nuts; improper sealant application.	Tighten mounting nuts; reapply plumber's putty or silicone sealant.
Difficulty Adjusting Temperature	Cartridge issue; water heater setting.	Inspect/replace cartridge; check water heater temperature.

## 9. SPECIFICATIONS

Feature	Detail
Brand	Moen
Model Name	Genta LX
Part Number	T908
Finish Type	Chrome
Material	Metal
Mounting Type	Deck Mount
Number of Handles	2
Hole Count	3
Maximum Flow Rate	16 Gallons Per Minute
Spout Height	6.94 Inches
Spout Reach	7.94 Inches
Item Weight	5.89 pounds
ADA Compliant	Yes

Feature	Detail
Country of Origin	USA

## 10. WARRANTY AND SUPPORT

---

Moen products are manufactured under the highest standards of quality and workmanship. This Moen faucet is backed by a **Limited Lifetime Warranty** against leaks, drips, and finish defects to the original consumer purchaser.

For detailed warranty information, replacement parts, or technical assistance, please visit the official Moen website or contact Moen customer service directly. Keep your purchase receipt as proof of purchase for warranty claims.

*Note: The M-PACT common valve system allows you to update the faucet style in the future without replacing any plumbing.*

---