

Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

manuals.plus /

- › [Summerset Grills](#) /
- › [Summerset SSRFR-24DR2 24-inch Outdoor Refrigerator User Manual](#)

Summerset Grills SSRFR-24DR2

Summerset SSRFR-24DR2 24-inch Outdoor Refrigerator User Manual

INTRODUCTION

This manual provides essential information for the safe and efficient operation, installation, and maintenance of your Summerset SSRFR-24DR2 24-inch 5.3 cubic foot outdoor rated deluxe 2-drawer refrigerator. Please read all instructions carefully before use to ensure proper functionality and to prevent injury or damage.

The Summerset SSRFR-24DR2 is constructed from 304-grade stainless steel and features front venting, making it suitable for built-in outdoor kitchen installations. Key features include a digital thermostat, temperature alarm, LED interior lighting, automatic defrost, and a door lock for security.

IMPORTANT SAFETY INFORMATION

Observe all safety precautions to reduce the risk of fire, electric shock, or injury.

- **Electrical Safety:** Ensure the refrigerator is connected to a properly grounded 115-volt, 1.3 Amp electrical outlet. Do not use extension cords or adapter plugs.
- **Outdoor Use:** This appliance is UL Certified for Outdoor Use. Ensure it is installed in a location protected from direct rain and excessive sunlight.
- **Ventilation:** Do not block the front ventilation grille. Adequate airflow is crucial for proper operation and to prevent overheating.
- **Flammable Materials:** Do not store or use gasoline or other flammable vapors and liquids in the vicinity of this or any other appliance.
- **Child Safety:** Prevent children from playing with, on, or inside the appliance. Old refrigerators are a suffocation hazard.
- **Servicing:** Do not attempt to repair or replace any part of your refrigerator unless specifically recommended in this manual. All other servicing should be referred to a qualified technician.

PACKAGE CONTENTS

Verify that all items are present upon unpacking:

- Summerset SSRFR-24DR2 Refrigerator Unit
- Adjustable Leveling Legs (pre-installed or in packaging)
- Keys for Door Lock

- User Manual (this document)

INSTALLATION AND SETUP

Unpacking

Carefully remove all packaging materials, including foam and tape. Inspect the unit for any shipping damage. Report any damage to your retailer immediately.

Location Requirements

- **Outdoor Placement:** This unit is designed for outdoor use. Install it in a location that is protected from direct weather exposure.
- **Ventilation:** The refrigerator features front venting. Ensure the front grille is not obstructed to allow for proper airflow.
- **Leveling:** Use the adjustable leveling legs to ensure the unit is stable and level. Proper leveling is crucial for efficient operation and door alignment.

Electrical Connection

Connect the refrigerator to a dedicated, grounded 115-volt, 60 Hz AC outlet with a 1.3 Amp capacity. Do not use a two-prong adapter or an extension cord. Consult a qualified electrician if you are unsure about your electrical supply.

Built-in Installation

The front venting design allows for flush built-in installation into an outdoor kitchen island. Ensure the cut-out dimensions are accurate:

- **Cut-Out Height:** 35 inches (88.9 cm)
- **Cut-Out Width:** 25 inches (63.5 cm)
- **Cut-Out Depth:** 26 inches (66.04 cm)



Figure 1: Refrigerator Dimensions for Installation



Figure 2: Built-in Installation Example

OPERATION

Powering On

After installation and electrical connection, the unit will power on. Allow several hours for the interior to reach the set temperature before loading with contents.

Temperature Control

The refrigerator features a digital thermostat and display located inside the upper drawer. Use the controls to set your desired temperature. The display will show the current internal temperature.

Temperature Alarm

The unit is equipped with a temperature alarm that activates if the interior temperature falls below or rises above the recommended range. Refer to the digital display for specific error codes or indicators.

Internal Lighting

An LED light is integrated into the interior for improved visibility of contents.

Door Lock

The refrigerator drawers are equipped with a lock for security. Use the provided keys to lock and unlock the drawers as needed.



Figure 3: Interior View with Digital Display

MAINTENANCE

Cleaning

- **Exterior:** Clean the stainless steel exterior with a soft cloth and a mild stainless steel cleaner. Avoid abrasive cleaners or scouring pads.
- **Interior:** Clean the interior with a solution of mild soap and warm water. Rinse thoroughly and dry with a soft cloth.
- **Gaskets:** Regularly clean the door gaskets to ensure a proper seal.

Automatic Defrost

The unit features an automatic defrost system, eliminating the need for manual defrosting. Water from the defrost cycle is evaporated.

Long-Term Storage

If the refrigerator will not be used for an extended period, unplug it, clean the interior, and leave the drawers slightly ajar to prevent odors and mold growth.

TROUBLESHOOTING

Review the following common issues and solutions before contacting customer support.

Problem	Possible Cause	Solution
Refrigerator does not operate	No power to the unit; circuit breaker tripped; power cord not fully plugged in.	Check power supply, circuit breaker, and ensure cord is securely plugged in.
Temperature is not cold enough	Temperature setting too high; door/drawer left open; excessive door/drawer openings; unit overloaded; poor ventilation.	Adjust temperature setting; ensure drawers are closed properly; reduce frequency of openings; do not overload; check for obstructed front grille.
Unit is noisy	Unit not level; normal operating sounds (compressor, fan).	Adjust leveling legs to ensure stability. Some operational sounds are normal.
Drawers do not close properly	Unit not level; contents obstructing closure; dirty door gaskets.	Level the unit; rearrange contents; clean door gaskets.

SPECIFICATIONS

Feature	Detail
Model Number	SSRFR-24DR2
Product Dimensions (D x W x H)	26"D x 25"W x 35"H
Capacity	5.3 Cubic Feet
Installation Type	Freestanding / Built-in (Front Venting)
Number of Doors	2 (Drawers)
Material	304 Grade Stainless Steel
Electrical Requirements	115 Volts, 1.3 Amps
Special Features	Digital Thermostat, Temperature Alarm, LED Light, Automatic Defrost, Door Lock, UL Certified for Outdoor Use

WARRANTY INFORMATION

Summerset warrants this product to be free from manufacturing defects and workmanship for three (3) years on the construction materials and compressor, and one (1) year for all electrical components. Labor is not included. Registration form must be submitted online within 30 days of the purchase date to validate the warranty.

Refer to the manufacturer's manual for full warranty details. Keep your proof of purchase for warranty claims.

CUSTOMER SUPPORT

For technical assistance, warranty inquiries, or to purchase replacement parts, please contact Summerset Grills customer support.

Visit the official Summerset Grills website for the most current contact information and support resources:

[Summerset Grills Store](#)