



[Manuals.plus](#) /

› [Nextbase](#) /

› Nextbase Click&Go PRO Powered Mount Instruction Manual

Nextbase NBDVRS2PM

Nextbase Click&Go PRO Powered Mount Instruction Manual

Model: NBDVRS2PM | Brand: Nextbase

INTRODUCTION

This manual provides detailed instructions for the installation, operation, and maintenance of your Nextbase Click&Go PRO Powered Mount. This mount is designed to securely hold your Nextbase Series 2 Dash Cam, offering both 3M adhesive and suction cup fitting methods for versatile placement in your vehicle. The integrated power connection allows for a wireless dash cam setup.

Key Features:

- **Dual Fitting Methods:** Includes both a 3M adhesive pad and a suction cup for flexible installation.
- **Wide Compatibility:** Compatible with Nextbase Dash Cams including 122, 222, 322GW, 422GW, 522GW, and 622GW models.
- **Magnetic Attachment:** Utilizes high-strength neodymium magnets for easy and secure attachment/removal of the dash cam.
- **Wireless Power:** Power cable connects directly to the mount, enabling a wireless connection to the dash cam.
- **Adjustability:** The 3M adhesive pads come in a pack of two for repositioning, and the suction cup allows for easy relocation.

SETUP AND INSTALLATION

Before installation, ensure your windshield is clean and dry. Choose a location that does not obstruct your view of the road or interfere with airbags.

Method 1: 3M Adhesive Pad Installation

1. **Prepare Surface:** Clean the chosen area on your windshield thoroughly with an alcohol wipe and allow it to dry completely.
2. **Apply Adhesive:** Remove the protective film from the 3M adhesive pad on the mount.
3. **Position Mount:** Firmly press the mount onto the cleaned windshield surface for at least 30 seconds. Apply pressure to ensure a strong bond.

4. **Allow Adhesion:** For optimal adhesion, allow the mount to set for at least 24 hours before attaching the dash cam or driving.



Image: The Nextbase Click&Go PRO mount showing the red 3M adhesive pad on its base.



Image: Another view of the Nextbase Click&Go PRO mount with the 3M adhesive pad.

Method 2: Suction Cup Installation

1. **Prepare Surface:** Clean the chosen area on your windshield thoroughly with an alcohol wipe and allow it to dry completely.
2. **Attach Suction Cup:** Ensure the suction cup lever is in the open position. Press the suction cup firmly against the windshield.
3. **Secure Mount:** Flip the lever to the closed position to create a vacuum seal, securing the mount to the windshield.



Image: The Nextbase Click&Go PRO mount, showing the grey foam pad which is part of the suction cup mechanism.

Power Connection

Once the mount is securely installed, connect the power cable (not included with mount, typically supplied with dash cam) directly into the power port on the mount. This allows the dash cam to receive power wirelessly when attached.

OPERATING INSTRUCTIONS

Attaching Your Dash Cam

Align the magnetic connector on the back of your Nextbase Dash Cam with the magnetic plate on the Click&Go PRO mount. The strong neodymium magnets will securely snap the dash cam into place, establishing both physical and power connections.


Video: Demonstrates how to easily attach a Nextbase Dash Cam to the Click&Go PRO Magnetic Mount.

Detaching Your Dash Cam

To remove your dash cam, gently pull it away from the magnetic mount. The magnetic connection allows for quick and easy detachment when needed.

MAINTENANCE

- **Cleaning:** Use a soft, dry cloth to clean the mount. Avoid abrasive cleaners or solvents.
- **Adhesive Pads:** If using 3M adhesive, avoid frequent removal and reapplication as this can weaken the bond.

Replacement pads are available if needed.

- **Suction Cup:** Periodically check the suction cup for dust or debris. Clean with water and allow to air dry if the suction weakens.
- **Temperature:** Extreme temperatures can affect adhesive and suction performance. Ensure the vehicle interior is at a moderate temperature during installation and for optimal long-term use.

TROUBLESHOOTING

Problem	Solution
Mount is not sticking (3M adhesive).	Ensure the windshield surface was clean and dry before application. Apply firm pressure for at least 30 seconds. Allow 24 hours for the adhesive to cure. If the issue persists, use a new 3M adhesive pad.
Mount is not sticking (suction cup).	Clean the windshield and the suction cup thoroughly. Ensure the lever is fully engaged to create a vacuum seal. Avoid oily or textured surfaces.
Dash cam not receiving power.	Verify the power cable is securely connected to the mount. Ensure the dash cam is correctly aligned and fully seated on the magnetic plate. Check the vehicle's power outlet.
Dash cam feels loose on the mount.	Ensure the dash cam is fully engaged with the magnetic plate. Check for any debris between the dash cam and the mount that might prevent a secure connection.

SPECIFICATIONS

Feature	Detail
Brand	Nextbase
Model Name	Click & Go PRO
Model Number	NBDVRS2PM
Color	Black
Mounting Type	Dashboard or Windshield (via 3M Adhesive or Suction Cup)
Compatible Devices	Nextbase Series 2 Dash Cams (122, 222, 322GW, 422GW, 522GW, 622GW)
Item Weight	40 Grams
Enclosure Material	Aluminum
Additional Features	Wireless power connection to dash cam

WARRANTY INFORMATION

This Nextbase Click&Go PRO Powered Mount comes with a **90-day warranty** from the date of purchase. This warranty covers manufacturing defects under normal use. It does not cover damage caused by misuse, accidents, unauthorized modifications, or improper installation. Please retain your proof of purchase for warranty claims.

SUPPORT

For further assistance, technical support, or to inquire about replacement parts, please visit the official Nextbase website or contact their customer service. You can find more information and contact details on the [Nextbase Store on Amazon](#).

© 2024 Nextbase. All rights reserved.