

Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

[manuals.plus](#) /

› [Glacier Bay](#) /

› [Glacier Bay Modern Single Hole Single-Handle Low-Arc Bathroom Faucet \(Model HD67732W-609005\) User Manual](#)

Glacier Bay HD67732W-609005

Glacier Bay Modern Single Hole Single-Handle Low-Arc Bathroom Faucet

MODEL: HD67732W-609005

Dual Finish: Polished Nickel and Bronze

Important Safety Information

Please read all instructions carefully before installation and use. Failure to follow these instructions may result in property damage or personal injury.

- Always turn off the main water supply before beginning any work on the faucet.
- Wear appropriate personal protective equipment, such as safety glasses.
- If you are unsure about any part of the installation, consult a qualified plumber.
- Ensure all connections are tight to prevent leaks, but do not overtighten.
- Keep small parts away from children.

Package Contents

Verify that all components are present before beginning installation.

- Single-Handle Faucet Assembly
- Deck Plate
- Drain Assembly (Polished Nickel)
- Mounting Hardware
- Hot and Cold Water Supply Lines



Image: The Glacier Bay Modern Single Hole Single-Handle Low-Arc Bathroom Faucet in its dual polished nickel and bronze finish, shown with its deck plate.

Tools Required (Not Included)

- Adjustable Wrench
- Phillips Head Screwdriver
- Plumber's Putty or Silicone Sealant
- Flashlight (optional)
- Basin Wrench (optional)

Setup and Installation

Follow these steps for proper installation of your new faucet.

1. **Prepare the Sink:** Ensure the sink surface is clean and free of debris. If replacing an old faucet, remove it and clean the area thoroughly.
2. **Install Deck Plate (Optional):** If your sink has multiple holes and you are using the deck plate, apply

a bead of plumber's putty or silicone sealant around the underside edge of the deck plate. Place the deck plate over the sink holes.

- 3. Mount the Faucet:** Insert the faucet body through the center hole of the sink (and deck plate, if used). From underneath the sink, secure the faucet with the provided mounting hardware (washer and mounting nut). Hand-tighten first, then use an adjustable wrench to snug it up, ensuring the faucet is aligned correctly.
- 4. Connect Water Supply Lines:** Attach the hot and cold water supply lines to the corresponding inlets on the faucet body. Connect the other ends to your hot and cold water supply valves. Hand-tighten, then use a wrench for a final quarter-turn. Do not overtighten.
- 5. Install Drain Assembly:**



Image: Diagram illustrating the Glacier Bay ClickInstall drain assembly. It shows inserting the horizontal rod, plugging in the lift rod, and locking the horizontal bar in place for quick installation.

The Glacier Bay ClickInstall drain assembly simplifies installation:

- Apply plumber's putty or silicone sealant to the underside of the drain flange and insert it into the sink drain hole.
 - From underneath, attach the drain body and tighten the retaining nut.
 - Insert the horizontal rod into the drain body.
 - Plug in the lift rod into the faucet body.
 - Connect the lift rod to the horizontal rod using the provided clip, ensuring proper operation.
- 6. Test for Leaks:** Once all connections are made, slowly turn on the main water supply. Check all connections for leaks. If leaks occur, tighten the connection slightly until the leak stops.

Operation

This faucet features a single-handle design for easy control of water flow and temperature.

- **Water Flow:** Lift the handle upwards to increase water flow. Push the handle downwards to decrease or turn off water flow.

- **Water Temperature:** Move the handle to the left for hot water and to the right for cold water. The handle has indicators for hot (H) and cold (C).



Image: A close-up view of the faucet handle, showing the subtle 'H' and 'C' markings for hot and cold water temperature control.



Image: The Glacier Bay faucet installed on a sink, with water flowing from its low-arc spout, demonstrating its operational state.

Maintenance

Regular cleaning and maintenance will help preserve the finish and functionality of your faucet.

- **Cleaning the Finish:** Clean the faucet with a soft, damp cloth. Avoid abrasive cleaners, harsh chemicals, or scouring pads, as these can damage the finish.
- **Aerator Cleaning:** If water flow decreases or becomes irregular, the aerator may be clogged. Unscrew the aerator from the end of the spout, clean any debris, and rinse it under water. Reattach the aerator.
- **Leak Prevention:** Periodically check under the sink for any signs of leaks. Address any leaks promptly to prevent water damage.

Troubleshooting

Refer to this section for common issues and their solutions.

Problem	Possible Cause	Solution
Low Water Flow	Clogged aerator; partially closed supply valves.	Clean the aerator. Ensure hot and cold water supply valves are fully open.

Problem	Possible Cause	Solution
Leaks from Faucet Base	Loose mounting nut; improper sealant application.	Tighten the mounting nut under the sink. Reapply plumber's putty or silicone if necessary.
Leaks from Supply Lines	Loose connections; damaged O-rings.	Tighten supply line connections. Check and replace O-rings if damaged.
Water Temperature Not Adjusting	Cartridge issue; supply lines reversed.	Verify hot and cold supply lines are connected correctly. If issue persists, the cartridge may need replacement (contact manufacturer support).

Specifications

- **Brand:** Glacier Bay
- **Model Number:** HD67732W-609005
- **Recommended Use:** Bathroom
- **Mounting Type:** Deck Mount
- **Finish Type:** Polished Nickel and Bronze
- **Material:** Ceramic (internal cartridge), Brass (handle material)
- **Number of Handles:** 1 (Single-Handle)
- **Included Components:** Faucet, Deck Plate, Drain, Handle
- **Hole Count:** 1 (Single Hole Installation)
- **Flow Rate:** 1.2 GPM (4.5 L/min) MAX (WaterSense Certified)



Image: The Glacier Bay faucet displaying the WaterSense label, indicating it meets EPA criteria for water efficiency.

Warranty and Support

For warranty information or technical support, please refer to the documentation included with your purchase or contact Glacier Bay customer service directly. Specific warranty terms and conditions may vary.

Please retain your proof of purchase for any warranty claims.