

Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

[manuals.plus](#) /

› [Mopar](#) /

› [Mopar OEM Door Sill Guards Instruction Manual for Jeep Gladiator \(Model 82215551\)](#)

Mopar 82215551

Mopar OEM Door Sill Guards Instruction Manual

Model: 82215551 for Jeep Gladiator

[Overview](#) [Setup &](#)

[Installation](#)

[Operation](#)

[Maintenance](#)

[Specifications](#)

[Troubleshooting](#)

[Warranty & Support](#)

1. PRODUCT OVERVIEW

These Mopar OEM Door Sill Guards are designed to protect the door sills of your Jeep Gladiator from scratches, scuffs, and daily wear and tear. Made from durable materials, they provide a custom fit and enhance the interior appearance of your vehicle.



Image: Mopar OEM Door Sill Guards for Jeep Gladiator.

2. SETUP & INSTALLATION

Proper installation ensures optimal performance and longevity of your door sill guards. Follow these steps carefully:

- 1. Clean the Door Sill:** Thoroughly clean the vehicle's door sill surface where the guards will be applied. Ensure it is free from dirt, dust, grease, and moisture. Use a clean cloth and a suitable automotive cleaner, then dry completely.
- 2. Test Fit:** Before removing any adhesive backing, carefully place each door sill guard in its intended position to confirm fitment and alignment. Note the orientation (front/rear, left/right).
- 3. Prepare Adhesive:** Peel off a small portion of the protective backing from the adhesive strips on the back of the guard. Do not remove the entire backing yet.
- 4. Align and Apply:** Carefully align the guard with the door sill. Once aligned, firmly press the guard into place, gradually peeling off the remaining adhesive backing as you go. Apply even pressure across the entire surface to ensure strong adhesion.
- 5. Secure:** After the guard is in place, apply firm pressure for at least 30 seconds to ensure the adhesive bonds securely to the surface. Avoid washing the vehicle or exposing the guards to excessive moisture

for 24-48 hours to allow the adhesive to fully cure.

Installation Video Guides:

Your browser does not support the video tag.

Video: This video demonstrates the usage and installation process for door sill guards, highlighting the material and adhesive strength. It shows cleaning the sill, peeling the adhesive, and pressing the guard into place for both long and short pieces.

Your browser does not support the video tag.

Video: This video showcases the SUPAREE door sill guards, emphasizing their toughness, scratch resistance, and ease of cleaning. It also provides a step-by-step guide for installation, including cleaning the surface and applying the guards.

Your browser does not support the video tag.

Video: This video demonstrates the installation of a 4-piece door sill guard kit. It shows the process of cleaning the door sill, removing the adhesive backing, and carefully positioning the guards for a secure fit.

Your browser does not support the video tag.

Video: This video provides detailed installation steps for ROWA Jeep door sill guards, including cleaning the surface, tearing the 3M tape, aligning the guards with the vehicle's groove lines, and pressing for reinforcement. It also shows the final fit with the door closed.

3. OPERATION

Once installed, the door sill guards provide continuous protection for your vehicle's entry points. They are designed to withstand regular foot traffic and prevent damage to the underlying paint and metal.

- **Enhanced Protection:** The guards act as a barrier against scratches, scuffs, and chips caused by shoes, cargo, or other objects entering and exiting the vehicle.
- **Improved Grip:** The textured surface of the guards can offer additional grip, especially in wet conditions, reducing the risk of slipping when entering or exiting the vehicle.
- **Seamless Integration:** The custom design ensures that the guards fit perfectly and do not interfere with the opening or closing of the vehicle doors.

4. MAINTENANCE

Maintaining your door sill guards is simple and helps preserve their appearance and protective qualities:

- **Regular Cleaning:** Clean the guards periodically with mild soap and water. Use a soft cloth or sponge to wipe away dirt and debris.
- **Avoid Harsh Chemicals:** Do not use abrasive cleaners, solvents, or harsh chemicals, as these can damage the material and finish of the guards.
- **Drying:** After cleaning, dry the guards thoroughly with a clean, soft cloth to prevent water spots.

Cleaning Demonstration Video:

Your browser does not support the video tag.

Video: This video demonstrates how easily the door sill guards can be cleaned with water and a cloth, showcasing their durable and low-maintenance design.

5. SPECIFICATIONS

Feature	Detail
Brand	Mopar
Model Number	82215551
Product Type	Auto Part (Door Sill Guard)
Material	Stainless Steel
Color	Black
Product Dimensions	26.52" L x 4" W
Item Weight	14.4 ounces
Fit Type	Vehicle Specific Fit (Jeep Gladiator)

Note: While product specifications list "Stainless Steel", some product videos show a flexible, rubber-like material. Please verify product material upon receipt.

6. TROUBLESHOOTING

- Adhesion Issues:** If the guards are not sticking properly, ensure the surface was thoroughly cleaned and dry before application. Ambient temperature can affect adhesive performance; ideally, install in temperatures between 68°F and 95°F (20°C and 35°C). Apply firm, even pressure during installation.
- Improper Fit:** Double-check that you have the correct guard for each door sill (front/rear, left/right) and that it is aligned correctly before pressing firmly.
- Damage/Wear:** For minor scuffs, cleaning as per maintenance instructions may suffice. For significant damage, replacement of the individual guard may be necessary.

7. WARRANTY & SUPPORT

For specific warranty information or product support, please refer to the documentation included with your purchase or contact Mopar customer service directly. Keep your proof of purchase for any warranty claims.