

Manuals+

[Q & A](#) | [Deep Search](#) | [Upload](#)

[manuals.plus](#) /

› [VANMASS](#) /

› [VANMASS Rotate Lock Suction Cup Car Phone Mount Instruction Manual](#)

VANMASS 9653fbfe-63f6-4194-b466-727169f4e024

VANMASS Rotate Lock Suction Cup Car Phone Mount Instruction Manual

PRODUCT OVERVIEW

The VANMASS Rotate Lock Suction Cup Car Phone Mount is designed to securely hold your smartphone in your vehicle. It features a robust rotate-lock suction cup mechanism for stable attachment to dashboards or windshields, and an adjustable arm for optimal viewing angles. This mount is engineered for durability and ease of use, providing a reliable solution for in-car phone access.

Key Features:

- Rotate Lock Suction Cup for secure attachment.
- Adjustable arm for customizable viewing angles.
- Compatible with various smartphone models.
- Designed for dashboard and windshield mounting.

PACKAGE CONTENTS

Please ensure all items are present before proceeding with installation:

- VANMASS Phone Holder Unit
- Rotate Lock Suction Cup Mount (for Dashboard/Windshield)
- Air Vent Clip Mount (optional attachment)
- Wet and Dry Cleaning Wipes (for surface preparation)

SETUP AND INSTALLATION

Surface Preparation

Before installing the suction cup mount, ensure the chosen surface (dashboard or windshield) is clean and dry. Dust and stains can affect adhesion.

1. Use the provided wet wipe to clean the desired flat surface.
2. Follow with the dry wipe to remove any moisture and ensure the surface is completely dry.

Dashboard/Windshield Mount Installation

Follow these steps for secure attachment of the suction cup mount:

1. Clean the central control panel or windshield thoroughly.
2. Press the suction cup firmly onto the cleaned surface for 10 seconds.
3. While maintaining pressure, rotate the bottom of the suction cup clockwise from the "UNLOCK" icon to the "LOCK" icon. Ensure it is fully rotated to the "LOCK" position for optimal performance.
4. Allow the suction cup to adhere for 15 minutes before attaching your phone for higher adhesion.

EASY TO INSTALL



Image: Easy 4-step installation guide for the suction cup mount. Steps include cleaning the surface, pressing the suction cup, rotating to lock, and allowing 15 minutes for adhesion.

Air Vent Mount Installation (Optional)

If using the air vent mount, attach the phone holder to the air vent clip mount. The clip is designed to securely fasten to most horizontal or vertical air vent fins.

1. Unscrew the nut from the back of the phone holder.
2. Place the nut onto the ball joint of the air vent clip mount.
3. Push the ball joint into the socket on the back of the phone holder.
4. Tighten the nut to secure the phone holder to the air vent clip mount.
5. Attach the air vent clip to a suitable air vent fin in your vehicle.

Attaching the Phone Holder to the Mount

Once your chosen mount (suction cup or air vent) is securely installed, attach the phone holder unit:

1. Ensure the large screw nut is placed over the ball joint of the mount arm.
2. Push the ball joint firmly into the circular socket on the back of the phone holder until it clicks into place.
3. Tighten the large screw nut clockwise to secure the phone holder at the desired angle.

OPERATING INSTRUCTIONS

Securing Your Phone

The phone holder features adjustable clamps to accommodate various phone sizes:

1. Press the release button (usually on the side or back) to open the side clamps.
2. Place your smartphone into the holder, ensuring it rests on the bottom support.
3. Gently squeeze the side clamps inward until they firmly grip your phone. The holder is suitable for phones between 4.0"-7.0".

Adjusting Viewing Angle

The mount offers flexibility for optimal viewing:

- The 360° ball joint allows you to rotate your phone to portrait or landscape orientation.
- The mechanical arm can be adjusted up to 270° and extended from 5" to 7.2" to bring your phone closer or further away.
- Loosen the adjustment knobs on the arm to change its position, then tighten them to lock the desired angle.

MAINTENANCE

Cleaning the Suction Cup

To restore the stickiness of the suction cup after prolonged use or if it gets smudged, follow these steps:

1. Rinse the bottom of the suction cup with warm water.
2. Allow the pad to air dry completely. Do not wipe with a cloth.
3. Once dry, the stickiness should be restored.



Your Beloved Deserve the Best

- 46 thousand people die each year as a result of road traffic
- There is no better gift than **Safety** !

Image: Steps to restore suction cup stickiness: rinse with warm water, let air dry, press adhesive dashboard pad, and rotate clockwise to lock.

TROUBLESHOOTING

- **Suction Cup Not Sticking:** Ensure the surface is clean, dry, and flat. Leather dashboards are not suitable for all suction cups; use on the windshield instead. Make sure the rotate-lock mechanism is fully engaged to the "LOCK" position. Clean the suction cup as per maintenance instructions.
- **Phone Holder Feels Loose:** Verify that all nuts and adjustment points are tightened securely. Ensure the ball joint is fully inserted into its socket.
- **Phone Not Fitting:** Adjust the side clamps by pressing the release button and manually expanding them to fit your phone. The holder supports phones from 4.0" to 7.0".

SPECIFICATIONS

Brand	VANMASS
Model Number	9653fbfe-63f6-4194-b466-727169f4e024
Color	Black
Mounting Type	Windshield, Dashboard, Air Vent
Compatible Devices	Smartphones (4.0"-7.0")
Item Weight	5.9 ounces

Package Dimensions	4.57 x 3.62 x 3.11 inches
Special Features	Rotatable, Adjustable Mechanical Arm

WARRANTY AND SUPPORT

For warranty information or product support, please refer to the contact details provided with your purchase or visit the official VANMASS website. Keep your purchase receipt for warranty claims.