

## Superer ADP190253D

# Superer 19V AC Charger Instruction Manual

For LG 32-inch LED LCD Monitors

## INTRODUCTION

---

This manual provides essential information for the safe and effective use of your Superer 19V AC Charger. This power adapter is designed to provide a stable power supply for compatible LG 32-inch LED LCD monitors. Please read these instructions thoroughly before use and retain them for future reference.

## SAFETY INFORMATION

---

Your Superer AC Charger is manufactured to meet nationally recognized standards for high-level electronic safety. It incorporates reliable overcharge protection to safeguard your devices.



Image: UL, FCC, and CE certifications for the power adapter, indicating compliance with safety and regulatory standards.

### Safety Certifications Overview

Certification	Description
UL Listed	Passed UL safety tests for high-level electronic safety.
FCC Approved	Meets regulated limits for ionizing radiation.
CE Marking	Meets EU safety, health, and environmental protection requirements.

- Do not expose the adapter to liquids, moisture, or extreme temperatures.
- Avoid dropping or subjecting the adapter to strong impacts.
- Do not attempt to disassemble or modify the adapter.
- Ensure the power outlet is easily accessible for disconnection if needed.

## PACKAGE CONTENTS

Verify that all items are present in the package:

- 1 x Superer 19V AC Power Adapter (Model: ADP190253D)
- 1 x Power Cord

# Adapter Details



01

Connector

02

Fastener Tape



03

Longer Wire



Image: The Superer 19V AC power adapter and its accompanying power cord.

Follow these steps to connect your Superer AC Charger to your LG monitor:

1. **Identify the correct port:** Locate the power input port on your LG 32-inch LED LCD monitor. This adapter is compatible with models such as 32MA70HY-P, 32MA68HY-P, 32MP58HQ-W, 32ML600M-B, 32MP58HQ-P, 32QK500-W, 32GK650F-B, and 32LH570B. Ensure your monitor requires 19V and does not exceed 2.53A.
2. **Connect the power cord:** Plug one end of the included power cord into the AC input port of the Superer power adapter.
3. **Connect to the monitor:** Insert the round-ended tip of the adapter's output cable into the power input port of your LG monitor.
4. **Plug into power outlet:** Connect the other end of the power cord into a standard wall power outlet (100-240V).

# Item Dimension



Image: The Superer AC charger properly connected to an LG monitor, ready for use.

## OPERATING INSTRUCTIONS

---

Once properly connected, the Superer AC Charger will provide consistent and stable power to your compatible LG monitor. No additional configuration is required for operation.




Image: A monitor setup powered by the Superer AC charger, illustrating a consistent power supply.

## MAINTENANCE

---

To ensure the longevity and optimal performance of your Superer AC Charger, follow these maintenance guidelines:

- **Cleaning:** Disconnect the adapter from the power source and monitor before cleaning. Use a soft, dry cloth to wipe the surface. Do not use liquid cleaners or abrasive materials.
- **Storage:** When not in use, store the adapter in a cool, dry place away from direct sunlight. Use the integrated fastener tape to neatly coil the cable, preventing tangles and damage.
- **Cable Care:** Avoid bending or crimping the cable excessively, especially near the connectors. Do not place heavy objects on the cable.



Image: Close-up view of the adapter's features, including the connector, fastener tape for cable management, and the extended cable length.

## TROUBLESHOOTING

---

If you encounter issues with your Superer AC Charger, refer to the following common problems and solutions:

- **No Power to Monitor:**
  - Ensure the power cord is securely plugged into both the adapter and the wall outlet.
  - Verify that the adapter's output tip is fully inserted into the monitor's power port.
  - Test the wall outlet with another device to confirm it is functional.
  - Check if the monitor's power button is on.
- **Monitor Flickers or Shuts Off:**
  - Confirm that the adapter's specifications (19V, 2.53A, 45W) match your monitor's power requirements. This adapter is not suitable for devices requiring more than 2.53A.
  - Ensure there are no loose connections.
  - Avoid using the adapter in poorly ventilated areas where it might overheat.
- **Adapter Feels Hot:**
  - It is normal for the adapter to feel warm during operation. However, if it becomes excessively hot, disconnect it immediately.
  - Ensure adequate ventilation around the adapter. Do not cover it.

## SPECIFICATIONS

---

Detailed technical specifications for the Superer 19V AC Charger:

Feature	Detail
Brand	Superer
Model Number	ADP190253D
Input Voltage	100-240V
Output Voltage	19V

Feature	Detail
Output Current	2.53A
Wattage	45W
Connector Type	Round-ended tip
Compatible Devices	LG 32-inch LED LCD Monitors (e.g., 32MA70HY-P, 32MA68HY-P, 32MP58HQ-W, 32ML600M-B, 32MP58HQ-P, 32QK500-W, 32GK650F-B, 32LH570B)
Color	BLACK
Material	Plastic
Special Feature	Reliable Overcharge Protection



Image: Chart illustrating various output power combinations and their compatibility status.



Image: Visual representation of the adapter's dimensions: Length 3.79 inches, Width 1.57 inches, Height 1.13 inches.

## WARRANTY AND SUPPORT

---

Superer stands by the quality of its products. Your AC Charger comes with the following:

- **30-Day Return Policy:** Eligible for replacement or returns within 30 days of purchase.
- **12-Month Guarantee:** The manufacturer provides an additional 12-month guarantee for replacement service.
- **1-Year Warranty:** A standard 1-year warranty covers manufacturing defects.

For any inquiries or support needs, please contact Superer customer service. We aim to provide quick feedback to any problems you may encounter.



Image: Overview of Superer's customer support, highlighting 12-month replacement service, 30-day refund, and quick problem resolution.