

SLLEA HER-48-12010

SLLEA AC Adapter for Hitron HER-48-12010 Power Supply Cord User Manual

Model: HER-48-12010

1. INTRODUCTION

This manual provides essential information for the safe and efficient use of your SLLEA AC Adapter, designed for the Hitron HER-48-12010 device. Please read these instructions carefully before use and retain them for future reference.

The SLLEA AC Adapter is engineered for reliability and safety, featuring multiple protection mechanisms to ensure stable power delivery.

- **Cable Length:** 4 feet (1.2 meters)
- **Industry Quality:** CE & FCC certified, tested by the manufacturer for durability and safety.
- **Protection Features:** Over Voltage Protection (OVP), Over Current Protection (OCP), Over Temperature Protection (OTP), Short Circuit Protection (SCP).



OVP (Over Voltage Protection)



OCP (Over Current Protection)



OTP (Over Temperature Protection)



SCP (Short Circuit Protection)



The charger is very durable and will not be damaged during transportation.



Noise



Physical noise is not emitted when charging

Image 1: SLLEA AC Adapter highlighting Over Voltage Protection (OVP), Over Current Protection (OCP), Over Temperature Protection (OTP), and Short Circuit Protection (SCP). The image also notes the charger's durability and 3-year warranty, and that it emits no physical noise during charging.

2. SETUP AND CONNECTION

Follow these steps to properly connect your AC adapter to your device and power source.

1. **Verify Compatibility:** Ensure that the output voltage and plug tip of this adapter match the requirements of your Hitron HER-48-12010 device. Incorrect voltage or plug type can damage your device.
2. **Connect to Device:** Insert the DC output plug of the adapter firmly into the power input port of your Hitron HER-48-12010 device.
3. **Connect to Power Outlet:** Plug the AC input prongs of the adapter into a standard electrical power outlet (100-240 VAC, 50/60Hz).
4. **Power On:** Once connected, your device should receive power. Refer to your device's manual for specific power-on procedures.

4FT



Image 2: Top-down view of the SLLEA AC Adapter, clearly showing the "4FT" cable length and the adapter's label with model ANU-090100A, input 100-240VAC, 0.3A, 50/60Hz, and output details.

3. OPERATING INSTRUCTIONS

The SLLEA AC Adapter is designed for straightforward operation. Once connected as described in the "Setup and Connection" section, it will provide continuous power to your compatible device.

- The adapter automatically adjusts to worldwide voltage (100-240 VAC), making it suitable for international travel.
- No user intervention is required for voltage selection.
- Ensure the adapter is placed in a well-ventilated area during prolonged use to prevent overheating.

4. MAINTENANCE AND CARE

Proper care will extend the lifespan of your AC adapter.

- **Cleaning:** Disconnect the adapter from the power outlet and your device before cleaning. Use a soft, dry cloth to wipe the exterior. Do not use liquid cleaners or solvents.
- **Ventilation:** Always ensure the adapter is in a suitable ventilating area, especially during extended use. Do not

cover it or place it on soft surfaces that can obstruct airflow.

- **Storage:** When not in use, store the adapter in a cool, dry place, away from direct sunlight and extreme temperatures. Avoid tightly winding the cable to prevent damage.
- **Handling:** Avoid dropping the adapter or subjecting it to strong impacts. Do not pull the cable to disconnect it from the outlet; always grasp the plug itself.

5. TROUBLESHOOTING

If you encounter issues with your SLLEA AC Adapter, refer to the following common solutions:

- **No Power to Device:**
 - Ensure the adapter is securely plugged into both the wall outlet and your device.
 - Check if the wall outlet is functional by plugging in another device.
 - Verify that the adapter's specifications (voltage, current, plug type) match your device's requirements.
 - Inspect the cable and plug for any visible damage. If damaged, discontinue use.
- **Adapter Overheating:**
 - Ensure the adapter is in a well-ventilated area and not covered.
 - Disconnect the adapter and allow it to cool down.
 - If overheating persists, discontinue use and contact support.

If these steps do not resolve the issue, please contact SLLEA customer support for further assistance.

6. SPECIFICATIONS

Feature	Specification
Input Voltage	100 - 240 VAC, 50/60Hz (Worldwide Use)
Cable Length	4 feet (1.2 meters)
Certifications	CE, FCC
Protection Features	OVP, OCP, OTP, SCP
Item Weight	3 ounces
Manufacturer	SLLEA
ASIN	B07T3C51VH
UPC	751332704196

7. WARRANTY AND SUPPORT

SLLEA stands behind the quality of its products.

- **Money Back Guarantee:** 30 Days
- **Free Exchange:** 60 Days (with paid return label)
- **Worry-Free Warranty:** 1080 Days (approximately 3 years)

For any questions, concerns, or warranty claims, please contact SLLEA customer support. We are here to help.

Contact Information: Please refer to your purchase documentation or the seller's information on the platform where the product was acquired (e.g., Amazon seller "SLLEA") for direct contact methods.

ASK A QUESTION ABOUT THIS MANUAL

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. [Privacy details](#).

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question