

[Manuals.plus](#) /

› [SLLEA](#) /

› SLLEA AC Power Charging Cord Instruction Manual for Duralast BP-DL500 Jump Starter

SLLEA BP-DL500

SLLEA AC Power Charging Cord Instruction Manual

For Duralast BP-DL500 Light Duty Peak 500 Amps Booster Pack Jump Starter

[Overview](#)

[Setup](#)

[Operation](#)

[Maintenance](#)
[Warranty &
Support](#)

[Troubleshooting](#)

[Specifications](#)

1. PRODUCT OVERVIEW

This manual provides essential information for the safe and effective use of your SLLEA AC Power Charging Cord. This cord is specifically designed to provide AC power input for charging compatible devices, such as the Duralast BP-DL500 Light Duty Peak 500 Amps Booster Pack Jump Starter.

Key features include:

- **Cable Length:** 5 feet (1.5 meters) for convenient reach.
- **Input:** 100 - 240 VAC 50/60Hz, suitable for worldwide voltage use.
- **Durability:** Designed for robust use, preventing easy pulling or breakage of wires.
- **Safety:** CE certified with over-heat and over-voltage protection, featuring a sturdy, thicker casing.



Figure 1: The SLLEA AC Power Charging Cord, coiled, showing both the two-prong male plug and the female receptacle.

2. SETUP INSTRUCTIONS

Before using the SLLEA AC Power Charging Cord, ensure that your Duralast BP-DL500 Jump Starter is compatible with a 2-slot AC input. This cord is designed for standard Type A outlets.

1. **Inspect the Cord:** Before each use, visually inspect the power cord for any signs of damage, cuts, or frayed wires. Do not use if damaged.
2. **Connect to Device:** Insert the female end of the SLLEA AC Power Charging Cord firmly into the AC input port of your Duralast BP-DL500 Jump Starter. Ensure a secure connection.
3. **Connect to Power Outlet:** Plug the two-prong male end of the power cord into a standard 100-240 VAC 50/60Hz wall outlet.



Figure 2: The SLLEA AC Power Charging Cord plugged into a wall outlet and connected to a Duralast 700A Peak Jump Starter, demonstrating proper setup.

Attention !

AC IN Power Charging Cord



Figure 3: Diagram illustrating the compatible two-slot female receptacle (JS-10, 10A 250V) and examples of incompatible plug types.

3. OPERATING INSTRUCTIONS

Once the SLLEA AC Power Charging Cord is securely connected to both the Duralast BP-DL500 Jump Starter and a live wall outlet, the jump starter should begin charging. Refer to your jump starter's specific manual for indicators of charging status (e.g., LED lights, display screens).

- Ensure the wall outlet is functioning correctly.
- Do not force the plug into an outlet or device.
- Disconnect the cord from the wall outlet first, then from the jump starter, once charging is complete or if the device is not in use.

4. MAINTENANCE

Proper maintenance ensures the longevity and safe operation of your SLLEA AC Power Charging Cord.

- **Cleaning:** Wipe the cord with a dry, soft cloth. Do not use liquid cleaners or immerse the cord in water.

- **Storage:** Store the cord in a cool, dry place, away from direct sunlight and extreme temperatures. Avoid tightly coiling or bending the cord sharply, which can damage internal wires.
- **Inspection:** Periodically check the cord and plugs for any signs of wear, damage, or corrosion. Replace the cord if any damage is observed.

5. TROUBLESHOOTING

Problem	Possible Cause	Solution
Device not charging.	Loose connection.	Ensure both ends of the cord are securely plugged into the wall outlet and the jump starter.
Device not charging.	Wall outlet is not live.	Test the wall outlet with another device or try a different outlet. Check circuit breaker if necessary.
Device not charging.	Damaged power cord.	Inspect the cord for visible damage. If damaged, discontinue use and replace the cord.
Cord feels hot during use.	Overload or internal issue.	Immediately unplug the cord from both the wall and the device. Do not use if it consistently overheats. Contact support if issues persist.

6. SPECIFICATIONS

Feature	Detail
Brand	SLLEA
Cable Length	5 feet (1.5 meters)
Input Voltage	100 - 240 VAC
Frequency	50/60Hz
Plug Format	Type A (US 2-prong)
Certifications	CE certified
Protection Features	Over-heat protection, Over-voltage protection
Item Weight	4 ounces
ASIN	B07TSNZ42T
UPC	760207354749

7. WARRANTY AND SUPPORT

For any questions, technical support, or warranty inquiries regarding your SLLEA AC Power Charging Cord, please contact the manufacturer directly. Refer to the product packaging or the seller's information for specific contact details.

Note: Warranty terms and conditions may vary. Please retain your proof of purchase for warranty claims.

Ask a question about this manual

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page's manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for conversion attribution. [Privacy details](#).

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question