

[Manuals.plus](#) /

› [U`King](#) /

› U`King 10W RGBW Mini Stage Pinspot Light Instruction Manual (Model ZQ-B93)

U`King ZQ-B93

U`King 10W RGBW Mini Stage Pinspot Light Instruction Manual

Model: ZQ-B93

INTRODUCTION

This manual provides detailed instructions for the safe and effective operation of your U`King 10W RGBW Mini Stage Pinspot Light. Please read this manual thoroughly before use and retain it for future reference.

SAFETY INFORMATION

- Ensure the power supply voltage matches the product's requirements.
- Do not open the housing; there are no user-serviceable parts inside. Refer all servicing to qualified personnel.
- Avoid direct eye exposure to the light beam.
- Keep the device away from water, moisture, and extreme temperatures.
- Ensure proper ventilation to prevent overheating.
- Always disconnect from power before cleaning or maintenance.

WHAT'S IN THE BOX

- U`King 10W RGBW Mini Stage Pinspot Light Unit
- Power Cord
- Mounting Bracket
- Remote Control
- Instruction Manual

PRODUCT FEATURES

- **High Power LED:** 10W RGBW LED bead (Red, Green, Blue, White).
- **Long Lifespan:** Up to 10,000 hours.
- **Control Modes:** DMX 512, Master Slave, Sound Activated, Auto.
- **Lighting Effects:** RGBW mixed color, strobe, and dimming.
- **Integrated Design:** ABS housing for temperature protection.
- **Adjustable Beam Angle:** Zoomable lens for beam adjustment.
- **Easy Installation:** Mini size with included brackets for versatile mounting.

SETUP

1. **Unpacking:** Carefully remove all components from the packaging. Inspect for any damage.
2. **Mounting Bracket Assembly:** Attach the included mounting bracket to the light unit using the provided screw. The bracket allows for direct placement on a surface or hanging from a truss.
3. **Power Connection:** Connect the power cord to the light unit and then plug it into a suitable power outlet.



Figure 1: Illustration of easy installation, showing a person mounting the light on a ceiling. The light can also be placed on the floor.

OPERATING INSTRUCTIONS

Control Panel and Digital Display

The light unit features a control panel with a 4-digit display and buttons (MENU, DOWN, UP, ENTER) for direct control and mode selection.



Cooling Fan



DMX IN / OUT



4-Digital Display



Figure 2: Detailed view of the control panel, showing DMX IN/OUT ports, the 4-digit display, and the cooling fan for optimal performance.

Remote Control Functions

The included remote control provides convenient access to various settings:

- **Power:** Turn the light ON/OFF.
- **Color Selection:** Directly select Red, Green, Blue, White, Yellow, Purple, or Cyan.
- **Modes:**
 - **Fade Mode:** Smooth transitions between colors.
 - **Jump Mode:** Instant color changes.
 - **Flash Mode:** Rapid flashing of colors.

- **Pulse Mode:** Pulsating color effects.
- **Strobe Mode:** Flashing white light effect.
- **Brightness/Speed:** Adjust the intensity of the light or the speed of dynamic modes using the '+' and '-' buttons.

Video 1: Demonstrates the U`King Pinspot Light's RGBW 10W LED beam in various colors and patterns, showcasing its dynamic lighting capabilities.

Beam Adjustment (Zoomable)

The front lens of the pinspot light is zoomable, allowing you to adjust the beam angle to achieve a tighter or wider light spread. Rotate the front ring to modify the beam focus.



Figure 3: Visual representation of the zoomable lens mechanism and the physical dimensions of the pinspot light.



Figure 4: Comparison illustrating the wider 12° beam angle of the U`King pinspot light compared to a typical 9° beam.

DMX 512 Control

For advanced control, connect the light to a DMX controller using standard DMX cables. Refer to your DMX controller's manual for specific programming instructions. The light supports DMX 512 protocol for integration into professional lighting setups.

Video 2: Showcases the high-power 10W LED bead with Red, Green, Blue, and White colors, highlighting its material quality and long lifespan.

MAINTENANCE

- Clean the lens regularly with a soft, lint-free cloth to maintain optimal light output.
- Do not use abrasive cleaners or solvents.
- Periodically check the power cord for any signs of damage.
- Ensure the cooling fan is free from dust and obstructions.

TROUBLESHOOTING

- No Power:** Check if the power cord is securely plugged into both the light unit and the power outlet. Verify the outlet is functional.
- Light Not Responding to Remote:** Ensure the remote's battery is functional and there are no obstructions between the remote and the light's sensor.
- Overheating:** Ensure the cooling fan is clear and the unit has adequate ventilation. If overheating persists, discontinue use and contact support.

SPECIFICATIONS

Brand	U`King
Model Number	ZQ-B93
Light Source Type	Light Emitting Diode (LED)
Light Source Wattage	10 Watts
Number of Light Sources	4 (RGBW)
Beam Angle	25 Degrees
Control Modes	DMX 512, Master Slave, Sound Activated, Auto
Material	Acrylonitrile Butadiene Styrene (ABS)
Item Weight	1 pounds (16 ounces)
Product Dimensions	14"L x 8"W x 8"H
Power Source	Corded Electric
UPC	745695300300

WARRANTY AND SUPPORT

For warranty information or technical support, please refer to the contact details provided with your purchase documentation or visit the official U`King website. Keep your proof of purchase for warranty claims.

ASK A QUESTION ABOUT THIS MANUAL

Ask about setup, troubleshooting, compatibility, parts, safety, or missing instructions. Manuals+ will review the question and use this page’s manual context to help answer it.

Name

Anonymous

Email

you@example.com

After a successful submission, we securely hash the supplied account or form email before sending it to Microsoft Advertising for

conversion attribution. [Privacy details](#).

Question

Example: How do I reset this device or fix this error?

Details

Model number, symptoms, what you tried, or the section of the manual you are using.

Submit question

Open the live page

<https://manuals.plus/asin/B07VT8YG9D>

More documents and user manuals: <https://manuals.plus/>